

	FM TRANSCEIVER UV-3R 136 ... 174 MHz, 400 ... 520 MHz Baofeng	PMR RADIO MOTOROLA CL8446 446.0 MHz ... 446.2 MHz	SET OF 2 PMR RADIOS MOTOROLA-TA2/BLUE 446.1 MHz ... 446.2 MHz	SET OF 2 PMR RADIOS MOTOROLA-TS2/BLUE 446.1 MHz ... 446.2 MHz	SET OF 2 PMR RADIOS MOTOROLA-TS2/RED 446.1 MHz ... 446.2 MHz	SET OF 2 PMR RADIOS MOTOROLA-TS2/EXTREME 446.1 MHz ... 446.2 MHz	SET OF 2 PMR RADIOS MOTOROLA-TS2/H2O 446.1 MHz ... 446.2 MHz	PMR RADIO MOTOROLA XT-460 446.0 MHz ... 446.2 MHz	INTERFACE FOR DIGITAL BROADCASTING: DIGVOX-2V2	COMMUNICATION CABLE DIGICAB-1 TO THE DIGVOX-2 INTERFACE DELTA	RADIOTELEPHONE PROGRAMMING INTERFACE UV-USB Baofeng
											
	30.82 EUR 30.82 EUR	147.65 EUR 147.65 EUR	25.27 EUR 25.27 EUR	56.31 EUR 56.31 EUR	55.84 EUR 55.84 EUR	87.96 EUR 87.96 EUR	105.87 EUR 105.87 EUR	168.36 EUR 168.36 EUR	21.54 EUR 21.54 EUR	20.85 EUR 20.85 EUR	8.00 EUR 8.00 EUR
In package			2 pcs	2 pcs	2 pcs	2 pcs	2 pcs				
Device type									Passive		
Frequency range	136 ... 174 MHz, 400 ... 520 MHz; 65.0 ... 108.0 MHz - FM	446.0 MHz ... 446.2 MHz	446.1 MHz ... 446.2 MHz	446.1 MHz ... 446.2 MHz	446.1 MHz ... 446.2 MHz	446.1 MHz ... 446.2 MHz	446.1 MHz ... 446.2 MHz	446.0 MHz ... 446.2 MHz			
Connectors type	—	—	—	—	—	—	—	—	• PC AUDIO : 2x Jack 3.5 mm socket. • TO RADIO : 4x detachable cable terminals		
Supported operating systems	—	—	—	—	—	—	—	—	—		Windows
Connectors	—	—	—	—	—	—	—	—	—	1 pcs Jack TRS 3.5 mm + 1 pcs Jack TRS 2.5 mm (to the radiotelephone) ; 4 pcs detachable cable terminals (to the DIGVOX-2 device)	1 pcs USB (to PC) 1 pcs K type plug (to the radiotelephone)
Compatibility	—	—	—	—	—	—	—	—	—	Radios with K-type connector	Baofeng / Wouxun
PTT output	—	—	—	—	—	—	—	—	• Open Collector (OC) type max. 30 V / 300 mA		
Length of the cable	—	—	—	—	—	—	—	—	20 ms	50 cm	1 m
PTT activation time	—	—	—	—	—	—	—	—	5 ms		
PTT off time	—	—	—	—	—	—	—	—	250 mV RMS		
Minimum value of the audio signal from the sound card	—	—	—	—	—	—	—	—	600 V		
Galvanic isolation	—	—	—	—	—	—	—	—			
Frequency step	2.5 kHz, 5 kHz, 6.25 kHz, 10 kHz, 12.5 kHz, 20 kHz, 25 kHz, 50 kHz	12.5 kHz	12.5 kHz	12.5 kHz	12.5 kHz	12.5 kHz	12.5 kHz	12.5 kHz	12.5 kHz		
Number of memory channels	128	16	16	16	16	16	8	16			
Tone	1750 Hz	87 Hz									
Output power	max. 5 W	0.5 W	0.5 W	0.5 W	0.5 W	0.5 W	0.5 W	0.5 W			
Antenna connector	SMA	—	—	—	—	—	—	—			
Speaker built-in	1 W	0.5 W	✓	✓	✓	✓	✓	✓			
Main features									• It allows you to connect any VHF/UHF or KP radio to a computer • Works very well with handheld radios such as Baofeng • Provides full and complete galvanic isolation between radio and computer (600V) • It does not require an external power supply • No need for a serial, parallel or USB port - the connection to the computer is done only through the audio input/output paths of the sound card • Works with most computer applications intended for digital broadcasting, e.g. Packet, PSK31, RTTY, SSTV, FAX • It works very well with the Winlink Express application (electronic mail using radio waves), which allows you to send messages in the absence of Internet via a gateway (e.g. Poznań SR3WLK) or directly (peer-to-peer)		
Function offset (for repeater access)	✓	—	—	—	—	—	—	—			
Selective call	✓	✓	—	✓	✓	✓	✓	✓			
Operation temp	✓	—	—	✓	✓	✓	✓	✓	-20 °C ... 55 °C		
Keyboard lock	✓	—	—	✓	✓	✓	✓	✓			
Modulation type	F3E (FM)	—	F3E (FM)	F3E (FM)	F3E (FM)	F3E (FM)	F3E (FM)	F3E (FM)			
Operation modes	Simplex / Half Duplex	—	—	—	—	—	—	—			
Antenna impedance	50 Ω	—	—	—	—	—	—	—			
Main features	• CTCSS and DTC tones - normal and invert mode • Listening to two frequencies at the same time (Dual Watch function) • Voice operated transmission activation function (VOX) • Power-saving mode • Built-in LED flashlight • Programmable using the device keyboard or computer • Switching the transmit power level : High / Medium / Low	• Channel scan function • Voice operated transmission activation function (VOX/VOX) • Call sound - A choice of 6 sounds • Escalate Call - initiate an important call or alert users on another channel to immediately communicate a message in high-risk situations • Customizable channel announcements • 219 private codes - PL, DPL • 15-level volume adjustment with Mute function • Operation status LED indicator - 8 colors (Channel, Operation mode, Battery charge level) • Battery saving function • Backup time - 18 h • Charger included • Housing - EIA 603 compliance (polycarbonate) • Compliance with MIL 810 C,D,E,F,G,H standards • Software CPS	• Battery charge indicator • Large, readable LCD display with backlight • Support for CTCSS and DCS codes • Channel scan function • Possibility to scan 2 channels at the same time • Voice operated transmission activation function (VOX) • Call sound • End of broadcast sound • Easy pairing function	• Battery charge indicator • Large, readable LCD display with backlight • Support for CTCSS and DCS codes • Channel scan function • Possibility to scan 2 channels at the same time • Voice operated transmission activation function (VOX) • Call sound • End of broadcast sound • Easy pairing function	• Battery charge indicator • Large, readable LCD display with backlight • Support for CTCSS and DCS codes • Channel scan function • Possibility to scan 2 channels at the same time • Voice operated transmission activation function (VOX) • Call sound • End of broadcast sound • Easy pairing function	• Battery charge indicator • Large, readable LCD display with backlight • Support for CTCSS and DCS codes • Channel scan function • Possibility to scan 2 channels at the same time • Voice operated transmission activation function (VOX) • Call sound • End of broadcast sound • Easy pairing function • The housing design makes the device float on the water • Emergency alert button	• Battery charge indicator • Large, readable LCD display with backlight • Support for CTCSS and DCS codes • Channel scan function • Scanning lists • Voice operated transmission activation function (VOX/VOX) • Call sound - A choice of 6 sounds • Programmable buttons • Battery saving function • Microphone sensitivity adjustment • Voice scrambling for extra privacy - SCRAMBLER • Customizable channel announcements • Programmable channel alias • Housing - EIA 603 compliance (polycarbonate) • Compliance with MIL 810 C,D,E,F,G standards				
Index of Protection*		IP52									
Color	Black	Black	Blue + Black	Black + Blue	Black + Red	Black + Orange	Yellow + Black	Black			
Power supply	Rechargeable 7.4V / 1800mAh battery, the set includes a 10V / 0.5A power adapter	3 x 1.5 V Li-Ion battery 1800 mAh (included)	3 x 1.5V, type AAA/LR03 battery (not included)	3 x 1.2 V Ni-MH batteries (included) or 3 x 1.5V, type AA/LR6/FR6 battery	3 x 1.2 V Ni-MH batteries (included) or 3 x 1.5V, type AA/LR6/FR6 battery	3 x 1.2 V Ni-MH batteries (included) or 3 x 1.5V, type AA/LR6/FR6 battery	3 x 1.2 V Ni-MH batteries (included) or 3 x 1.5V, type AA/LR6/FR6 battery	3 x 1.2 V Ni-MH batteries (included) or 3 x 1.5V, type AA/LR6/FR6 battery			
Weight	0.2 kg	0.15 kg	0.08 kg	0.15 kg	0.15 kg	0.15 kg	0.23 kg	0.26 kg	0.94 kg	0.04 kg	0.04 kg
Dimensions	99 x 58 x 33	153 x 51 x 23 mm	136 x 48 x 27	165 x 54 x 31 mm	165 x 54 x 31 mm	181 x 56 x 33	178 x 61 x 40	187 x 58 x 42 mm	118 x 30 x 59		
Manufacturer / Brand	Baofeng	Motorola	Motorola	Motorola	Motorola	Motorola	Motorola	Motorola	DELTA	DELTA	Baofeng
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel.:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00