

	PLUG BNC-W/SS-HAND	PLUG BNC-W/SS-HAND*P10	PLUG BNC-W/70-HAND	PLUG BNC-W/SKR-RG59 TWIST-ON	PLUG BNC-W/SKR-MET*P10	PLUG BNC-W/SKR- MET*P10Q	PLUG BNC-W/SKR- PLAST*P10	PLUG BNC-W/SKR- PLAST*P10Q	ANGULAR PLUG BNC- W/SKR/KAT	RUBBER BUSH BNC-WP*P10
										
	0.45 EUR 0.45 EUR	3.95 EUR 3.95 EUR	0.47 EUR 0.47 EUR	0.35 EUR 0.35 EUR	3.67 EUR 3.67 EUR	29.36 EUR 29.36 EUR	3.98 EUR 3.98 EUR	31.82 EUR 31.82 EUR	0.46 EUR 0.46 EUR	1.10 EUR 1.10 EUR
In package	...	10 pcs The price for package	...	...	10 pcs The price for package	100 pcs The price for package	10 pcs The price for package	100 pcs The price for package	...	10 pcs The price for package
Type	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Straight plug	BNC Angular plug	Bush
Attachment of connector elements	—	—	—	Twisting on	Twisting on	Twisting on	Twisting on	Twisting on	Crimping	Pressed
Shield fastening	Twisting-on	Twisting-on	Twisting-on	Twisting on	Crimping	Crimping	Crimping	Crimping	Crimping	—
Wire mounting	Pressing	Pressing	Pressing	Soldering	Twisting on	Twisting on	Twisting on	Twisting on	Twisting on	—
Application	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable
Cable diameter	max. 5.5 mm	max. 5.5 mm	max. 7.0 mm	max. 5.9 mm	max. 7.2 mm	max. 7.2 mm	max. 7.2 mm	max. 7.2 mm	max. 7.2 mm	max. 7.2 mm
Impedance	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	—
Material	Metal	Metal	Metal	Metal	Metal	Metal	Metal / PET	Metal / PET	Metal / PET	Rubber
Example of application	• YAP • K-60 • RG59 • YWDX	• YAP • K-60 • RG59 • YWDX	• RG6 • HFEK • Triset113	• RG59 • VWDIX	• RG6 • HFEK • Triset113	• RG6 • HFEK • Triset113	• RG59 • YWDX	• RG59 • VWDIX	• RG59 • VWDIX • RG6 • HFEK • Triset113	—
Main features	• Wide frequency range • Corrosion resistance • Very easy and quick installation without any tools	• Wide frequency range • Corrosion resistance • Very easy and quick installation without any tools	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance	• Wide frequency range • Corrosion resistance • Very easy and quick assembly	Protects against weather conditions
Weight	0.011 kg	0.011 kg	0.010 kg	0.010 kg	0.012 kg	0.012 kg	0.01 kg	0.010 kg	0.020 kg	0.002 kg
Dimensions	Ø 14 mm x 36 mm	Ø 14 mm x 36 mm	Ø 14 mm x 35 mm	Ø 20 mm x 20 mm	Ø 14 mm x 60 mm	Ø 14 mm x 56 mm	Ø 15 mm x 59 mm	Ø 15 mm x 55 mm	Ø 40 mm x 40 mm	Ø 11 mm x 44 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00