

	FILTER LTE TF-001	FILTER LTE TF-005	FILTER LTE TF-007A
			
	14.97 EUR 14.97 EUR	14.20 EUR 14.20 EUR	37.03 EUR 37.03 EUR
Working frequency band	5 ... 1000 MHz	5 ... 1000 MHz	5 ... 1000 MHz
Stop-band	694 ... 1000 MHz	694 ... 1000 MHz	240 ... 470 MHz 694 ... 3000 MHz
Return loss	> 60 dB @ 733 MHz > 60 dB @ 1000 MHz	> 50 dB @ 733 MHz > 50 dB @ 1000 MHz	> 23 dB @ 350 MHz > 25 dB @ 703 MHz > 25 dB @ 733 MHz > 35 dB @ 1000 MHz
Insertion loss	< 3 dB @ 5 ... 470 MHz < 3.5 dB @ 694 MHz	< 3 dB @ 5 ... 470 MHz < 3.5 dB @ 694 MHz	< 0.3 dB @ 5 MHz < 2 dB @ 240 MHz < 3 dB @ 470 MHz < 4 dB @ 694 MHz
Main features	• It is equipped with 24V/100mA DC pass • Shielded • F type connectors • Mast mounting diameter	• It is equipped with 24V/100mA DC pass • Shielded • F type connectors • Mast mounting diameter	• It is equipped with 24V/100mA DC pass • Shielded • F type connectors • Mast mounting diameter
Weight	0.17 kg	0.07 kg	0.17 kg
Dimensions	89 x 107 x 43 mm	79 x 27 x 18 mm	89 x 107 x 43 mm
Guarantee	2 years	2 years	2 years