

	CONVERTER AV/HDMI	CONVERTER HDMI/AV	ADAPTER DP-W/HDMI-G	ADAPTER DP-W/HDMI-W-L8M	ADAPTER DVI-D/HDMI-W-2.0M-UNITEK	CONVERTER HDMI/VGA+AU-ECO	CONVERTER HDMI/VGA+AU-ECO-3	ADAPTER MDP-W/HDMI-G	ADAPTER USB-C/HDMI	CONVERTER VGA+AU/HDMI-ECO	CONVERTER TO COMPUTER MONITORS VGA-1920F	VGA-VIDEO CONVERTER AX-2560	VGA-VIDEO CONVERTER AX-2560F	CONVERTER DA/AU-3	CONVERTER HV/HDMI+HV-V2
															
	8.80 EUR 8.80 EUR	8.03 EUR 8.03 EUR	5.26 EUR 5.26 EUR	5.91 EUR 5.91 EUR	5.51 EUR 5.51 EUR	6.62 EUR 6.62 EUR	6.48 EUR 6.48 EUR	5.25 EUR 5.25 EUR	18.74 EUR 18.74 EUR	8.11 EUR 8.11 EUR	25.11 EUR 25.11 EUR	13.39 EUR 13.39 EUR	14.92 EUR 14.92 EUR	9.77 EUR 9.77 EUR	82.24 EUR 82.24 EUR
Connectors	...	...	...	...	DVI - plug HDMI - plug	...	...	...	...	...	...	...	...	...	...
Inputs	Composite Video (CVBS) - 1 pcs CINCH Audio - 2 pcs Cinch (L/R)	1 pcs HDMI	DisplayPort - plug	DisplayPort - plug	...	HDMI	HDMI	Mini DisplayPort plug	USB-C - plug	• VGA, • Audio (Jack stereo socket)	...	...	...	• 1 pcs Coaxial, (CINCH) • 1 pcs Optical TOSLINK	...
Input	...	...	...	...	...	...	...	...	...	...	...	• Video composite (BNC socket), • S-VIDEO, • VGA (bypass)	VGA	VGA	1 x BNC - AHD / HD-CVI / HD-TVI / CVBS @ 8 Mpx (max)
Outputs	1 pcs HDMI	Composite Video (CVBS) - 1 pcs CINCH Audio - 2 pcs Cinch (L/R)	HDMI - socket	HDMI - plug	...	• VGA, • Audio (Jack stereo socket)	• VGA, • Audio (Jack stereo socket)	HDMI socket	HDMI - socket	HDMI	...	...	...	• Audio (2 x cinch - L/R), • Headphones output - Jack 3.5 mm socket	...
Supported HDMI input resolutions	...	...	...	...	...	720p 1080p	480p 576p 720p 1080p	...	...	...	...	...	...	...	...
Power connector	...	...	...	...	...	...	...	...	...	...	...	...	...	5.5 / 2.1 mm	...
Supported audio formats	...	...	...	...	...	...	...	...	...	...	...	...	...	LPCM (stereo) channels	...
Input signal possible standards	...	...	...	...	...	...	...	...	...	...	• PAL NTSC, • VGA (bypass)	...	...	...	...
DisplayPort standard	...	...	1.2	1.2	...	...	...	1.1a	...	...	...	...	...	...	...
Bandwidth	...	...	...	...	...	...	...	max. 225 MHz	...	...	...	...	...	...	...
Sampling frequency	...	...	...	...	...	...	...	...	...	...	...	...	...	32, 44.1, 48, 96 kHz	...
Bitrate	...	...	≤ 17.28 Gb/s Video ≤ 21.6 Gb/s TDMS	≤ 17.28 Gb/s Video ≤ 21.6 Gb/s TDMS	≤ 18 Gb/s Video	...	...	≤ 6.75 Gb/s Video ≤ 10.8 Gb/s TDMS	...	...	...	...	...	...	...
Number of displayed colors	...	...	48 bpp	48 bpp	...	...	...	36 bpp	...	...	...	...	...	...	...
Output	...	...	...	...	...	...	...	...	...	...	VGA (bypass)	Video composite (Cinch), S-VIDEO, VGA (bypass)	Video composite (BNC socket), S-VIDEO, VGA (bypass)	...	• 1 x BNC - AHD / HD-CVI / HD-TVI / CVBS @ 8.3 Mpx (max), • 1 x HDMI @ 1080p 60 fps
Output signal possible standards	...	...	...	...	...	...	...	...	...	...	...	PAL / NTSC	PAL / NTSC	...	PAL / NTSC
Audio support	...	...	8 Channels / 768 kHz / 24 bit	8 Channels / 768 kHz / 24 bit	...	...	...	8 Channels / 192 kHz / 24 bit	✓	...	...	...	...	...	...
Supported VGA output resolutions	...	...	...	...	...	1600 x 1200 1920 x 1080	640 x 480 800 x 600 1024 x 768 1280 x 720 1280 x 800 1280 x 1024 1400 x 1050 1440 x 900 1600 x 1200 1680 x 1050 1920 x 1080	...	...	...	...	...	...	...	...
Manufacturer / Brand	...	...	...	...	UNITEK	...	...	...	...	...	...	...	...	...	...
Main features	...	...	• Plug & Play • Standby mode detection • Standby mode enter into sleep mode automatically	• Plug & Play • Standby mode detection • Standby mode enter into sleep mode automatically	...	...	...	• Plug & Play • Standby mode detection • Standby mode enter into sleep mode automatically	• Plug & Play, • Operation modes : Mirror, Extend, • HDR support	...	...	...	...	...	...
Color	...	...	...	...	...	...	Device is available in two versions depending on delivery (it is not subject to selection) : Black or White	...	...	...	...	...	...	...	...
Main features	...	...	...	...	...	...	...	...	...	...	...	...	...	...	• In the case of no input signal, the device displays a test chart (color bars) on the connected screen • Automatic recognition of the resolution - LED indication • USB cable 0.9 m (included) • BNC cable 0.9 m (included)
Supported resolutions	• PAL / NTSC - Composite Video (CVBS) • 720p @ 60, 1080p @ 60 - HDMI	• HDMI : 3840 x 2160 4K @ 30 Hz , 2560 x 1440 @ 30 Hz , 1920 x 1080 @ 50/60 Hz , 1600 x 1200 @ 60 Hz , 1280 x 1024 @ 60 Hz , 1360 x 768 @ 50/60 Hz , 1024 x 768 @ 60 Hz , 1280 x 720 @ 50/60 Hz	max. 4K UHD	max. 4K UHD	max. 4K UHD - DVI to HDMI conversion max. 1080p - HDMI to DVI conversion	...	...	480i 480p 576i 576p 720p 1080p	max. 4K UHD @ 60 Hz	...	• 4:3 800 x 600 @ 60/75 Hz 1024 x 768 @ 60 Hz 1280 x 1024 @ 60 Hz 1600 x 1200 @ 60 Hz • 16:9 / 16:10 1280 x 720 @ 60 Hz 1366 x 768 @ 60 Hz 1440 x 900 @ 60 Hz 1680 x 1050 @ 60 Hz 1920 x 1080 @ 60 Hz 1920 x 1200 @ 60 Hz	640 x 480, 800 x 600, 1024 x 640, 1024 x 768, 1280 x 768, 1280 x 800, 1280 x 1024, 1280 x 960, 1360 x 768, 1440 x 900, 1600 x 1200, 1680 x 1050, 1768 x 992, 1792 x 1344, 1600 x 1440, 1920 x 1080, 1920 x 1200, 1920 x 1440, 2048 x 1152, 2048 x 1280, 2048 x 1536, 2560 x 1600	800 x 600, 1024 x 768, 1280 x 1024, 1366 x 768, 1440 x 900, 1600 x 900, 1600 x 1200, 1680 x 1050, 1920 x 1080, 1920 x 1200, 2048 x 1536, 2560 x 1600	...	• HDMI - 1080p • BNC - 8.3 Mpx (max)
OSD menu	...	• Composite Video (CVBS) : PAL / NTSC	...	...	...	...	...	...	...	...	✓	✓	✓	...	...
Possible settings	...	...	...	...	...	...	...	...	...	...	• brightness, contrast, saturation, hue - the settings are saved after power off • PIP - Picture In Picture	vertical and horizontal size, vertical and horizontal position brightness, contrast, saturation sharpness, hue Monitor type correction - LCD/CRT	• vertical and horizontal size, vertical and horizontal position • brightness, contrast, saturation sharpness, hue • Monitor type correction - LCD/CRT	...	...
Supported VGA input resolutions	...	...	...	...	...	...	...	...	...	1024 x 768 @ 60 / 70 / 75 / 85 Hz 1152 x 864 @ 75 Hz 1280 x 720 @ 60 Hz 1280 x 768 @ 60 Hz 1280 x 800 @ 60 Hz 1280 x 960 @ 60 Hz 1280 x 1024 @ 60 Hz 1360 x 768 @ 60 Hz 1440 x 900 @ 60 Hz 1600 x 1200 @ 60 Hz 1680 x 1050 @ 60 Hz 1920 x 1080 @ 60 Hz	...	...	...	...	...

Supported HDMI output resolutions	...	...	...	...	...	...	...	...	...	...	1024 x 768 @ 60 / 70 / 75 / 85 Hz 1152 x 864 @ 75 Hz 1280 x 720 @ 60 Hz 1280 x 768 @ 60 Hz 1280 x 800 @ 60 Hz 1280 x 960 @ 60 Hz 1280 x 1024 @ 60 Hz 1360 x 768 @ 60 Hz 1440 x 900 @ 60 Hz 1440 x 1050 @ 60 Hz 1680 x 1050 @ 60 Hz 1600 x 1200 @ 60 Hz 1920 x 1080 @ 60 Hz	...	...	...	...	...
HDCP	—	—	...	...	...	—	—	...	...	...	...	...	...	...	...	
Maximal range of HDMI transmission	...	...	...	...	...	...	...	...	...	...	15 m	...	...	...	...	
Power supply	5 V DC from USB port	5 V DC from USB port (optional)	5 V DC - from HDMI port	5 V DC - from HDMI port	...	5 V DC (power adapter not included)	5 V DC - from HDMI port	5 V DC - from HDMI port	5 V DC - from USB-C port	5 V DC - mini USB socket (power adapter not included)	5 V / 1 A (power adapter included)	USB or power adapter 5 V DC (power adapter not included)	USB or power adapter 5 V DC (power adapter not included)	5 V DC / 0.5 A	5 V DC / 2 A (power adapter included)	
Weight	0.04 kg	0.04 kg	0.026 kg	0.06 kg	0.150 kg	0.01 kg	0.036 kg	0.024 kg	0.012 kg	0.085 kg	0.07 kg	0.064 kg	0.07 kg	0.07 kg	0.18 kg	
Dimensions	68 x 56 x 20 mm	68 x 56 x 20 mm	49 x 20 x 12 mm - DisplayPort plug 45 x 22 x 12 mm - HDMI socket ~ 15 cm (cable length)	49 x 20 x 12 mm - DisplayPort plug 55 x 22 x 12 mm - HDMI socket ~ 180 cm (cable length)	53 x 39 x 14 mm - DVI plug 47 x 18 x 12 mm - HDMI plug ~ 200 cm (cable length)	55 x 25 x 17 mm	45 x 45 x 15 mm	45 x 45 x 15 mm ~ 18 cm (cable length)	69 x 26 x 16 mm	64 x 55 x 20 mm	100 x 65 x 26 mm	100 x 62 x 26 mm	100 x 67 x 26 mm	64 x 42 x 27 mm	108 x 95 x 25 mm	
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00