

	OPTICAL RETRANSMITTER GL-FIBRE-020/RPT	SATELLITE OPTICAL RECEIVER GL-FIBRE-JRS- GIU/MKII QUATRO	SPLITTER RL-2/1E-SAT-RL	SPLITTER RL-2/1E-SAT-SIG	SPLITTER RL-3/1E-SAT-OPTI OPTICUM	SPLITTER RL-3/1E-SAT-SIG	SPLITTER RL-4/1E-SAT-OPTI OPTICUM	SPLITTER RL-4/1E-SAT-OPTI OPTICUM	SPLITTER RL-4/1E-SAT-SIG	SPLITTER RL-6/1E-SAT-OPTI OPTICUM	SPLITTER RL-6/1E-SAT-SIG	TV/SAT SPLITTER SD-504	TV/SAT SPLITTER SD-515	TV/SAT SPLITTER SD-904 TERRA	TV/SAT SPLITTER SDQ-508 TERRA	TV/SAT SPLITTER SDQ-908 TERRA
																
	310.29 EUR 310.29 EUR	129.47 EUR 129.47 EUR	3.28 EUR 3.28 EUR	2.39 EUR 2.39 EUR	1.77 EUR 1.77 EUR	3.23 EUR 3.23 EUR	1.81 EUR 1.81 EUR	3.76 EUR 3.76 EUR	6.55 EUR 6.55 EUR	3.67 EUR 3.67 EUR	6.75 EUR 6.75 EUR	40.05 EUR 40.05 EUR	44.98 EUR 44.98 EUR	71.85 EUR 71.85 EUR	84.81 EUR 84.81 EUR	156.74 EUR 156.74 EUR
Number of inputs	1 pcs FC/UPC	...	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	...	...	9 pcs	5 pcs	9 pcs
Number of outputs	2 pcs FC/UPC	...	2 pcs	2 pcs	3 pcs	3 pcs	4 pcs	6 pcs	6 pcs	8 pcs	8 pcs	...	...	18 pcs	20 pcs	36 pcs
Attenuation	-12 dBm ... -3 dBm	...	3.5 dB	6 dB	8 dB	8 dB	< 11.9 dB	< 15.9 dB	12 dB	< 15.9 dB	15 dB	...	...	...	...	...
Input signal level	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Output signal level	7 dBm	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Possibility to pass the DC voltage to the preamplifier	...	...	✓	✓	✓	✓	✓	✓	✓	✓	✓	...	...	...	...	...
Shielding	...	...	✓	✓	✓	✓	✓	✓	✓	✓	✓	...	...	...	...	...
Impedance	...	...	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	...	...	...	...	...
Frequency range	...	• 88 ... 108 MHz - FM, • 174 ... 240 MHz - DAB, • 470 ... 790 MHz - DVB-T/T2, • 950 ... 2150 MHz - SAT	5 ... 2400 MHz	5 ... 2300 MHz	5 ... 2450 MHz	5 ... 2300 MHz	5 ... 2450 MHz	5 ... 2450 MHz	5 ... 2300 MHz	5 ... 2450 MHz	5 ... 2300 MHz	950 ... 2400 MHz - SAT, 5 ... 862 MHz - TV	950 ... 2400 MHz - SAT, 5 ... 862 MHz - TV	• 950 ... 2400 MHz - SAT, • 5 ... 862 MHz - RTV	• 950 ... 2400 MHz - SAT, • 5 ... 862 MHz - RTV	• 950 ... 2400 MHz - SAT, • 5 ... 862 MHz - RTV
Connection loss	...	...	...	...	...	...	...	...	...	...	...	4 dB - SAT, 4 dB - TV	15 ... 16 dB - SAT, 13 ... 17 dB - TV	4 dB - SAT, 4 dB - RTV	• 8 dB - SAT • 8 dB - RTV	• 8 dB - SAT • 8 dB - RTV
Housing	...	...	• For outdoor use • Splash-proof casing • Plastic	...	...	...	...	...	...	...	...	...	...	...	...	...
Isolation between outputs	...	...	...	16 dB	...	16 dB	...	...	...	...	...	> 30 dB	> 30 dB	> 30 dB	> 30 dB	30 dB
Mount	...	...	To the mast, To the wall	...	...	...	...	...	...	...	...	...	...	...	...	...
DC-transition	...	...	...	...	...	...	...	...	...	...	...	max. 2 A	max. 2 A	max. 2 A	max. 2 A	max. 2 A
Main features	...	...	Recommended for UNICABLE system - single- cable technology	...	...	...	...	...	...	...	...	...	...	The die-cast metal body provides effective shielding and high mechanical resistance	The die-cast metal body provides effective shielding and high mechanical resistance	• 8 path SAT + RTV terrestrial splitter • The die-cast metal body provides effective shielding and high mechanical resistance
Operation temp	-10 °C ... 50 °C	...	...	...	...	...	...	...	...	...	...	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C
SAT RF outputs	...	• 18 V / 22 kHz - HH • 13 V / 22 kHz - VH • 18 V / 0 kHz - HL • 13 V / 0 kHz - VL	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Manufacturer / Brand	...	...	...	...	OPTICUM	...	OPTICUM	OPTICUM	...	OPTICUM	...	...	...	TERRA	TERRA	TERRA
Output level	...	• 79 dBµV - SAT, • 68 dBµV - DVB-T/T2	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Optical wavelength	1100 nm ... 1650 nm	1100 nm ... 1650 nm	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Optical connector type	...	FC/PC	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Power supply	20 V DC / 150 mA (F connector) - Power adapter included	10.5 V ... 21 V DC	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Weight	0.17 kg	0.17 kg	0.073 kg	0.09 kg	0.04 kg	0.1 kg	0.04 kg	0.1 kg	0.16 kg	0.1 kg	0.16 kg	0.39 kg	0.4 kg	0.75 kg	0.77 kg	1.5 kg
Dimensions	108 x 76 x 26 mm	121 x 80 x 26 mm	77 x 68 x 44 mm	60 x 50 x 25 mm	73 x 46 x 17 mm	85 x 55 x 20 mm	73 x 46 x 17 mm	120 x 57 x 23 mm	120 x 60 x 20 mm	120 x 57 x 24 mm	120 x 60 x 20 mm	126 x 135 x 30 mm	126 x 135 x 30 mm	126 x 135 x 50 mm	267 x 135 x 30 mm	267 x 135 x 51 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00