

	<a href="#">SAT AMPLIFIER SVS-2-01 20 dB AXING</a>	<a href="#">AMPLIFIER SVS-2-04 10 dB AXING</a>	<a href="#">AMPLIFIER FOR MULTISWITCHES SA-51 5 INPUTS / 5 OUTPUTS TERRA</a>	<a href="#">AMPLIFIER FOR MULTISWITCHES SA-91L 9 INPUTS / 9 OUTPUTS TERRA</a>
				
	5.13 EUR 6.31 EUR	5.97 EUR 7.34 EUR	134.60 EUR 165.56 EUR	208.01 EUR 255.85 EUR
Frequency range	950 MHz ... 2400 MHz	47 MHz ... 2400 MHz	...	...
Gain	20 dB	10 dB	...	...
Correction in satellite frequencies range	—	—	...	...
Output level	106 dB $\mu$ V	95 dB $\mu$ V ... 97 dB $\mu$ V	...	...
Connectors type	"F"	"F"	...	...
Inputs	...	...	4x 950 MHz ... 2400 MHz , 1x 47 MHz ... 790 MHz	8x 950 MHz ... 2400 MHz , 1x 47 MHz ... 790 MHz
DC voltage passing	✓	✓	...	...
Operation voltage	...	14 ... 18 V DC	...	...
Current consumption	≤ 80 mA (without LNB powering)	≤ 40 mA (without LNB powering)	...	...
Outputs	...	...	V.Lo, H.Lo, V.Hi, H.Hi, RTV	2 x V.Lo, 2 x H.Lo, 2 x V.Hi, 2 x H.Hi, RTV
SAT amplification	...	...	22 dB	22 dB
SAT Gain control	...	...	0 ... 15 dB by 1 dB step	0 ... 15 dB by 1 dB step
SAT amplification (cable pre-correction)	...	...	0 / 3 / 5 / 7 dB	0 / 3 / 5 / 7 dB
TV amplification	...	...	22 dB	22 dB
TV Gain control	...	...	0 ... 15 dB by 1 dB step	0 ... 15 dB by 1 dB step
TV amplification (cable pre-correction)	...	...	0 / 6 / 12 / 18 dB	0 / 6 / 12 / 18 dB
Isolation	...	...	• Between inputs SAT/SAT 30 dB • Between inputs TV/SAT 30 dB	• Between inputs SAT/SAT 30 dB • Between inputs TV/SAT 30 dB
Self-noises	...	...	< 9 dB	< 9 dB
Maximal output level SAT	...	...	114 dB $\mu$ V	114 dB $\mu$ V
Maximal output level TV	...	...	109 dB $\mu$ V	109 dB $\mu$ V
Device powering	...	...	14 V DC / 0.5 A , 18 V DC / 2 A ( max. 1 A for 1 line )	14 V DC / 0.5 A , 18 V DC / 1.8 A ( max. 1 A for 1 line )
Pre-amplifiers powering	...	...	12 V DC / 0.1 A	12 V DC / 0.1 A
DC pass (max.)	...	...	2 A	2 A
Power supply	14 ... 18 V DC (from the SAT receiver or the multiswitch)	...	230 V AC, 50 / 60 Hz	230 V AC, 50 / 60 Hz
Power consumption	...	...	5 W	7 W
Operation temp	...	...	-20 °C ... 50 °C	-20 °C ... 50 °C
Dimensions	...	...	284 x 135 x 52 mm	364 x 135 x 52 mm
Weight	...	...	0.83 kg	1.07 kg
Manufacturer / Brand	AXING	AXING	TERRA	TERRA
Guarantee	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00