

	FIBER OPTIC VIDEO CONVERTER OVH-1D/SC 1X VIDEO + RS-485 TXRX SET	FIBER OPTIC VIDEO CONVERTER OVH-2D/SC 2x VIDEO + RS-485 TXRX SET	FIBER OPTIC VIDEO CONVERTER OVH-4D/SC 4x VIDEO + RS-485 TXRX SET
			
	76.29 EUR 76.29 EUR	95.46 EUR 95.46 EUR	141.46 EUR 141.46 EUR
Standard	AHD / HD-CVI / HD-TVI / PAL	AHD / HD-CVI / HD-TVI / PAL	AHD / HD-CVI / HD-TVI / PAL
Optical connector type	SC	SC	SC
Number of fibers	1 pcs	1 pcs	1 pcs
Recommended fiber	Single-mode fiber	Single-mode fiber	Single-mode fiber
Transmission range	20 km - Single-mode fiber	20 km - Single-mode fiber	20 km - Single-mode fiber
Number of video channels	1 pcs - AHD / HD-CVI / HD-TVI / PAL	2 pcs - AHD / HD-CVI / HD-TVI / PAL	4 pcs - AHD / HD-CVI / HD-TVI / PAL
Supported resolutions	• AHD : 8 Mpx 4K UHD @ 15 fps, 5 Mpx, 4 Mpx, 3 Mpx, 1080p, 720p @ 25 / 20 / 12.5 fps, • HD-CVI : 1080p, 720p @ 25 fps, • HD-TVI : 5 Mpx @ 12.5 fps, • CVBS : 1080p @ 25 fps	• AHD : 8 Mpx 4K UHD @ 15 fps, 5 Mpx, 4 Mpx, 3 Mpx, 1080p, 720p @ 25 / 20 / 12.5 fps, • HD-CVI : 1080p, 720p @ 25 fps, • HD-TVI : 5 Mpx @ 12.5 fps, • CVBS : 1080p @ 25 fps	• AHD : 8 Mpx 4K UHD @ 15 fps, 5 Mpx, 4 Mpx, 3 Mpx, 1080p, 720p @ 25 / 20 / 12.5 fps, • HD-CVI : 1080p, 720p @ 25 fps, • HD-TVI : 5 Mpx @ 12.5 fps, • CVBS : 1080p @ 25 fps
Video connectors type	BNC	BNC	BNC
Video resolution	8 bit	8 bit	8 bit
Video bandwidth	0 MHz ... 50 MHz	0 MHz ... 50 MHz	0 MHz ... 50 MHz
Video input voltage / impedance	1 Vpp / 75 Ω	1 Vpp / 75 Ω	1 Vpp / 75 Ω
Audio input	—	—	—
RS-485 signal	one-direction RS-485 Connectors 1 (+), 2 (-) - terminals	one-direction RS-485 Connectors 1 (+), 2 (-) - terminals	one-direction RS-485 Connectors 1 (+), 2 (-) - terminals
Optical wavelength	1310 / 1550 nm	1310 / 1550 nm	1310 / 1550 nm
LED diodes	LEDs indicating device operation state	LEDs indicating device operation state	LEDs indicating device operation state
Power supply	5 V DC / 1.0 A (power adapter included)	5 V DC / 1.0 A (power adapter included)	5 V DC / 2 A (power adapter included)
Operation temp	-40 °C ... 75 °C	-40 °C ... 75 °C	-40 °C ... 75 °C
Permissible relative humidity	0 % ... 95 % (non-condensing)	0 % ... 95 % (non-condensing)	0 % ... 95 % (non-condensing)
Weight	0.234 kg	0.664 kg	0.67 kg
Dimensions	108 x 121 x 28 mm	183 x 109 x 26 mm	173 x 190 x 30 mm
Guarantee	2 years	2 years	2 years