







	OUTDOOR SIDE OPENING HOUSING TP-434	OUTDOOR SIDE OPENING HOUSING PFH610N-IR-W DAHUA	OUTDOOR SIDE OPENING HOUSING PFH610N-IR-W-V2 DAHUA	OUTDOOR SIDE OPENING HOUSING PFH610V-H-POE-V2 DAHUA	OUTDOOR SIDE OPENING HOUSING PFH610V-IR-V2 DAHUA	THERMOSTAT TT-12E
						
	20.95 EUR 25.77 EUR	330.42 EUR 406.42 EUR	346.66 EUR 426.39 EUR	258.77 EUR 318.29 EUR	308.61 EUR 379.59 EUR	5.64 EUR 6.94 EUR
Thermostat switching on temperature	...	...	...	...	...	3 °C
External dimensions	380 x 138 x 101 mm	404 x 164 x 175 mm	404 x 164 x 132 mm	404 x 164 x 132 mm	404 x 164 x 132 mm	...
Housing type	...	...	...	...	...	TP-601, TP-606, TP-607, TH-200
Internal dimensions	285 x 100 x 75 mm	255 x 90 x 83 mm	255 x 90 x 83 mm	255 x 90 x 83 mm	215 x 90 x 83 mm	...
Camera power supply adapter	...	...	...	...	...	—
Glass dimensions	63 x 84 mm	Ø 50 mm	Ø 60 mm	Ø 60 mm	Ø 60 mm	...
Material	Aluminum - powder painted	Aluminum - powder painted / PC	Aluminum - powder painted + PC	Aluminum - powder painted + PC	Aluminum - powder painted + PC	...
Power / current consumption	...	...	...	...	...	max. 5.5 W / 460 mA
Thermostat	—	✓	✓	✓	✓	...
Certificates	IP66	...	...	...	...	...
IR illuminator	...	100 m	100 m - RS-485 control	...	100 m	...
Dimensions	...	...	...	...	...	57 x 32 x 15 mm (heaters board)
Vandal-proof	...	...	...	IK10	IK10	...
"Index of Protection"	...	IP66	IP66	IP67	IP66	...
Main features	The product is adapted to work outdoors • Bracket not included in the kit	• The product is adapted to work outdoors (heater and fan cooler built-in) • Wiper • Bracket not included in the kit	• The product is adapted to work outdoors (heater and fan cooler built-in) • Wiper - RS-485 control • Bracket not included in the kit	• The product is adapted to work outdoors (heater and fan cooler built-in), • Power supply of the camera : PoE (802.3af/at), • Bracket not included in the kit	• The product is adapted to work outdoors (heater and fan cooler built-in) • Controlling the IR illuminator via RS-485 • Bracket not included in the kit	...
Operation temp	...	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	...
Power supply	...	24 V AC / 5 A	24 V AC / 3 A	PoE (802.3at)	24 V AC / 5 A (max)	12 V DC
Power consumption	...	...	...	12 W - without camera	≤ 55 W	...
Weight	0.900 kg	2.78 kg	2.79 kg	2.67 kg	2.52 kg	...
Manufacturer / Brand	...	DAHUA	DAHUA	DAHUA	DAHUA	DELTA
Guarantee	2 years	3 years	3 years	3 years	3 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00