

	SINGLE-MODE MODULE GTS-SFP-21CG	SINGLE-MODE MODULE GTS-SFP-35G	SINGLE-MODE MODULE GTS-SFP-53G	SINGLE-MODE MODULE SFP MINI GBIC MGRIC-LH-E	MULTI-MODE MODULE SFP MINI GBIC MGRIC-SX-E	SFP DUMMY PLUG PFOZ- SFPB	SINGLE-MODE MODULE DS-1-25G-20-1310 Hikvision	SINGLE-MODE MODULE DS-1-25G-20-1550 Hikvision	MULTI-MODE MODULE PFT2900 DAHUA	SINGLE-MODE MODULE PFT3910 DAHUA	MULTI-MODE MODULE PFT3950 DAHUA	SINGLE-MODE MODULE PFT3960 DAHUA	SINGLE-MODE MODULE PFT3970 DAHUA	MULTI-MODE MODULE SFP-011M	MULTI-MODE MODULE SFP-023G	SINGLE-MODE MODULE SFP-203G5G	SINGLE-MODE MODULE SFP-203G	SINGLE-MODE MODULE SFP-205G5G
	9.03 EUR 11.11 EUR	11.74 EUR 14.44 EUR	15.26 EUR 18.77 EUR	32.94 EUR 40.52 EUR	21.18 EUR 26.05 EUR	0.31 EUR 0.38 EUR	28.34 EUR 34.86 EUR	37.71 EUR 46.38 EUR	52.11 EUR 64.10 EUR	52.11 EUR 64.10 EUR	62.62 EUR 77.02 EUR	66.28 EUR 81.52 EUR	100.33 EUR 123.41 EUR	8.33 EUR 10.25 EUR	8.97 EUR 11.03 EUR	8.91 EUR 10.96 EUR	8.98 EUR 11.05 EUR	10.92 EUR 13.43 EUR
Transmission protocols	IEEE 802.3z 1000Base-FX	IEEE 802.3z 1000Base-FX	IEEE 802.3z 1000Base-FX	1000Base-LX Ethernet	1000Base-SX Ethernet	SFP dummy plug	IEEE 802.3z 1000Base-FX	IEEE 802.3z 1000Base-FX	IEEE 802.3u 100Base-FX	IEEE 802.3u 100Base-FX	IEEE 802.3z 1000Base-FX	IEEE 802.3z 1000Base-FX	IEEE 802.3z 1000Base-FX	IEEE 802.3u 100Base-FX	IEEE 802.3z 1000Base-FX	IEEE 802.3z 1000Base-FX	IEEE 802.3z 1000Base-FX	IEEE 802.3z 1000Base-FX
Application	...	...	...	...	...	SFP dummy plug	...	...	...	...	...	...	...	...	...	...	...	...
Material	...	...	...	...	...	Rubber	...	...	...	...	...	...	...	...	...	...	...	...
Color	...	...	...	...	...	Black	...	...	...	...	...	...	...	...	...	...	...	...
Fiber type	8.3/125 µm, 8.7/125 µm, 9/125 µm, 10/125 µm - Single-mode fiber	8.3/125 µm, 8.7/125 µm, 9/125 µm, 10/125 µm - Single-mode fiber	8.3/125 µm, 8.7/125 µm, 9/125 µm, 10/125 µm - Single-mode fiber	9 / 125 µm Single-mode fiber	50 / 125 µm / 62 / 125 µm Multi-mode fiber	...	Single-mode fiber	Single-mode fiber	Multi-mode fiber	Single-mode fiber	Multi-mode fiber	Single-mode fiber	Single-mode fiber	50/125 µm, 62.5/125 µm - Multi-mode fiber	50/125 µm, 62.5/125 µm - Multi-mode fiber	8.3/125 µm, 8.7/125 µm, 9/125 µm, 10/125 µm - Single-mode fiber	8.3/125 µm, 8.7/125 µm, 9/125 µm, 10/125 µm - Single-mode fiber	8.3/125 µm, 8.7/125 µm, 9/125 µm, 10/125 µm - Single-mode fiber
Dimensions	...	...	...	...	...	15 x 14 x 9 mm	...	...	...	...	...	...	...	...	...	...	...	...
Maximal transmission range	20 km	20 km	20 km	20 km	0.5 km @ 50/125 µm 0.22 km @ 62/125 µm	...	20 km	20 km	2 km	20 km	0.5 km	20 km	20 km	0.5 km @ 50/125 µm 0.3 km @ 62/125 µm	2 km	20 km	20 km	20 km
Transfer rate	max. 1.25 Gb/s	max. 1.25 Gb/s	max. 1.25 Gb/s	max. 1.25 Gb/s	max. 1.25 Gb/s	...	max. 1.25 Gb/s	max. 1.25 Gb/s	max. 155 Mbps	max. 155 Mbps	max. 1.25 Gb/s	max. 1.25 Gb/s	max. 1.25 Gb/s	max. 155 Mbps	max. 1.25 Gb/s	max. 1.25 Gb/s	max. 1.25 Gb/s	max. 1.25 Gb/s
Number of used fibers	2	1	1	2	2	...	1	2	2	1	2	1	1	2	1	1	2	1
Optical connectors	2 x LC	SC	SC	2x LC	2x LC	...	LC	LC	2 x LC	LC	2 x LC	LC	LC	2 x LC	2 x LC	LC	2 x LC	LC
Light source / optical wavelength	Laser FP / 1310 nm	Laser FP - 1310 / 1550 nm (Tx / Rx)	Laser FP - 1550 / 1310 nm (Tx / Rx)	Laser FP / 1310 nm	Surface VCSEL Laser / 850 nm	...	Laser FP - 1310 / 1550 nm (Tx / Rx)	Laser FP - 1550 / 1310 nm (Tx / Rx)	Laser FP - 850 nm (Tx / Rx)	Laser FP - 1310 / 1550 nm (Tx / Rx)	Laser FP - 850 nm (Tx / Rx)	Laser FP - 1310 / 1550 nm (Tx / Rx)	Laser FP - 1550 / 1310 nm (Tx / Rx)	Laser FP / 850 nm	Laser FP / 1310 nm	Laser FP - 1310 / 1550 nm (Tx / Rx)	Laser FP / 1310 nm	Laser FP - 1550 / 1310 nm (Tx / Rx)
Main features	...	Wavelength-Division Multiplexing technology WDM (Tx 1310nm / Rx 1550nm)	Wavelength-Division Multiplexing technology WDM (Tx 1550nm / Rx 1310nm)	...	...	...	Wavelength-Division Multiplexing technology WDM (Tx 1310nm / Rx 1550nm)	Wavelength-Division Multiplexing technology WDM (Tx 1550nm / Rx 1310nm)	...	Wavelength-Division Multiplexing technology WDM (Tx 1310nm / Rx 1550nm)	...	Wavelength-Division Multiplexing technology WDM (Tx 1310nm / Rx 1550nm)	Wavelength-Division Multiplexing technology WDM (Tx 1550nm / Rx 1310nm)	...	...	Wavelength-Division Multiplexing technology WDM (Tx 1310nm / Rx 1550nm)	...	Wavelength-Division Multiplexing technology WDM (Tx 1550nm / Rx 1310nm)
Transmitter power	-8 ... -3 dB	-8 ... -3 dB	-8 ... -3 dB	...	...	...	...	...	...	...	...	...	...	...	-8 ... -3 dB	-8 ... -3 dB	-8 ... -3 dB	-8 ... -3 dB
Receiver sensitivity	≥ -22 dB	≥ -22 dB	≥ -22 dB	...	...	...	...	...	...	...	...	...	...	...	≥ -19 dB	≥ -19 dB	≥ -22 dB	≥ -22 dB
SAP Code	...	...	...	...	...	...	307400045	307400046	...	...	...	...	...	...	...	...	...	...
Power supply	3.3 V DC	3.3 V DC	3.3 V DC	3.3 V	3.3 V	...	3.3 V DC	3.3 V DC	3.3 V DC	3.3 V DC	3.3 V DC	3.3 V DC	3.3 V DC	3.3 V DC	3.3 V DC	3.3 V DC	3.3 V DC	3.3 V DC
Operation temp	0 °C ... 70 °C	0 °C ... 70 °C	0 °C ... 70 °C	0 °C ... 70 °C	0 °C ... 70 °C	...	0 °C ... 70 °C	0 °C ... 70 °C	-40 °C ... 85 °C	-40 °C ... 85 °C	-40 °C ... 85 °C	-40 °C ... 85 °C	-40 °C ... 85 °C	0 °C ... 70 °C	0 °C ... 70 °C	0 °C ... 70 °C	0 °C ... 70 °C	0 °C ... 70 °C
Weight	0.017 kg	0.024 kg	0.024 kg	0.020 kg	0.016 kg	0.0005 kg	0.02 kg	0.02 kg	0.02 kg	0.02 kg	0.02 kg	0.02 kg	0.02 kg	0.016 kg	0.018 kg	0.02 kg	0.018 kg	0.02 kg
Manufacturer / Brand	...	...	...	...	...	...	Hikvision	Hikvision	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	...	...	...	...	...
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00