

	CRIMP SOCKET SMA-G-RP/ZAC.H-155	CRIMP SOCKET SMA-G/ZAC.H-155	CRIMP PLUG SMA-W-RP/ZAC.H-155	CRIMP PLUG SMA-W/ZAC.H-155
				
	1.05 EUR 1.29 EUR	1.02 EUR 1.25 EUR	0.93 EUR 1.14 EUR	0.99 EUR 1.22 EUR
Connector type	SMA Socket RP	SMA Socket	SMA Plug RP	SMA Plug
Attachment of connector elements	Crimping	Crimping	Crimping	Crimping
Shield fastening	Crimping	Crimping	Crimping	Crimping
Wire mounting	Soldering	Soldering	Soldering	Soldering
Application	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable
Cable diameter	max. 6.1 mm	max. 6.1 mm	max. 6.1 mm	max. 6.1 mm
Impedance	50 Ω	50 Ω	50 Ω	50 Ω
Material	Metal	Metal	Metal	Metal
Example of application	<ul style="list-style-type: none"> • TRI-LAN/100 • H-155 	<ul style="list-style-type: none"> • TRI-LAN/100 • H-155 	<ul style="list-style-type: none"> • TRI-LAN/100 • H-155 	<ul style="list-style-type: none"> • TRI-LAN/100 • H-155
Main features	<ul style="list-style-type: none"> • Wide frequency range • Corrosion resistance • To crimp use the crimping tool HT-301C 	<ul style="list-style-type: none"> • Wide frequency range • Corrosion resistance • To crimp use the crimping tool HT-301C 	<ul style="list-style-type: none"> • Wide frequency range • Corrosion resistance • To crimp use the crimping tool HT-301C 	<ul style="list-style-type: none"> • Wide frequency range • Corrosion resistance • To crimp use the crimping tool HT-301C
Weight	0.010 kg	0.010 kg	0.005 kg	0.010 kg
Guarantee	2 years	2 years	2 years	2 years