

	RS-485 KEYBOARD CONTROLLER KT-610	IP / RS-485 KEYBOARD CONTROLLER BCS-DVR- KN-III BCS Line	USB KEYBOARD CONTROLLER DS-1005KJ Hikvision	IP / RS-485 KEYBOARD CONTROLLER NKB1000-E DAHUA	IP / RS-485 KEYBOARD CONTROLLER DS-1200KJ Hikvision	IP KEYBOARD CONTROLLER DS-1600KJ(B) Hikvision	IP / RS-485 KEYBOARD CONTROLLER BCS-V-KN BCS View	USB KEYBOARD CONTROLLER BCS-V-KUSB BCS View
								
	133.58 EUR 133.58 EUR	510.22 EUR 510.22 EUR	406.70 EUR 406.70 EUR	562.46 EUR 562.46 EUR	652.15 EUR 652.15 EUR	2188.60 EUR 2188.60 EUR	651.19 EUR 651.19 EUR	406.70 EUR 406.70 EUR
Users + admins	...	...	...	...	...	31 + 1	15 + 1	...
Protocols	Pelco-D, Pelco-P, SAMSUNG, YAAN, SAE	DH-SD1, DH-2, Pelco-P, Pelco-D and others	HID	DH-SD1, DH-2, Pelco-P, Pelco-D and others	...	...	...	HID
Number of users	...	max. 64	...	max. 64	...	...	...	...
Number of cameras in the system	...	max. 2048	...	max. 2048	...	...	...	...
Connectors	...	...	...	...	...	• 1 x RJ-45 - Gigabit Ethernet • 2 x USB 2.0 • 1 x HDMI • 1 x DVI • 2 x Jack 3.5 mm socket - Headphones output, External microphone input	...	...
Baud rates	1200, 2400, 4800, 9600, 19200 bps	...	...	...	...	...	...	...
Cameras numbers (ID)	0 ... 255	0 ... 254	...	1 ... 255	...	...	...	...
Maximal control distance	1200 m	...	...	...	1200 m @ RS-485 / RS-422	...	...	...
Video output	...	...	...	...	...	1 x HDMI 1 x DVI	...	...
Communication standard	RS-485	• Network mode - Ethernet, RJ-45 socket • Direct mode - RS-485, terminals • Direct mode - RS-422, terminals • Direct mode - RS-232, D-sub socket • USB - Software PC	USB HID	• Network mode - Ethernet, RJ-45 socket • Direct mode - RS-485, terminals • Direct mode - RS-232, D-sub socket	• Ethernet - RJ-45 socket, RS-485 / RS-422 - terminals	• Gigabit Ethernet, RJ-45 socket, • Network mode - Wi-Fi	• Ethernet, RJ-45 socket, • RS-485 - terminals, • RS-422 - terminals, • RS-232, D-sub socket, • Port USB 2.0	USB 2.0 HID
Manipulator	3-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick)	3-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick)	• 3-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick) • 2 additional buttons on the joystick	3-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick)	4-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick)	4-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick)	• 4-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick) • 1 additional button on the joystick	• 3-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick) • 2 additional buttons on the joystick
Alarm inputs / outputs	...	...	...	...	...	...	...	...
Display	LCD 2x16 characters	LCD - with light indication	✓	LCD - with light indication	LCD - 128 x 64 px, with light indication	10.1" LCD - 1024 x 600 px, capacitive touch screen, with light indication	LCD - 128 x 64 px, with light indication	7-segment display
PTZ control	...	• BCS or other manufacturers Speed Dome cameras • Recorders BCS	...	• Dahua or other manufacturers Speed Dome cameras • Recorders DAHUA	• HIKVISION or other manufacturers Speed Dome cameras • Recorders Hikvision	• IP cameras - Hikvision • Recorders Hikvision • Other elements of the VMS system	• BCS View Speed Dome Cameras • Recorders BCS View	...
Main features	• Speed Dome cameras, motor units, Motozoom cameras/lenses support • Admin password	...	...	...	...	• Backup to USB drive (pendrive, external drive) • Live image view : 2 x 1080p (for full resolution), 16 x Sub stream • Bi-directional audio streaming support • Large, readable LCD display with backlight • Detachable joystick module allows you to place it in the most ergonomic place for the user • Split screen at view from cameras : 1 / 4 / 8 / 9 / 16 • Graphic menu - touch control or Mouse support	• 3D PTZ support • Programmable buttons • Keyboard operation status indicator • Supports max. 1000 devices • Built-in Webservice, photo capture via USB	• 3D PTZ support • Programmable buttons • Keyboard operation status indicator
Power supply	12 V DC / 2 A (power adapter included)	12 V DC / 2 A	5 V DC - via USB port	12 V DC / 1 A	12 V DC / 1.5 A	• 12 V DC / 4 A (power adapter included) • 802.3af/at	12 V DC / 375 mA	5 V DC - via USB port
Power consumption	...	...	≤ 5 W	...	...	≤ 15 W	< 4.5 W	< 5 W
Operation temp. / Relative humidity	-20 °C ... 55 °C / ≤ 90 %	-10 °C ... 55 °C / ≤ 90 % (non-condensing)	-10 °C ... 55 °C / max. 90 %	-10 °C ... 55 °C / 10 % ... 90 % non-condensing	-10 °C ... 55 °C / 10 % ... 90 % (non-condensing)	-10 °C ... 55 °C / 10 % ... 90 % (non-condensing)	-10 °C ... 55 °C / 10 % ... 90 % (non-condensing)	-10 °C ... 55 °C / 10 % ... 90 % (non-condensing)
Weight	0.75 kg	0.7 kg	0.55 kg	0.702 kg	0.80 kg	1.72 kg	1.08 kg	0.55 kg
Dimensions	220 x 130 x 95 mm	330 x 160 x 105 mm	174 x 167 x 121 mm	330 x 160 x 105 mm	349 x 172 x 125 mm	404 x 154 x 180 mm	435 x 193 x 110 mm	178 x 167 x 116 mm
Supported languages	...	...	...	...	...	English	...	...
Manufacturer / Brand	...	BCS Line	Hikvision	DAHUA	Hikvision	...	BCS View	BCS View
SAP Code	...	...	302600066	...	302600140	302600232	...	...
Guarantee	2 years	2 years	3 years	3 years	3 years	3 years	2 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00