

	LED FLOODLIGHT AD- NL-6252BL4 ADVITI	LED FLOODLIGHT WITH MOTION SENSOR AD- NL-6252BLR4 ADVITI	LED FLOODLIGHT AD- NL-6253BL4 ADVITI	LED FLOODLIGHT WITH MOTION SENSOR AD- NL-6253BLR4 ADVITI	LED FLOODLIGHT AD- NL-6254BL4 ADVITI	LED FLOODLIGHT WITH MOTION SENSOR AD- NL-6254BLR4 ADVITI	LED FLOODLIGHT AD- NL-6255BL4 ADVITI	LED FLOODLIGHT WITH MOTION SENSOR AD- NL-6255BLR4 ADVITI	LED FLOODLIGHT WITH MOTION SENSOR AD- NL-6462BLR4 ADVITI	LED FLOODLIGHT WITH MOTION SENSOR AD- NL-6463BLR4 ADVITI	LED FLOODLIGHT WITH MOTION SENSOR AD- NL-6464BLR4 ADVITI	LED FLOODLIGHT WITH MOTION SENSOR AD- NL-6465BLR4 ADVITI	LED FLOODLIGHT WITH BATTERY AD-NR-6466L4 ADVITI	SOLAR LED FLOODLIGHT WITH MOTION SENSOR AD-SL-6108BLR4	SOLAR LED FLOODLIGHT WITH MOTION SENSOR AD-SL-6467BLR4	LED FLOODLIGHT MCE-510 MACLEAN ENERGY	LED FLOODLIGHT MCE-520 MACLEAN ENERGY	LED FLOODLIGHT MCE-530 MACLEAN ENERGY	LED FLOODLIGHT MCE-550 MACLEAN ENERGY	TWILIGHT SENSOR MCE-35	TWILIGHT SENSOR TS-02B7
																					
Luminous flux	5.87 EUR 5.87 EUR	12.31 EUR 12.31 EUR	7.16 EUR 7.16 EUR	13.57 EUR 13.57 EUR	9.53 EUR 9.53 EUR	16.12 EUR 16.12 EUR	13.32 EUR 13.32 EUR	19.90 EUR 19.90 EUR	8.20 EUR 8.20 EUR	9.71 EUR 9.71 EUR	11.64 EUR 11.64 EUR	14.55 EUR 14.55 EUR	25.99 EUR 25.99 EUR	36.29 EUR 36.29 EUR	26.40 EUR 26.40 EUR	4.17 EUR 4.17 EUR	7.33 EUR 7.33 EUR	9.95 EUR 9.95 EUR	12.74 EUR 12.74 EUR	9.38 EUR 9.38 EUR	7.60 EUR 7.60 EUR
Illumination angle	800 lm	800 lm	1600 lm	1600 lm	2400 lm	2400 lm	4000 lm	4000 lm	800 lm	1600 lm	2400 lm	4000 lm	2 x 600 lm	500 lm	1200 lm	900 lm	1600 lm	2400 lm	4700 lm	...	...
Light color	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	Neutral, 4000 K	...	...
Maximal load	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	15 A / 3450 W	6 A / 1400 W (resistance load), 350 W (inductive load)
Lighting switching threshold	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	< 2 Lux ... 100 Lux	< 5 Lux ... 50 Lux
Twilight switch	—	✓	—	✓	—	✓	—	✓	✓	✓	✓	✓	✓	✓	✓	—	—	—	—	...	...
Nominal power	10 W	10 W	20 W	20 W	30 W	30 W	50 W	50 W	10 W	20 W	30 W	50 W	2 x 10 W	5 W	10 W	10 W	20 W	30 W	50 W	...	...
Power factor	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.9	0.8	...	...	...	...	...	...	...	...	...
Operation modes	...	...	...	...	...	...	...	...	...	...	...	...	3 light modes	...	...	...	...	...	...	...	...
Energy class	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	Energy efficiency class F (Regulation (EU) 2019/2015)	Energy efficiency class A++/A+/A (Regulation (EU) 874/2012)	Energy efficiency class A++/A+/A (Regulation (EU) 874/2012)	Energy efficiency class F (Regulation (EU) 2019/2015)	...	...
CRI	> 80	> 80	> 80	> 80	> 80	> 80	> 80	> 80	> 80	> 80	> 80	> 80	80	80	80	> 80	> 80	> 80	> 80	...	...
Power supply	230 V AC	230 V AC	230 V AC	230 V AC	230 V AC	230 V AC	230 V AC	230 V AC	230 V AC	230 V AC	230 V AC	230 V AC	Li-Ion battery 5000 mAh	3.7 V DC - 3000 mAh Li-Ion battery	3.7 V DC - 3000 mAh Li-Ion battery	220 ... 240 V AC	220 ... 240 V AC	220 ... 240 V AC	220 ... 240 V AC	220 ... 240 V AC	220 ... 240 V AC
Mechanical protection class	...	...	...	...	...	...	...	...	...	...	IK08	...	...	...	...	...	...	...	...	...	...
Main features	• LED SMD diodes • LED lifetime 30 000 h • Solid workmanship • PIR detector - Built-in, Range : 4 ... 8 m, Detection angle : 120 ° • PIR detection sensitivity adjustment, • Sensitivity adjustment of the twilight sensor : 10 ... 2000 lx, • Lighting time adjustment : 10 ... 600 s, • IK rating : IK04	• LED SMD diodes • LED lifetime 30 000 h • Solid workmanship • PIR detector - Built-in, Range : 4 ... 8 m, Detection angle : 120 ° • PIR detection sensitivity adjustment, • Sensitivity adjustment of the twilight sensor : 10 ... 2000 lx, • Lighting time adjustment : 10 ... 600 s, • IK rating : IK04	• LED SMD diodes • LED lifetime 30 000 h • Solid workmanship • PIR detector - Built-in, Range : 4 ... 8 m, Detection angle : 120 ° • PIR detection sensitivity adjustment, • Sensitivity adjustment of the twilight sensor : 10 ... 2000 lx, • Lighting time adjustment : 10 ... 600 s, • IK rating : IK04	• LED SMD diodes • LED lifetime 30 000 h • Solid workmanship • PIR detector - Built-in, Range : 4 ... 8 m, Detection angle : 120 ° • PIR detection sensitivity adjustment, • Sensitivity adjustment of the twilight sensor : 10 ... 2000 lx, • Lighting time adjustment : 10 ... 600 s, • IK rating : IK04	• LED SMD diodes • LED lifetime 30 000 h • Solid workmanship • PIR detector - Built-in, Range : 4 ... 8 m, Detection angle : 120 ° • PIR detection sensitivity adjustment, • Sensitivity adjustment of the twilight sensor : 5 ... 2000 lx, • Lighting time adjustment : 5 ... 600 s, • IK rating : IK04	• LED SMD diodes • LED lifetime 30 000 h • Solid workmanship • PIR detector - Built-in, Range : 4 ... 8 m, Detection angle : 120 ° • PIR detection sensitivity adjustment, • Sensitivity adjustment of the twilight sensor : 5 ... 2000 lx, • Lighting time adjustment : 5 ... 600 s, • IK rating : IK08	• LED SMD diodes • LED lifetime 35 000 h • Solid workmanship • PIR detector - Built-in, Range : 0.5 ... 8 m, Detection angle : 120 ° • PIR detection sensitivity adjustment, • Sensitivity adjustment of the twilight sensor : 5 ... 2000 lx, • Lighting time adjustment : 5 ... 600 s, • IK rating : IK08	• LED SMD diodes • LED lifetime 35 000 h • Solid workmanship • PIR detector - Built-in, Range : 0.5 ... 8 m, Detection angle : 120 ° • PIR detection sensitivity adjustment, • Sensitivity adjustment of the twilight sensor : 5 ... 2000 lx, • Lighting time adjustment : 5 ... 600 s, • IK rating : IK08	• LED SMD diodes • LED lifetime 35 000 h • Solid workmanship • PIR detector - Built-in, Range : 0.5 ... 8 m, Detection angle : 120 ° • PIR detection sensitivity adjustment, • Sensitivity adjustment of the twilight sensor : 5 ... 2000 lx, • Lighting time adjustment : 5 ... 600 s, • IK rating : IK08	• LED SMD diodes • LED lifetime 35 000 h • Solid workmanship • PIR detector - Built-in, Range : 0.5 ... 8 m, Detection angle : 120 ° • PIR detection sensitivity adjustment, • Sensitivity adjustment of the twilight sensor : 5 ... 2000 lx, • Lighting time adjustment : 5 ... 600 s, • IK rating : IK08	• LED SMD diodes • LED lifetime 35 000 h • Solid workmanship • PIR detector - Built-in, Range : 0.5 ... 8 m, Detection angle : 120 ° • PIR detection sensitivity adjustment, • Sensitivity adjustment of the twilight sensor : 5 ... 2000 lx, • Lighting time adjustment : 5 ... 600 s, • IK rating : IK08	• LED SMD diodes • LED lifetime 35 000 h • Solid workmanship • PIR detector - Built-in, Range : 0.5 ... 8 m, Detection angle : 120 ° • PIR detection sensitivity adjustment, • Sensitivity adjustment of the twilight sensor : 5 ... 2000 lx, • Lighting time adjustment : 5 ... 600 s, • IK rating : IK08	• 2 x LED COB indicator • Estimated battery operation time : 5 h • Charging via USB-C port (power adapter not included) • The USB output for charging mobiles • Solid workmanship • LED lifetime 50 000 h	• 30 x LED SMD 2835 diodes • LED lifetime 35 000 h • Solar Panel, polycrystalline • Built-in, Nominal power : 5 W • PIR detector - Built-in, Detection angle : 120 °, Detection range ≤ 6 m • Tilt adjustment : 135 ° (vertical) • 2 Operation modes • Motion sensor control • Solid workmanship • Assembly : < 4 m	• LED lifetime : 25 000 h • Solar Panel • Connecting cable 2m • PIR detector - Built-in, Detection angle : 120 °, Detection range ≤ 6 m • 2 Operation modes • Solid workmanship • IK rating : IK06	• LED SMD diodes • LED lifetime 20 000 h • Solid workmanship	• LED SMD diodes • LED lifetime 50 000 h • Solid workmanship	• LED SMD diodes • LED lifetime 50 000 h • Solid workmanship	• LED SMD diodes • LED lifetime 20 000 h • Solid workmanship	• Length of the cable, 17 cm • For indoor use	
Housing	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Nylon + Rubber	Plastic (ABS) + PC - UV radiation resistance	PC	Aluminum	Aluminum	Aluminum	Aluminum	Plastic	Plastic
Index of Protection	IP65	IP44	IP65	IP44	IP65	IP44	IP65	IP44	IP65	IP44	IP65	IP44	IP65	IP65	IP54	IP65	IP65	IP65	IP65	IP65	IP54
Operation temp	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	...	-20 °C ... 50 °C	0 °C ... 45 °C	-20 °C ... 35 °C	-20 °C ... 35 °C	-20 °C ... 35 °C	-20 °C ... 35 °C	-20 °C ... 40 °C	...
Weight	0.17 kg	0.22 kg	0.22 kg	0.27 kg	0.33 kg	0.38 kg	0.48 kg	0.53 kg	0.205 kg	0.157 kg	0.282 kg	0.400 kg	0.58 kg	0.61 kg	0.74 kg	0.15 kg	0.23 kg	0.35 kg	0.098 kg	0.048 kg	...
Dimensions	104 x 72 x 44 mm	105 x 130 x 65 mm	121 x 82 x 43 mm	120 x 140 x 65 mm	155 x 105 x 44 mm	155 x 170 x 65 mm	190 x 130 x 46 mm	190 x 195 x 65 mm	135 x 110 x 37 mm	160 x 120 x 65 mm	190 x 150 x 48 mm	195 x 190 x 65 mm	230 x 200 x 60 mm	234 x 150 x 34 mm	300 x 190 x 160 mm	90 x 70 x 26 mm	110 x 90 x 28 mm	140 x 120 x 30 mm	170 x 150 x 28 mm	• 48 x 63 x 27 mm • 42 x 71 x 29 mm	75 x 38 x 24 mm
Manufacturer / Brand	ORNO / ADVITI	ORNO / ADVITI	ORNO / ADVITI	ORNO / ADVITI	ORNO / ADVITI	ORNO / ADVITI	ORNO / ADVITI	ORNO / ADVITI	ORNO / ADVITI	ORNO / ADVITI	ORNO / ADVITI	ORNO / ADVITI	ORNO / ADVITI	ORNO / ADVITI	ORNO / ADVITI	MACLEAN ENERGY	MACLEAN ENERGY	MACLEAN ENERGY	MACLEAN ENERGY	...	...
Guarantee	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	2 years	3 years	2 years	2 years	2 years	2 years	2 years	2 years