

	ANGULAR COMPRESSION SOCKET IEC-GK/ZAC- TRI113	IEC SOCKET GJS	IEC SOCKET IEC-G/SKR-113	COMPRESSION SOCKET IEC-G/ZAC-TRI113/MSR	IEC SOCKET IEC- GK/SKR-113	IEC SOCKET WK-G-506	IEC SOCKET WPG-307
							
	0.83 EUR 0.83 EUR	0.16 EUR 0.16 EUR	1.15 EUR 1.15 EUR	0.55 EUR 0.55 EUR	2.42 EUR 2.42 EUR	1.12 EUR 1.12 EUR	1.12 EUR 1.12 EUR
Connector type	IEC Angular socket	IEC Socket	IEC Socket	IEC Straight socket	IEC Angular socket	IEC Angular socket	IEC Socket
Color	---	Black	---	---	---	---	---
Attachment of connector elements	Compression mounting	Twisting on	Twisting on	Compression mounting	Twisting on	---	---
Shield fastening	Compression mounting	Crimping	Twisting-on	Compression mounting	Twisting-on	Twisting-on	Twisting-on
Wire mounting	Pressing	Twisting on	Pressing	Pressing	Pressing	Pressing	Pressing
Application	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable	Coaxial cable
Dielectric diameter	max. 6.5 mm	---	min. 4.9 mm max. 5.1 mm	---	min. 4.9 mm max. 5.1 mm	---	---
Cable diameter	max. 8.5 mm	max. 7.0 mm	max. 7.5 mm	max. 8.0 mm	max. 7.5 mm	min. 6.6 mm max. 6.9 mm	min. 6.6 mm max. 6.9 mm
Impedance	75 Ω	---	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω
Material	Brass (Nickel-platted)	Metal / PET	Metal / PET	Brass (Nickel-platted)	Metal / PET	Metal	Metal
Watertightness	✓	---	✓	✓	✓	✓	✓
Example of application	Triset113	• RG6 • HFEK • Triset113	• RG6 • HFEK • Triset113	Triset-Profi, Triset113, Triset-113PE, Triset-113HF	• RG6 • HFEK • Triset113	• RG6 • HFEK • Triset113	• RG6 • HFEK • Triset113
Manufacturer / Brand	---	---	---	---	---	TELMOR	TELMOR
Main features	• Wide frequency range • Very low loss in the whole operating band • Perfect matching to the transmission line within the whole operating band • Watertightness of connector with cable connection • Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric • Properly compressed connection is highly resistant to break • Many patent-pending solutions • To crimp use the crimping tool ZAC/MSR-2K, HT-5082R	• Very easy and quick assembly • Corrosion resistance	• Very easy and quick assembly • Corrosion resistance	• Wide frequency range • Watertightness of connector with cable connection • Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric • Very low loss in the whole operating band • Perfect matching to the transmission line within the whole operating band • Properly compressed connection is highly resistant to break • Many patent-pending solutions • To crimp use the crimping tool HT-5082R	• Very easy and quick assembly • Corrosion resistance	• Very easy and quick assembly • Corrosion resistance • The die-cast metal body provides effective shielding and high mechanical resistance	• Very easy and quick assembly • Corrosion resistance • The die-cast metal body provides effective shielding and high mechanical resistance
Weight	0.024 kg	0.005 kg	0.012 kg	0.009 kg	0.023 kg	0.010 kg	0.015 kg
Dimensions	12 x 39 x 26 mm	Ø 15 x 50 mm	Ø 14 x 38 mm	Ø 11 x 33 mm	39 x 23 x 14 mm	26 x 24 x 11 mm	Ø 13 x 41 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel.: +48 61 864 69 60 / GSM: +48 607 60 11 66 / Fax: +48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00