

	TV OVERVOLTAGE PROTECTOR ZPP-4645F	GALVANIC ISOLATOR SG-4170 5-2400 MHz	OVERVOLTAGE PROTECTION PP- ZPP-4645F/12F
			
	2.44 EUR 2.44 EUR	4.09 EUR 4.09 EUR	132.95 EUR 132.95 EUR
Number of terminal pairs	...	...	12
Bandwidth	...	5 ... 2400 MHz	...
Frequency range	5 ... 2400 MHz	...	5 ... 2400 MHz
Input, input connector	F socket	...	F socket
Impedance	75 Ω	...	75 Ω
Attenuation	< 0.5 dB	5 ... 550 MHz (< 1dB) 550 ... 1000 MHz (<1.5 dB)	< 0.5 dB
Voltage protection	35 V	...	35 V
Threshold voltage	...	3000 V for 1 minute with leakage current < 0.7 mA	...
Residual voltage	10 mV / 230 V AC	...	10 mV / 230 V AC
Screening efficiency	5 ... 300 MHz - 85 dB 300 ... 470 MHz - 80 dB 470 ... 1000 MHz - 75 dB	...	5 ... 300 MHz - 85 dB 300 ... 470 MHz - 80 dB 470 ... 1000 MHz - 75 dB
Weight	...	...	2.22 kg
Dimensions	40 x 12.5 mm	...	315 x 235 x 128 mm
Guarantee	2 years	2 years	2 years