

	OVERVOLTAGE LIMITER AXON-POWER/DIN	OVERVOLTAGE LIMITER LE-412223 THREE-PHASE 2 TYPE LEGRAND	OVERVOLTAGE LIMITER LE-412253 THREE-PHASE 1+2 TYPE LEGRAND	PLUG-IN MODULE FOR OVERVOLTAGE LIMITER LE-412297 2 TYPE 20 kA LEGRAND	PLUG-IN MODULE FOR OVERVOLTAGE LIMITER LE-412302 1+2 TYPE 50 kA LEGRAND	MULTI-SOCKET PLUG WITH SURGE PROTECTION ACAR-MINI-AGD	POWER DISTRIBUTION UNIT ACAR-P7 (5 + 2 OUTLETS)	POWER DISTRIBUTION UNIT LE-049419 (6 OUTLETS) 1.5 m LEGRAND	POWER DISTRIBUTION UNIT ACAR-304/WF/RACK	POWER DISTRIBUTION UNIT ACAR-F5/FA/RACK	POWER DISTRIBUTION UNIT ACAR-S8-DUAL	POWER DISTRIBUTION UNIT ACAR-S8/FA/RACK	POWER DISTRIBUTION UNIT ACAR-XPROTECTOR	POWER DISTRIBUTION UNIT AK-SP-05A AKYGA	POWER DISTRIBUTION UNIT AK-SP-05B AKYGA	POWER DISTRIBUTION UNIT AK-SP-05L (5 OUTLETS + 2 USB) AKYGA	POWER DISTRIBUTION UNIT WITH REMOTE CONTROL OR-AE-13132 (5 OUTLETS) ORNO	POWER DISTRIBUTION UNIT OR-AE-13144 (4 OUTLETS + 2 USB) ORNO	POWER DISTRIBUTION UNIT ACAR-DIGITAL (5 OUTLETS)	POWER DISTRIBUTION UNIT ACAR-ECO-PLUS (6 OUTLETS)	POWER DISTRIBUTION UNIT ACAR-SMART (6 OUTLETS)
																					
	24.99 EUR 24.99 EUR	82.51 EUR 82.51 EUR	217.03 EUR 217.03 EUR	23.10 EUR 23.10 EUR	47.92 EUR 47.92 EUR	9.94 EUR 9.94 EUR	16.11 EUR 16.11 EUR	38.77 EUR 38.77 EUR	36.17 EUR 36.17 EUR	27.01 EUR 27.01 EUR	23.85 EUR 23.85 EUR	29.35 EUR 29.35 EUR	20.13 EUR 20.13 EUR	7.95 EUR 7.95 EUR	8.92 EUR 8.92 EUR	14.21 EUR 14.21 EUR	42.00 EUR 42.00 EUR	17.41 EUR 17.41 EUR	55.19 EUR 55.19 EUR	58.05 EUR 58.05 EUR	21.95 EUR 21.95 EUR
Total maximal current	...	...	...	...	...	10 A	10 A	16 A	...	...	...	...	10 A	10 A	10 A	10 A	10 A	10 A	...	...	...
Device type	...	Overvoltage limiter, Three-phase	Overvoltage limiter, Three-phase	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Nominal voltage	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Nominal load current	...	...	...	...	...	...	...	...	...	max. 10 A (total)	10 A (total)	10 A (total)	...	...	...	...	...	...	10 A (total)	230 V AC / 50 Hz	10 A (total)
Maximal total load	...	...	...	...	...	2300 W	2300 W	3680 W	...	2300 W	...	...	2300 W	2500 W	2500 W	2500 W	2300 W	2300 W	...	...	...
Fuse	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	10 A / 250 V	...
Rated current	10 A	...	...	...	...	...	...	...	10 A (total)	...	...	...	...	...	...	...	...	...	...	...	...
Rated voltage	230 V AC / 50 Hz	230 / 400 V AC, 50 / 60 Hz	230 / 400 V AC, 50 / 60 Hz	230 / 400 V AC, 50 / 60 Hz	230 / 400 V AC, 50 / 60 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz
Maximal load power	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	2300 W	2300 W	...
Protection level Up L/N	≤ 3 kV	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Socket type	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	CEE 7/5 E type	...	...	...	...
Maximal voltage	250 V AC / 50 Hz	320 V AC, 50 / 60 Hz	320 V AC, 50 / 60 Hz	320 V AC, 50 / 60 Hz	320 V AC, 50 / 60 Hz	250 V / 50 Hz	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Plug type	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	CEE 7/7	...	...	...	...
Nominal discharge current (L/N, L/PE, N/PE)	4 kA - 8/20 μs	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Protection level	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Class	...	2 type (Class C)	1+2 type (Class B+C)	2 type (Class C)	1+2 type (Class B+C)	...	...	...	...	...	...	...	...	...	...	...	...	...	≤ 1.3 kV	1.3 kV (L/N)	≤ 1.3 kV
Protection level Up	...	...	...	1.2 kV @ 8/20 μs (T2)	1.2 kV @ 10/350 μs (T1) 1.7 kV @ 8/20 μs (T2)	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Automatic delayed fuse	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Leak current	...	...	...	...	...	...	10 A / 250 V ≤ 0.5 mA	...	...	10 A / 250 V	✓	✓	≤ 0.5 mA	10 A / 250 V	10 A / 250 V	10 A / 250 V	10 A / 250 V	...	✓	≤ 0.5 mA	≤ 0.5 mA
Protection level Up L/PE, N/PE	≤ 1.3 kV	1.2 kV @ 8/20 μs (T2)	1.2 kV @ 10/350 μs (T1) 1.7 kV @ 8/20 μs (T2)	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
DC filter to eliminate interferences	...	...	...	...	...	...	...	...	...	...	...	...	...	...	RFI ≤ 10 dB	RFI ≤ 10 dB	RFI ≤ 10 dB	...	...	...	...
Number of outlets	...	...	...	...	...	2 grounded outlets 10A/250V	5 grounded outlets 10A/250V 2 non-grounded outlets 2.5A/250V	6 grounded outlets 16A/250V - CEE 7/5	5 grounded outlets 10A/250V	5 grounded outlets 10A/250V	8 grounded outlets 10A/250V	8 grounded outlets 10A/250V	5 grounded outlets 10A/250V	5 grounded outlets 10A/250V	5 grounded outlets 10A/250V	5 grounded outlets 10A/250V	5 grounded outlets 10A/250V • 2 USB ports 2A/5V	5 grounded outlets 10A/250V • 4 grounded outlets 10A/250V, • 2 USB ports 2.1A/5V	5 grounded outlets 16A/250V - (Schuko)	...	...
Wireless	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	• 433.92 MHz • Remote control • Operating range in open area : 30 m	...	...	...
Electric shock protection system	...	...	...	...	...	Ground connectors (pins) connected with ground wire of AC mains	...	...	...	...	...	...	...	...	...	...	...	...	...	Ground connectors (pins) connected with ground wire of AC mains	...
Nominal voltage of surge suppressor	...	...	...	...	...	...	250 V / 50 Hz	275 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	...	...	250 V	...
Nominal discharge current	...	...	...	5 kA @ 8/20 μs (T2)	8 kA @ 10/350 μs (T1) 20 kA @ 8/20 μs (T2)	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Maximum energy absorption	...	...	...	...	...	...	...	...	...	...	...	...	...	...	150 J	150 J	150 J	...	...	...	...
Response time	...	...	...	...	...	≤ 25 ns	≤ 25 ns	≤ 25 ns	≤ 25 ns	≤ 25 ns	≤ 25 ns	≤ 25 ns	≤ 25 ns	≤ 25 ns	≤ 25 ns	≤ 25 ns	≤ 25 ns	...	≤ 25 ns	≤ 25 ns	≤ 25 ns
Protection level of surge suppressor	...	...	...	...	...	≤ 1.3 kV (L/N)	≤ 1.3 kV (L/N)	< 1.5 kV (L/N)	≤ 1.3 kV (L/N)	≤ 1.3 kV (L/N)	≤ 1.3 kV (L/N)	≤ 1.3 kV (L/N)	≤ 1.3 kV (L/N)	≤ 1.3 kV (L/N)	...	...	...	...	...	...	...
Nominal discharge current (L/PE, N/PE)	...	5 kA @ 8/20 μs (T2)	8 kA @ 10/350 μs (T1) 20 kA @ 8/20 μs (T2)	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Nominal stroke current	...	...	...	...	...	2 kA (L/N) - (8/20μs)	2 kA (L/N) - (8/20μs)	1.5 kA (L/N) - (8/20μs)	2.5 kA (L/N) - 8/20 μs	2 kA (L/N) - 8/20 μs	2 kA (L/N) - 8/20 μs	2 kA (L/N) - 8/20 μs	1 kA (L/N) - (8/20μs)	...	...	...	...	...	2 kA (L/N) - 8/20 μs	2 kA (L/N) - (8/20μs)	2 kA (L/N) 8/20 μs 8/20 μs
Number of output outlets	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	• 1 MASTER outlet, two-contact with ground contact • 3 SLAVE outlets with auto switch off the power supply after switch off the receiver powered from MASTER outlet • 2 outlets separate from MASTER outlet	6
Maximum stroke current (L/N, L/PE, N/PE)	10 kA 8/20 μs (type 2)	20 kA @ 8/20 μs (T2)	50 kA @ 8/20 μs (T2)	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Operation state indication	✓	✓	✓	✓	✓	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Connectors type	2 x terminals	screw terminals	screw terminals	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Operation temp	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Switch	...	...	...	...	...	two-way, with light indication	with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	with light indication	with light indication	with light indication	...	Two-way switch - with light indication	two-way	2 pcs
Maximum stroke current	...	...	...	20 kA @ 8/20 μs (T2)	50 kA @ 8/20 μs (T2)	10 kA (L/N) - (8/20μs)	6.5 kA (L/N) - (8/20μs)	...	6.5 kA (L/N) - 8/20 μs	10 kA (L/N) - 8/20 μs 2 type	6.5 kA (L/N) - 8/20 μs	6.5 kA (L/N) - 8/20 μs	4.5 kA (L/N) - (8/20μs)	4.5 kA	4.5 kA	4.5 kA	...	...	6.5 kA (L/N) - 8/20 μs	6.5 kA (L/N) - (8/20μs)	6.5 kA (L/N)
Width in 17.5 mm modules	...	4	4	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Main features	...	...	...	Varistor	Varistor	...	...	• Mounting brackets for screwing the device to a flat surface or mounting with fastening ties • The body of the device rotates in the range of 180° relative to the mounting brackets • Outlets protected with a protection shutter • LED indication : Power supply, Overvoltage protection	...	• Current paths shutters • DC filter to eliminate interferences : ≤ 35 dB	...	...	...	...	...	...	...	• radio remote controller in the set • Remote controlled : Supports max. 5 devices • LED indicators displaying the device's operating status • Overload protection • Current paths shutters • Insulation - PVC • Wire gauge : 3 x 1.5 mm² • "Index of Protection" : IP20	...	...	...
Color	...	...	...	...	...	...	...	...	...	...	...	...	...	Black	Black	Black	Black	White + Gray	...	...	...
Power supply	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	• 230 V AC, 50 Hz • Remote control : 12V, type A23 battery (included)	...	...	...
Main features	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	• Easily readable LCD with backlight displaying detailed information on system state, • Supply voltage measurement : 80 V ... 250 V @ 50Hz, • Supply current measurement : 0.01 A ... 10 A @ 50/60 Hz, • Power measurement : 1 W ... 2500 W, • Energy measurement : 1 Wh ... 9999 Wh • Energy meter reset • Setting the alarm after exceeding the power consumption	...	...

Length of the cable	...	...	...	...	...	...	1.45 m	1.5 m	2.7 m	2.9 m	1.4 m	2.9 m	1.45 m	1.8 m	3.0 m	1.5 m	3 m	1.4 m	3 m	1.45 m	1.4 m
Housing	• Plastic • DIN, TS-35 rail mounting	Plastic, DIN, TS-35 rail mounting	Plastic, DIN, TS-35 rail mounting	Plastic	Plastic	Plastic - non-flammable	Plastic - non-flammable	Plastic	RACK 19", 1U, Plastic - non-flammable	RACK 19", 1U, Plastic - non-flammable	Plastic - non-flammable	RACK 19", 1U, Plastic - non-flammable	Plastic - non-flammable	Plastic (ABS)	Plastic (ABS)	Plastic (ABS)	Plastic	Plastic	Plastic - non-flammable	Plastic - non-flammable	Plastic - non-flammable
Weight	0.075 kg	0.334 kg	0.552 kg	0.042 kg	0.098 kg	0.12 kg	0.44 kg	0.59 kg	0.59 kg	0.93 kg	0.52 kg	0.61 kg	0.51 kg	0.306 kg	0.372 kg	0.318 kg	0.92 kg	0.35 kg	0.65 kg	0.56 kg	0.4 kg
Manufacturer / Brand		LEGRAND	LEGRAND	LEGRAND	LEGRAND			LEGRAND						AKYGA	AKYGA	AKYGA	ORNO	ORNO			
Dimensions	86 x 58 x 35 mm	71 x 83 x 70 mm	71 x 83 x 70 mm	62 x 54 x 17 mm	62 x 54 x 17 mm	131 x 55 x 75 mm	370 x 65 x 44 mm	423 x 66 x 100 mm	383 x 58 x 55 mm	484 x 54 x 55 mm	445 x 54 x 55 mm	445 x 54 x 55 mm	365 x 65 x 52 mm	305 x 50 x 40 mm	305 x 50 x 40 mm	305 x 50 x 40 mm	390 x 68 x 45 mm	94 x 78 x 78 mm	447 x 57 x 43 mm	447 x 55 x 53 mm	138 x 100 x 63 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years