

	POWER DISTRIBUTION UNIT L19/6VF	POWER DISTRIBUTION UNIT L19/6S	POWER DISTRIBUTION UNIT PD-6-5/RACK	POWER DISTRIBUTION UNIT L19/7E	POWER DISTRIBUTION UNIT PD-7/RACK	POWER DISTRIBUTION UNIT L19/8	POWER DISTRIBUTION UNIT PD-8/RACK-N	POWER DISTRIBUTION UNIT PD-4/R10	POWER DISTRIBUTION UNIT PD-4/R10S	POWER DISTRIBUTION UNIT PD-7/RACK/DEC	POWER DISTRIBUTION UNIT PD-8/RACK	POWER DISTRIBUTION UNIT PD-8/RACK/DEC	POWER DISTRIBUTION UNIT PD-7/RACK	POWER DISTRIBUTION UNIT PD-8/RACK	POWER DISTRIBUTION UNIT PD-9/RACK
	87.00 PLN 107.01 PLN	106.00 PLN 130.38 PLN	67.17 PLN 82.62 PLN	74.00 PLN 91.02 PLN	49.97 PLN 61.46 PLN	82.00 PLN 100.86 PLN	64.00 PLN 78.72 PLN	35.89 PLN 44.14 PLN	35.88 PLN 44.13 PLN	41.83 PLN 51.45 PLN	45.36 PLN 55.67 PLN	48.31 PLN 59.42 PLN	45.98 PLN 56.56 PLN	50.14 PLN 61.67 PLN	87.52 PLN 107.65 PLN
Rated voltage	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz
Total maximal current	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A
Maximal total load	3500 W	3500 W	3680 W	3500 W	3680 W	3500 W	4000 W	3500 W	3500 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W
Number of outlets	6 for universal plug 230 V (Schuko)	6 for universal plug 230 V (Schuko)	6 for universal plug 230 V (DIN 49441)	7 for universal plug 230 V (Schuko)	7 for universal plug 230 V (DIN 49441)	8 for universal plug 230 V (Schuko)	8 for universal plug 230 V (Schuko)	4 x CEE 7/5	4 x CEE 7/3 (Schuko)	7 for universal plug 230 V (DIN 49441)	8 for universal plug 230 V (DIN 49441)	8 for universal plug 230 V (DIN 49441)	7 for universal plug 230 V (DIN 49441)	8 for universal plug 230 V (DIN 49441)	8 for universal plug 230 V (DIN 49441)
Assembly	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 10" cabinets	In RACK 10" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets
Length of the power cable	1.8 m	1.8 m	2.15 m	1.8 m	2 m	1.8 m	1.8 m	1.8 m	1.8 m	2 m - cable with power connector IEC320 C14	2 m	2 m - cable with power connector IEC320 C14	2 m	2 m	3 m
Nominal voltage of surge suppressor	250 V / 50 Hz	250 V / 50 Hz
Protection level of surge suppressor	≤ 1.3 kV (L/N)
Main features	• Overvoltage protection • LED indicators displaying the device's operating status	Overload protection C16	..	Overload protection
Housing type	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U Rack 10"	1 U Rack 10"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	RACK 19", 1U	1 U RACK 19"	1 U RACK 19"
Switch	Yes (with built-in LED indicator)	✓	two-way, with light indication	Yes (with built-in LED indicator)	two-way, with light indication	Yes (with built-in LED indicator)	Yes (with built-in LED indicator and protected by a cover)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	..	Yes (with built-in LED indicator)	..	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	..
Dimensions	482 x 45 x 54 mm	478 x 45 x 79 mm	530 x 75 x 55 mm	484 x 45 x 56 mm	483 x 45 x 44 mm	484 x 45 x 57 mm	484 x 46 x 51 mm	257 x 45 x 45 mm	254 x 46 x 45 mm	482 x 46 x 44 mm	530 x 75 x 55 mm	482 x 46 x 44 mm	450 x 45 x 44 mm	450 x 45 x 44 mm	448 x 45 x 45 mm
Weight	0.75 kg	0.88 kg	0.830 kg	0.75 kg	0.72 kg	0.74 kg	0.72 kg	0.510 kg	0.550 kg	0.69 kg	0.830 kg	0.700 kg	0.35 kg	0.830 kg	0.85 kg
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00