

	VIDEO SPLITTER RV-16/32-UHD/R19	VIDEO SPLITTER RV-8/16-UHD/R	VIDEO SPLITTER RV-8/16-UHD/R19
			
	154.72 EUR 154.72 EUR	52.05 EUR 52.05 EUR	89.58 EUR 89.58 EUR
Standard	• AHD / HD-CVI / HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC	• AHD / HD-CVI / HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC	• AHD / HD-CVI / HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC
Number of inputs	16 pcs BNC	8 pcs BNC	8 pcs BNC
Number of outputs	32 pcs BNC	16 pcs BNC	16 pcs BNC
Bandwidth	0 ... 120 MHz (-3dB)	0 ... 120 MHz (-3dB)	0 ... 120 MHz (-3dB)
Inputs impedance	75 Ω	75 Ω	75 Ω
Outputs impedance	75 Ω	75 Ω	75 Ω
Input / Output protection	...	ESD, IEC 61000-4-2, ± 30 kV contact, ± 30 kV airLightning, IEC 61000-4-5, 12A ($t_P=8/20\mu s$)	...
Input protection	ESD, IEC 61000-4-2, ± 30 kV contact, ± 30 kV air Lightning, IEC 61000-4-5, 12A ($t_P=8/20\mu s$)	...	ESD, IEC 61000-4-2, ± 30 kV contact, ± 30 kV air Lightning, IEC 61000-4-5, 12A ($t_P=8/20\mu s$)
Outputs protection	ESD, IEC 61000-4-2, ± 30 kV contact, ± 30 kV air Lightning, IEC 61000-4-5, 12A ($t_P=8/20\mu s$)	...	ESD, IEC 61000-4-2, ± 30 kV contact, ± 30 kV air Lightning, IEC 61000-4-5, 12A ($t_P=8/20\mu s$)
Power supply	7 ... 26 V DC (power adapter not included)	7 ... 26 V DC (power adapter not included)	7 ... 26 V DC (power adapter not included)
Current consumption	120 mA @ 12 V DC	60 mA @ 12 V DC	120 mA @ 12 V DC
Gain	0 dB	0 dB	0 dB
Housing type	1 U Rack 19"	...	1 U Rack 19"
Dimensions	490 x 44 x 38 mm	218 x 40 x 22 mm (without stand)	490 x 44 x 38 mm
Weight	0.44 kg	0.13 kg	0.34 kg
Manufacturer / Brand	DELTA	DELTA	DELTA
Guarantee	5 years	5 years	5 years