	SIDE MAGNETIC CONTACT B/T SATEL	SIDE MAGNETIC CONTACT B/BR SATEL	SIDE MAGNETIC CONTACT B/DP SATEL	SIDE MAGNETIC CONTACT B/DP/BR SATEL	SIDE MAGNETIC CONTACT B/GP SATEL	SIDE MAGNETIC CONTACT B/GP/BR SATEL	SIDE MAGNETIC CONTACT B/IPT SATEL	SIDE MAGNETIC CONTACT B/IPT/BR SATEL	SIDE MAGNETIC CONTACT B/IS SATEL	SIDE MAGNETIC CONTACT B/IS/BR SATEL	SIDE MAGNETIC CONTACT B/S SATEL	SIDE MAGNETIC CONTACT B/S/BR SATEL	SIDE MAGNETIC CONTACT B/T SATEL	SIDE MAGNETIC CONTACT B/T/BR SATEL	SIDE MAGNETIC CONTACT B/T/IS SATEL	SIDE MAGNETIC CONTACT B/T/IS/BR SATEL	SIDE MAGNETIC CONTACT EN-GX1/VP33	SIDE MAGNETIC CONTACT EN-GX1/UNO/NO-OUTPUT	SIDE MAGNETIC CONTACT EN-GX1/WP33	SIDE MAGNETIC CONTACT EN-GX1/BWP33	SIDE MAGNETIC CONTACT EN-GX1/BWP33	SIDE MAGNETIC CONTACT EN-GX4/WP33	SIDE MAGNETIC CONTACT EN-GX1	SIDE MAGNETIC CONTACT EN-GX1	SIDE MAGNETIC CONTACT EN-MG1	SIDE MAGNETIC CONTACT EN-MG4	SIDE MAGNETIC CONTACT EN-MG	SIDE MAGNETIC CONTACT EN-MG	SIDE MAGNETIC CONTACT HIGHLY ALARMED/DP	MAGNETIC CONTACT S-S SATEL	MAGNETIC CONTACT S-S/BR SATEL	SIDE MAGNETIC CONTACT B/GN SATEL	SIDE MAGNETIC CONTACT B/GN/BR SATEL	SIDE MAGNETIC CONTACT B/S/BR SATEL	SIDE MAGNETIC CONTACT WITH TAMPER B/T/IS/BR SATEL	SIDE MAGNETIC CONTACT WITH TAMPER B/T/IS/BR SATEL	MAGNETIC CONTACT B-L/BR SATEL	MAGNETIC CONTACT B-L SATEL	MAGNETIC CONTACT B-L/BR SATEL
	2.62 EUR 2.62 EUR	2.62 EUR 2.62 EUR	3.10 EUR 3.10 EUR	3.10 EUR 3.10 EUR	3.34 EUR 3.34 EUR	3.34 EUR 3.34 EUR	3.34 EUR 3.34 EUR	3.34 EUR 3.34 EUR	3.34 EUR 3.34 EUR	3.34 EUR 3.34 EUR	2.86 EUR 2.86 EUR	2.86 EUR 2.86 EUR	7.61 EUR 7.61 EUR	7.61 EUR 7.61 EUR	6.01 EUR 6.01 EUR	6.01 EUR 6.01 EUR	5.46 EUR 5.46 EUR	5.46 EUR 5.46 EUR	11.87 EUR 11.87 EUR	11.87 EUR 11.87 EUR	1.54 EUR 1.54 EUR	1.54 EUR 1.54 EUR	1.54 EUR 1.54 EUR	1.54 EUR 1.54 EUR	1.99 EUR 1.99 EUR	1.99 EUR 1.99 EUR	20.22 EUR 20.22 EUR	5.75 EUR 5.75 EUR	17.13 EUR 17.13 EUR	6.33 EUR 6.33 EUR	6.77 EUR 6.77 EUR	6.36 EUR 6.36 EUR	6.08 EUR 6.08 EUR	6.99 EUR 6.99 EUR	5.27 EUR 5.27 EUR	9.58 EUR 9.58 EUR	10.25 EUR 10.25 EUR	10.25 EUR 10.25 EUR	8.82 EUR 8.82 EUR	8.53 EUR 8.53 EUR	8.53 EUR 8.53 EUR	8.53 EUR 8.53 EUR	8.53 EUR 8.53 EUR	8.45 EUR 8.45 EUR	5.94 EUR 5.94 EUR	5.94 EUR 5.94 EUR
In package																			**10 pcs The price for package**			**20 pcs The price for package**	**20 pcs The price for package**																
Detection	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window
Maximum reed switched voltage	100 V	100 V	100 V	100 V	100 V	100 V	100 V	100 V	100 V	100 V	100 V	100 V	100 V	100 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V
Maximal switched current	500 mA	500 mA	500 mA	500 mA	500 mA	500 mA	500 mA	500 mA	500 mA	500 mA	500 mA	500 mA	500 mA	500 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA
Contact type																			2DOL/NC - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed																							
Make distance	24 mm	24 mm	25 mm	25 mm	19 mm	19 mm	25 mm	25 mm	15.6 mm	15.6 mm	38 mm	38 mm	19 mm	19 mm	29 mm	29 mm	17 mm	17 mm	18 mm	18 mm	16 mm	18 mm	18 mm	18 mm	14 mm	18 mm	16 mm	18 mm	18 mm	19 mm	19 mm	19 mm	24 mm	49 mm	27 mm Wrost / 24 mm Steel	19 mm	18 mm	38 mm	30 mm	30 mm	25 mm	25 mm	18 mm	18 mm	18 mm
Tamper output																																			27 mm Wrost / 25 mm Steel										
Break distance	34 mm	34 mm	36 mm	36 mm	30 mm	30 mm	37 mm	37 mm	31 mm	31 mm	52 mm	52 mm	38 mm	38 mm	40 mm	40 mm	18 mm	18 mm	18 mm	18 mm	16 mm	18 mm	18 mm	18 mm	16 mm	18 mm	16 mm	18 mm	18 mm	19 mm	19 mm	19 mm	24 mm	49 mm	27 mm Wrost / 24 mm Steel	34 mm	38 mm	82 mm	33 mm	33 mm	30 mm	30 mm	72 mm	72 mm	72 mm
Main features	• Length of the cable - 40 cm • Flat casing design	• Length of the cable - 40 cm • Flat casing design	• Length of the cable - 60 cm • Small sealed pill shaped body	• Length of the cable - 60 cm • Small sealed pill shaped body	• Length of the cable - 60 cm • Small sealed pill shaped body	• Length of the cable - 60 cm • Small sealed pill shaped body	• 2x cable terminals • Small sealed pill shaped body • Can be mounted on any surface with double-sided adhesive tape attached at the back	• 2x cable terminals • Small sealed pill shaped body	• Length of the cable - 45 cm • Miniature sealed body	• Length of the cable - 45 cm • Miniature sealed body	Rugged, metal sealed body		EOL resistors - 1.1 kΩ 2DOL/NC		The contact is designed for surface mounting	• Plastic (ABS) • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Length of the cable - 35 cm	• Plastic (ABS) • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Length of the cable - 35 cm	• Plastic (ABS) • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed	• Plastic (ABS) • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed	Plastic (ABS)		• Plastic (ABS) • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Connectors - screw terminals • Leads out the cables - On the long edge	• Plastic (ABS) • NO output • Connectors - screw terminals • Leads out the cables - On the long edge	• Plastic (ABS) • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Length of the cable - 25 cm • Leads out the cables - On the short edge	• Plastic (ABS) • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Length of the cable - 25 cm • Leads out the cables - On the long edge	• Plastic (ABS) • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Length of the cable - 25 cm • Leads out the cables - On the long edge	• Plastic (ABS) • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Length of the cable - 25 cm • Leads out the cables - On the long edge	• Metal housing • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Length of the cable - 25 cm • Leads out the cables - On the short edge	• Rugged, metal sealed body • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Length of the cable - 25 cm	• Rugged, metal sealed body • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed	• Rugged, metal sealed body • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed	• Rugged, metal sealed body • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed	• Rugged, metal sealed body • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed	• Rugged, metal sealed body • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed	• Plastic ABS) • NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed • Connectors - screw terminals • Compatibility to EN 50131-2-6 @ Grade 2 standard • Environmental class EN 50131-1 - Class II • "Sales of Protection" - Grade 2	• Cable terminals • Tamper signaling	• Cable terminals • Tamper signaling	• Rugged, metal sealed body • Internal cables • Length of the cable - 33 cm	The contact is designed for surface mounting	The contact is designed for surface mounting			Tamper signaling	Tamper signaling
Color	White	Brown	White	Brown	White	Brown	White	Brown	White	Brown	Silver	White	White	Brown	White	Brown	White	Brown	White	White	White	White	White	White	White	White	White	White	White	White	White	White	White	White	White	White	White	White	White	White
Operation temp																																	-40 °C - 70 °C									
Weight	0.01 kg	0.01 kg	0.01 kg	0.01 kg	0.006 kg	0.006 kg	0.002 kg	0.002 kg	0.003 kg	0.003 kg	0.05 kg	0.05 kg	0.01 kg	0.01 kg	0.022 kg	0.022 kg	0.024 kg	0.024 kg	0.02 kg	0.02 kg	0.01 kg	0.012 kg	0.01 kg	0.01 kg	0.01 kg	0.01 kg	0.01 kg	0.01 kg	0.01 kg	0.01 kg	0.01 kg	0.01 kg	0.01 kg	0.08 kg	0.08 kg	0.08 kg	0.04 kg	0.04 kg	0.04 kg	0.04 kg	0.04 kg	0.04 kg	0.04 kg
Dimensions	28 x 12.5 x 7.3 mm	28 x 12.5 x 7.3 mm	68 x 20 x 5.5 mm	68 x 20 x 5.5 mm	28 x 9.5 x 5 mm	28 x 9.5 x 5 mm	28 x 10 x 6.5 mm	28 x 10 x 6.5 mm	37 x 8 x 6 mm	37 x 8 x 6 mm	50 x 17 x 9.8 mm	50 x 17 x 9.8 mm	31.5 x 15.5 x 7.3 mm	31.5 x 15.5 x 7.3 mm	21.5 x 13.5 x 7.3 mm	21.5 x 13.5 x 7.3 mm	31.5 x 13.5 x 7.3 mm	31.5 x 13.5 x 7.3 mm	27.3 x 15 x 8.5 mm	27.3 x 15 x 8.5 mm	• 64 x 13 x 13 mm • 64 x 19.5 x 13 mm	• 64 x 13 x 13 mm • 64 x 19.5 x 13 mm	• 64 x 13 x 13 mm • 64 x 19.5 x 13 mm	• 64 x 13 x 13 mm • 64 x 19.5 x 13 mm	47.5 x 14.5 x 11.9 mm	47.5 x 14.5 x 11.9 mm	61.9 x 19.7 x 12.9 mm - Bend switch 64.2 x 13.9 x 12.9 mm - Reed switch	61.9 x 19.7 x 12.9 mm - Bend switch 64.2 x 13.9 x 12.9 mm - Reed switch	27 x 14 x 8 mm	27.5 x 14 x 8 mm	50.7 x 9.9 x 7.4 mm - Bend switch 50.5 x 9.9 x 6.3 mm - Reed switch	50.8 x 15 x 12.2 mm	31.2 x 14.4 x 7.6 mm	49 x 19.5 x 9.8 mm	31.3 x 14.5 x 7.3 mm	49 x 19.7 x 9.7 mm	49 x 20 x 9.7 mm	105.8 x 15.8 x 15.6 mm	40 x 20.6 x 16.8 mm - Bend switch 40 x 14.5 x 16.8 mm - Reed switch	• Transmitter - 58.5 x 16.5 x 15.2 mm • magnet - 58.5 x 14.7 x 10.2 mm	• Transmitter - 58.5 x 16.5 x 15.2 mm • magnet - 58.5 x 14.7 x 10.2 mm	39 x 17 x 9.8 mm	31 x 9 x 12 mm	31 x 9 x 12 mm	66 x 13.5 x 11 mm	66 x 13.5 x 11 mm	13.5 x 33.5 x 7.3 mm	13.5 x 33.5 x 7.3 mm	13.5 x 33.5 x 7.3 mm
Manufacturer / Brand	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00