	[SIDE MAGNETIC CONTACT B-1 SATEL]	[SIDE MAGNETIC CONTACT B-1-BR SATEL]	[SIDE MAGNETIC CONTACT B-3 SATEL]	[SIDE MAGNETIC CONTACT K-1 SATEL]	[SIDE MAGNETIC CONTACT K-1-2E SATEL]	[SIDE MAGNETIC CONTACT K-1-2E-BR SATEL]	[SIDE MAGNETIC CONTACT KN-02]	[SIDE MAGNETIC CONTACT KN-02-BR]	[SIDE MAGNETIC CONTACT KN-04]	[SIDE MAGNETIC CONTACT KN-04-BR]	[SIDE MAGNETIC CONTACT KN-06]
	8.40 PLN 10.33 PLN	8.40 PLN 10.33 PLN	25.00 PLN 30.75 PLN	14.00 PLN 17.22 PLN	18.00 PLN 22.14 PLN	18.00 PLN 22.14 PLN	5.94 PLN 7.31 PLN	5.94 PLN 7.31 PLN	5.94 PLN 7.31 PLN	5.94 PLN 7.31 PLN	5.94 PLN 7.31 PLN
Detection	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window
Maximum switching voltage of the magnetic contact	100 V	100 V	100 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V
Maximum switching current	500 mA	500 mA	400 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA
Make distance	24 mm	24 mm	38 mm	18 mm	18 mm	18 mm	17 mm	17 mm	29 mm	29 mm	17 mm
Contact type	...	...	...	...	...	2EOL/NC	...	...	...	...	...
Break distance	29 mm	29 mm	42 mm	28 mm	28 mm	28 mm	18 mm	18 mm	30 mm	30 mm	18 mm
Main features	...	...	Rugged, metal sealed body	...	EOL resistors - 1.1 kΩ 2EOL/NC	The contact is designed for surface mounting	• Plastic (ABS) • NC output • Length of the cable : 30 cm	• Plastic (ABS) • NC output • Length of the cable : 30 cm	• Plastic (ABS) • NC output	• Plastic (ABS) • NC output	Plastic (ABS)
Color	White	Brown	Silver	White	White	Brown	White	Brown	White	Brown	White
Weight	0.01 kg	0.01 kg	0.05 kg	0.01 kg	0.015 kg	0.015 kg	0.01 kg	0.01 kg	0.022 kg	0.02 kg	0.024 kg
Manufacturer / Brand	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	...	...	...	...	...
Dimensions	28 x 12.5 x 7.3 mm	28 x 12.5 x 7.3 mm	50 x 17 x 9.8 mm	33,5 x 13.5 x 7.3 mm	33.5 x 13.5 x 7.3 mm	33.5 x 13.5 x 7.3 mm	27.3 x 15 x 8.5 mm	27.4 x 14 x 8.5 mm	• 64 x 13 x 13 mm • 64 x 19.5 x 13 mm	• 64 x 13 x 13 mm • 64 x 19.5 x 13 mm	67.5 x 14.5 x 11.9 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

	[SIDE MAGNETIC CONTACT KN-06-BR]	[SIDE MAGNETIC CONTACT KN-CA31]	[SIDE MAGNETIC CONTACT KN-CA31/NO NO OUTPUT]	[SIDE MAGNETIC CONTACT KN-CA32]	[SIDE MAGNETIC CONTACT KN-CA37]	[SIDE MAGNETIC CONTACT KN-CA37B]	[SIDE MAGNETIC CONTACT KN-CA38]	[SIDE MAGNETIC CONTACT KN-CA38B]	[SIDE MAGNETIC CONTACT KN-CA40]	[SIDE MAGNETIC CONTACT KN-CA42]	[SIDE MAGNETIC CONTACT KN-CA43]
	5.94 PLN 7.31 PLN	4.20 PLN 5.17 PLN	13.10 PLN 16.11 PLN	4.32 PLN 5.31 PLN	3.70 PLN 4.55 PLN	4.32 PLN 5.31 PLN	4.20 PLN 5.17 PLN	4.20 PLN 5.17 PLN	6.20 PLN 7.63 PLN	6.00 PLN 7.38 PLN	3.36 PLN 4.13 PLN
Detection	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window
Maximum switching voltage of the magnetic contact	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V
Maximum switching current	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA	20 mA
Make distance	17 mm	18 mm	18 mm	18 mm	18 mm	18 mm	18 mm	18 mm	18 mm	18 mm	18 mm
Contact type	...	...	...	...	...	...	...	...	...	...	...
Break distance	18 mm	28 mm	28 mm	28 mm	28 mm	28 mm	28 mm	28 mm	28 mm	28 mm	28 mm
Main features	Plastic (ABS)	• Plastic (ABS) • NC output • Connectors : screw terminals • Leads out the cables : On the long edge	• Plastic (ABS) • NO output • Connectors : screw terminals • Leads out the cables : On the long edge	• Plastic (ABS) • NC output • Length of the cable : 25 cm • Leads out the cables : On the long edge	• Plastic (ABS) • NC output • Length of the cable : 25 cm • Leads out the cables : On the short edge	• Plastic (ABS) • NC output • Length of the cable : 25 cm • Leads out the cables : On the long edge	• Plastic (ABS) • NC output • Length of the cable : 25 cm • Leads out the cables : On the short edge	• Plastic (ABS) • NC output • Length of the cable : 25 cm • Leads out the cables : On the long edge	• Plastic (ABS) • NC output • Connectors : screw terminals • Leads out the cables : On the long edge	• Plastic (ABS) • NC output • Connectors : screw terminals • Leads out the cables : On the long edge	• Plastic (ABS) • NC output • Length of the cable : 25 cm • Leads out the cables : On the long edge
Color	Brown	White	White	White	White	White	White	White	White	White	White
Weight	0.024 kg	0.02 kg	0.02 kg	0.017 kg	0.01 kg	0.01 kg	0.010 kg	0.012 kg	0.01 kg	0.02 kg	0.01 kg
Manufacturer / Brand	...	...	...	...	...	...	...	...	...	...	...
Dimensions	67.5 x 14.5 x 11.9 mm	63.9 x 19.7 x 12.9 mm - Reed switch 64.2 x 13.0 x 12.9 mm - magnet	63.9 x 19.7 x 12.9 mm - Reed switch 64.2 x 13.0 x 12.9 mm - magnet	64 x 13 x 13 mm	34.3 x 14 x 7.7 mm	33.7 x 13.3 x 7.5 mm	27 x 14 x 8 mm	28.5 x 14 x 8 mm	50.7 x 9.9 x 7.4 mm - Reed switch 50.5 x 9.9 x 8.3 mm - magnet	50.6 x 15.7 x 12 mm - Reed switch 50.4 x 14.4 x 12.4 mm - magnet	35 x 10 x 10.5 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

	[SIDE MAGNETIC CONTACT KN-CA44A]	[SIDE MAGNETIC CONTACT KN-CA44B]	[SIDE MAGNETIC CONTACT KN-CA50]	[SIDE MAGNETIC CONTACT KN-CA51]	[SIDE MAGNETIC CONTACT KN-CA52]	[SIDE MAGNETIC CONTACT KN-CA53]	[SIDE MAGNETIC CONTACT KN-CA56]	[SIDE MAGNETIC CONTACT KN-CA60B]	[SIDE MAGNETIC CONTACT KN-M02]	[SIDE MAGNETIC CONTACT KN-M04]	[SIDE MAGNETIC CONTACT KN-M06]
	5.50 PLN 6.76 PLN	6.00 PLN 7.38 PLN	3.04 PLN 3.74 PLN	17.10 PLN 21.03 PLN	18.30 PLN 22.51 PLN	6.88 PLN 8.46 PLN	9.60 PLN 11.81 PLN	19.20 PLN 23.62 PLN	18.38 PLN 22.61 PLN	23.21 PLN 28.55 PLN	19.50 PLN 23.98 PLN
Detection	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window
Maximum switching voltage of the magnetic contact	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V	20 V
Maximum switching current	20 mA	20 mA	20 mA	20 mA	10 mA	20 mA	20 mA	10 mA	10 mA	10 mA	10 mA
Make distance	18 mm	18 mm	18 mm	18 mm	19 mm	18 mm	18 mm	19 mm	19 mm	19 mm	24 mm
Contact type	...	...	...	...	...	...	...	...	...	...	...
Break distance	28 mm	28 mm	28 mm	28 mm	20 mm	28 mm	28 mm	20 mm	20 mm	20 mm	25 mm
Main features	• Plastic (ABS) • NC output • Connectors : screw terminals • Leads out the cables : On the long edge	• Plastic (ABS) • NC output • Connectors : screw terminals • Leads out the cables : On the long edge	• Plastic (ABS) • NC output • Length of the cable : 25 cm • Leads out the cables : On the long edge	• Metal housing • NC output • Length of the cable : 25 cm • Leads out the cables : On the short edge	• Rugged, metal sealed body • NC output • Length of the cables : 25 cm	• Plastic (ABS) • Hermetic casing • NC output • Length of the cables : 25 cm • Leads out the cables : On the long edge	• Metal housing • NC output • Length of the cable : 25 cm • Leads out the cables : On the short edge	• Rugged, metal sealed body • NC output • Length of the cables : 40 cm	• Rugged, metal sealed body • NC output	• Rugged, metal sealed body • NC output	• Rugged, metal sealed body • NC output
Color	White	White	White	Silver	Silver	White	Silver	Silver	Silver	Silver	Silver
Weight	0.02 kg	0.02 kg	0.015 kg	0.04 kg	0.1 kg	0.07 kg	0.14 kg	0.18 kg (total)	0.04 kg	0.125 kg	0.105 kg
Manufacturer / Brand	...	...	...	...	...	...	...	...	...	...	...
Dimensions	50.5 x 14.3 x 12.4 mm	50.8 x 15 x 12.2 mm	51 x 13 x 9.5 mm	31.2 x 14.4 x 7.6 mm	49 x 19.5 x 9.8 mm	88.4 x 16 x 16 mm	47.8 x 24.3 x 14.5 mm	104 x 50 x 8.5 mm - Reed switch 104.5 x 19 x 16.3 mm - Magnet	31.3 x 14.5 x 7.5 mm	49 x 19.7 x 9.7 mm	49 x 20 x 9.7 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

	[SIDE MAGNETIC CONTACT KN-M08]	[MAGNETIC CONTACT S-4 SATEL]	[MAGNETIC CONTACT S-4-BR SATEL]	[SIDE MAGNETIC CONTACT B-3A SATEL]	[SIDE MAGNETIC CONTACT B-1M SATEL]	[SIDE MAGNETIC CONTACT B-1M-BR SATEL]	[SIDE MAGNETIC CONTACT WITH TERMINALS B-1T SATEL]	[SIDE MAGNETIC CONTACT WITH TERMINALS B-1T-BR SATEL]	[MAGNETIC CONTACT K-1-BR SATEL]	[MAGNETIC CONTACT S-1 SATEL]	[MAGNETIC CONTACT S-1-BR SATEL]
	23.21 PLN 28.55 PLN	34.00 PLN 41.82 PLN	34.00 PLN 41.82 PLN	29.00 PLN 35.67 PLN	14.70 PLN 18.08 PLN	14.70 PLN 18.08 PLN	14.70 PLN 18.08 PLN	14.70 PLN 18.08 PLN	14.00 PLN 17.22 PLN	20.00 PLN 24.60 PLN	20.00 PLN 24.60 PLN
Detection	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window, Gate opening	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window	Opening the door or window
Maximum switching voltage of the magnetic contact	20 V	20 V	20 V	100 V	100 V	100 V	100 V	100 V	20 V	20 V	20 V
Maximum switching current	10 mA	20 mA	20 mA	400 mA	500 mA	500 mA	500 mA	500 mA	20 mA	20 mA	20 mA
Make distance	49 mm	18 mm	18 mm	38 mm	30 mm	30 mm	25 mm	25 mm	18 mm	18 mm	18 mm
Contact type	...	...	...	...	...	...	...	...	...	...	...
Break distance	50 mm	28 mm	28 mm	42 mm	33 mm	33 mm	30 mm	30 mm	28 mm	28 mm	28 mm
Main features	• Rugged, metal sealed body • NC output	• Cable terminals • Tamper signaling	• Cable terminals • Tamper signaling	• Rugged, metal sealed body • Armored cables	The contact is designed for surface mounting	The contact is designed for surface mounting	...	...	...	Tamper signaling	Tamper signaling
Color	Silver	White	Brown	...	White	Brown	White	Brown	Brown	White	Brown
Weight	0.16 kg	0.024 kg	0.024 kg	0.08 kg	0.02 kg	0.02 kg	0.02 kg	0.02 kg	0.01 kg	0.035 kg	0.035 kg
Manufacturer / Brand	...	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL	SATEL
Dimensions	105.8 x 15.8 x 15.4 mm	• Transmitter - 58.5 x 16.5 x 15.2 mm • magnet - 58.5 x 14.7 x 8.3 mm	• Transmitter : 58.5 x 16.5 x 15.2 mm • magnet : 58.5 x 14.7 x 8.3 mm	50 x 17 x 9.8 mm	51 x 9 x 12 mm	51 x 9 x 12 mm	66 x 13.5 x 11 mm	66 x 13.5 x 11 mm	13.5 x 33.5 x 7.3 mm	13.5 x 33.5 x 7.3 mm	13.5 x 33.5 x 7.3 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years