

	POWER SUPPLY ADAPTER 12V/230MA/5.5-ZOL	POWER SUPPLY ADAPTER 12V/0.5A/TRP	SWITCHING ADAPTER 12V/1A/5.5	SWITCHING ADAPTER 12V/1A/5.5*P100	SWITCHING ADAPTER ADS-12FC-12N Hikvision	POWER SUPPLY ADAPTER 12V/1.28A/5.5	POWER SUPPLY ADAPTER 12V/1.5A/5.5	POWER SUPPLY ADAPTER 12V/2A/5.5	POWER SUPPLY ADAPTER 12V/2A/5.5*P100	POWER SUPPLY ADAPTER PEM320-EN-S-DAHUA	POWER SUPPLY ADAPTER PEM320D-EN-DAHUA	POWER SUPPLY ADAPTER PEM321D-EN-DAHUA	POWER SUPPLY ADAPTER 12V/3A/5.5	POWER SUPPLY ADAPTER 12V/4A/5.5	POWER SUPPLY ADAPTER 12V/5A/5.5	POWER SUPPLY ADAPTER 12V/5A/5.5*P50	POWER SUPPLY ADAPTER 12V/10A/5.5-TAY
Power voltage	5.65 EUR 6.95 EUR	3.80 EUR 4.67 EUR	2.91 EUR 3.58 EUR	282.15 EUR 347.04 EUR	6.11 EUR 7.52 EUR	3.22 EUR 3.96 EUR	3.72 EUR 4.58 EUR	4.26 EUR 5.24 EUR	413.71 EUR 508.86 EUR	9.74 EUR 11.98 EUR	12.00 EUR 14.76 EUR	6.11 EUR 7.52 EUR	6.24 EUR 7.68 EUR	7.48 EUR 9.20 EUR	9.30 EUR 11.44 EUR	451.30 EUR 555.10 EUR	30.23 EUR 37.18 EUR
Power voltage	230 V AC																
Voltage frequency range	47 ... 63 Hz																
In package				100 pcs The price for package					100 pcs The price for package								50 pcs The price for package
Model identifier		12V/0.5A/TRP	12V/1A/5.5	12V/1A/5.5*P100				12V/2A/5.5	12V/2A/5.5*P100				12V/3A/5.5	12V/4A/5.5	12V/5A/5.5	12V/5A/5.5*P50	
Maximal load	0.25 A																
Input voltage		200 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 230 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	100 - 240 V AC	230 V AC
Output power	3 W																
AC input frequency		50 Hz	50 / 60 Hz	50 / 60 Hz	47 ... 63 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	47 ... 63 Hz
Output voltage	12 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC	12.0 V DC
Output current	0.5 A	1.0 A	1.0 A	1.0 A	1.0 A	1.25 A	1.5 A	2.0 A	2.0 A	2.0 A	2.0 A	2.0 A	3.0 A	4.0 A	5.0 A	5.0 A	10.0 A
Output power	6.0 W	12.0 W	12.0 W	12.0 W	12.0 W	15.0 W	8.0 W	24.0 W	24.0 W	24.0 W	24.0 W	12.0 W	36.0 W	48.0 W	60.0 W	60.0 W	120.0 W
Average efficiency during work		78.9 %	83.0 %	83.0 %	82.96 %	84.1 %	85.0 %	86.2 %	86.2 %				87.4 %	87.8 %	88.0 %	88.0 %	
Efficiency at low load (10%)		20.4 %	67.1 %	67.1 %		65.2 %	74.7 %	66.8 %	66.8 %				81.0 %	84.5 %	84.1 %	84.1 %	
No-load power consumption		< 0.10 W	< 0.10 W	< 0.10 W	< 0.10 W	< 0.10 W	< 0.10 W	< 0.10 W	< 0.10 W				< 0.10 W	< 0.10 W	< 0.21 W	< 0.21 W	
Adapter type	Transforming	Transforming	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching
Output voltage adjustment																	
Number of outputs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs
Power connectors type	• 230 V Plug • 12 V - 2.1/5.5 mm Straight plug	• 230 V Plug • 12 V - 2.1/5.5 mm Straight plug	• 230 V Plug • 12 V - 2.1/5.5 mm Straight plug	• 230 V Plug • 12 V - 2.1/5.5 mm Straight plug	• 230 V Plug • 12 V - 2.1/5.5 mm Straight plug	• 230 V Plug • 12 V - 2.1/5.5 mm Straight plug	• 230 V Plug • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug	• 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug
Housing type	Casing with plug	Desktop	Casing with plug	Casing with plug	Casing with plug	Casing with plug	Casing with plug	Desktop	Desktop	Casing with plug	Desktop	Desktop	Desktop	Desktop	Desktop	Desktop	Desktop
Manufacturer / Brand					Hikvision					DAHUA	DAHUA	DAHUA					
Protections			Overload	Overload	Overload	Overload	Overload	Overload	Overload				Overload	Overload	Overload	Overload	Overload
Length of the cable			1 m	1 m	1 m	1 m	1 m	1 m	1 m								
SAP Code					101701320												
Weight	0.24 kg	0.480 kg	0.125 kg	0.125 kg	0.08 kg	0.12 kg	0.14 kg	0.172 kg	0.172 kg	0.12 kg	0.17 kg	0.1 kg	0.26 kg	0.31 kg	0.34 kg	0.34 kg	0.49 kg
Dimensions	100 x 90 x 60 mm	85 x 58 x 50 mm	80 x 55 x 75 mm	80 x 55 x 75 mm	31 x 68 x 78 mm			91 x 53 x 31 mm	91 x 53 x 31 mm				110 x 50 x 30 mm	120 x 55 x 38 mm	121 x 57 x 36 mm	121 x 57 x 36 mm	121 x 57 x 36 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	3 years	3 years	3 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00