

	SWITCHING ADAPTER 12V/3A/PA4	SWITCHING ADAPTER 12V/8A/PA9	SWITCHING ADAPTER 12V/10A/PA18	SWITCHING ADAPTER 12V/21A/PA18	SWITCHING ADAPTER PEM340-5CH DAHUA	SWITCHING ADAPTER PEM341-9CH DAHUA	SWITCHING ADAPTER DS KAW50-1 Hikvision	SWITCHING ADAPTER PSDC-04124	SWITCHING ADAPTER PSDC-05125T	SWITCHING ADAPTER PSDC-08128T	SWITCHING ADAPTER PSDC-SEP-04124	SWITCHING ADAPTER ZK-100-8	SWITCHING ADAPTER PSDC-08128	SWITCHING ADAPTER PSDC-161214	SWITCHING ADAPTER PSDC-161216T	
	69.60 PLN 85.61 PLN	121.60 PLN 149.57 PLN	152.00 PLN 186.96 PLN	192.00 PLN 236.16 PLN	260.00 PLN 319.80 PLN	330.00 PLN 416.97 PLN	404.00 PLN 496.92 PLN	246.00 PLN 302.58 PLN	201.00 PLN 247.23 PLN	232.00 PLN 285.36 PLN	446.00 PLN 548.58 PLN	187.20 PLN 230.26 PLN	311.00 PLN 382.53 PLN	440.00 PLN 541.20 PLN	325.00 PLN 399.75 PLN	
Adapter type	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	
Output voltage	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 ... 15 V DC	12 ... 15 V DC	12 V ... 15 V DC	12 V ... 15 V DC	12 V DC	12 ... 15 V DC	12 ... 15 V DC	12 / 15 V DC	
Output voltage adjustment	11 ... 13 V	11 ... 12.7 V	11 ... 13 V	11 ... 13 V	—	—	11 ... 14 V DC	By potentiometer	✓ By potentiometer	✓ By potentiometer	✓ By potentiometer	Separate adjustment for each channel - By potentiometer	10.8 V ... 13.2 V DC - By potentiometer	✓ By potentiometer	✓ By potentiometer	✓ By potentiometer
Max. output current (total)	3.3 A	8 A	10 A	21 A	4 A	5 A	4.17 A	4 A	5 A	8 A	4 A	8 A	8 A	13.9 A	16 A	
Max. output current for single output	0.85 A	1.5 A	—	1.1 A	0.8 A	2.5 A	4.17 A	1 A	1 A	1 A	1 A	1 A	1 A	0.87 A	1 A	
Protections	• Overload • Short-circuit	• Overload • Short-circuit	—	—	—	—	—	—	—	—	—	—	—	—	—	
Outputs protection	—	—	—	—	2.5 A Glass Fuse	3.15 A Glass Fuse	—	1 A Polymer / Glass Fuse	1 A Glass Fuse	1 A Glass Fuse	4 x 1 A - Glass Fuse	1 A Glass Fuse	1 A Polymer / Glass Fuse	1 A Polymer / Glass Fuse	1 A Glass Fuse	
AW output (fault) - OC type 50mA, LED indication of at least one output fault	—	—	—	—	—	—	—	✓	—	—	—	—	—	✓	✓	
LED indication	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Main features	—	—	—	—	—	—	—	• Short-circuit protection • Overload protection • Overvoltage protection	—	—	—	—	—	—	—	
Protection	—	—	—	—	• Overload • Overvoltage	• Overload • Overvoltage	—	• Short-circuit • Overload • Overvoltage • Tamper	• Short-circuit • Overload • Overvoltage	• Short-circuit • Overload • Overvoltage	• Short-circuit • Overload • Overvoltage	• Short-circuit • Overload • Overvoltage	• Short-circuit • Overload • Overvoltage • Tamper	• Short-circuit • Overload • Overvoltage	• Short-circuit • Overload • Overvoltage	
Input voltage	230 V AC	230 V AC	230 V AC	230 V AC	90 ... 264 V	90 ... 264 V	100 V ... 240 V AC	230 V @ 50Hz	85 ... 264 V @ 50Hz	176 ... 264 V @ 50Hz	85 V ... 264 V AC	85 ... 264 V @ 50Hz	176 ... 264 V @ 50Hz	176 ... 264 V @ 50Hz	176 ... 264 V @ 50Hz	
Power	40 W	96 W	120 W (momentary 145W)	252 W	48 W (max)	60 W (max)	50 W	60 W (max)	60 W (max)	100 W (max)	48 W (max)	100 W (max)	120 W (max)	200 W (max)	200 W (max)	
Number of outputs	4	9	18	18	5	9	1	4	5	8	4	8	8	16	16	
Connector type	Cable terminals	Cable terminals	Cable terminals	Cable terminals	Cable terminals	Cable terminals	screw terminals	Cable terminals	Cable terminals	Cable terminals	Cable terminals	Cable terminals	Cable terminals	Cable terminals	Cable terminals	
Housing type	Metal, wall-mounted	Metal, wall-mounted	Metal, wall-mounted	Metal, wall-mounted	Metal, wall-mounted	Metal, wall-mounted	Metal, wall-mounted	Metal, wall-mounted	Metal, wall-mounted	Metal, wall-mounted	Metal, wall-mounted	Metal, wall-mounted	Metal, wall-mounted	Metal, wall-mounted	Metal, wall-mounted	
SAP Code	—	—	—	—	—	—	305300178	—	—	—	—	—	—	—	—	
Key closed	✓	✓	✓	✓	✓	✓	—	—	—	—	—	—	—	—	—	
Operation temp. / Relative humidity	—	—	—	—	-20 ... 45 °C / < 90 %	-20 ... 45 °C / < 90 %	—	—	-10 ... 50 °C / 20 ... 90 %	-10 ... 50 °C / 20 ... 90 %	—	-15 ... 50 °C / 20 ... 90 %	-10 ... 50 °C / 20 ... 90 %	-10 ... 50 °C / 20 ... 90 %	-10 ... 50 °C / 20 ... 90 %	
Weight	0.8 kg	1.47 kg	1.95 kg	1.89 kg	0.9 kg	0.9 kg	1.86 kg	1.34 kg	1.3 kg	1.79 kg	2.3 kg	1.704 kg	2 kg	2.5 kg	2.16 kg	
Dimensions	165 x 165 x 51 mm	236 x 207 x 52 mm	315 x 207 x 55 mm	212 x 314 x 65 mm	165 x 165 x 50 mm	165 x 165 x 50 mm	267 x 244 x 81 mm	230 x 177 x 60 mm	230 x 176 x 59 mm	295 x 245 x 60 mm	220 x 210 x 80 mm	340 x 210 x 90 mm	280 x 256 x 58 mm	280 x 256 x 58 mm	290 x 241 x 59 mm	
Manufacturer / Brand	—	—	—	—	DAHUA	DAHUA	Hikvision	PULSAR	PULSAR	PULSAR	PULSAR	PULSAR	PULSAR	PULSAR	PULSAR	
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00