

	SWITCHING ADAPTER 12V/1A/1ER	SWITCHING ADAPTER 12V/3.2A/2P	SWITCHING ADAPTER ADLS-120-12 ADLER Power	SWITCHING ADAPTER ADLS-120-24 ADLER Power	SWITCHING ADAPTER ADLS-40-12 ADLER Power	SWITCHING ADAPTER ADLS-40-24 ADLER Power	SWITCHING ADAPTER ADLS-80-12 ADLER Power	SWITCHING ADAPTER ADLS-80-24 ADLER Power	SWITCHING ADAPTER DSM-60-12ST MEAN WELL	SWITCHING ADAPTER LRS-100-12 MEAN WELL	SWITCHING ADAPTER LRS-150-12 MEAN WELL	SWITCHING ADAPTER LRS-35-12 MEAN WELL	SWITCHING ADAPTER LRS-50-12 MEAN WELL	SWITCHING ADAPTER LRS-75-12 MEAN WELL	SWITCHING ADAPTER RS-15-12 MEAN WELL	SWITCHING ADAPTER RS-25-12 MEAN WELL	SWITCHING ADAPTER 12V/10A/2P	SWITCHING ADAPTER 12V/15A/2P	SWITCHING ADAPTER 12V/20A/2P	SWITCHING ADAPTER 12V/25A/2P	SWITCHING ADAPTER 12V/30A/2P	SWITCHING ADAPTER 12V/35A/2P4	SWITCHING ADAPTER PDM3200-015 DAHUA	SWITCHING ADAPTER PMT-12V150W/2BA Delta Electronics	SWITCHING ADAPTER PMT-12V150W/2BA Delta Electronics	SWITCHING ADAPTER PMT-12V250W/2BA Delta Electronics	SWITCHING ADAPTER PSSD ROGER	
																												
Adapter type	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching	Switching
Frequency range	...	...	...	...	...	...	...	...	...	...	selectable by switch • 85 V ... 132 V AC • 170 V ... 264 V AC	...	...	...	47 ... 63 Hz	47 ... 63 Hz	...	...	...	...	...	...	50 / 60 Hz	...	...	...	...	...
Power voltage	100 ... 240 V AC	230 V AC	230 V AC	230 V AC	230 V AC	230 V AC	230 V AC	230 V AC	100 ... 240 V AC	85 ... 264 V AC	...	85 ... 264 V AC	85 ... 264 V AC	85 ... 264 V AC	85 ... 264 V AC	88 ... 264 V AC	230 V AC	230 V AC	• 110 V AC • 230 V AC	230 / 115 V AC	110 / 230 V AC	230 V AC	100 ... 240 V AC	100 V ... 240 V AC 50/60 Hz	100 V ... 240 V AC	selectable by switch • 100 V ... 120 V AC, • 200 V ... 240 V AC	100 V ... 240 V AC	230 V AC
Number of fan coolers	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	1 pcs	1 pcs	1 pcs	...	...	...	...	...	...	...
Operating frequency	...	...	...	...	...	...	...	...	50 / 60 Hz	47 ... 63 Hz	47 ... 63 Hz	47 ... 63 Hz	47 ... 63 Hz	47 ... 63 Hz	47 ... 63 Hz	...	...	...	...	1 pcs	1 pcs	1 pcs	...	...	...	...	...	...
Output voltage	12 V DC	12 V DC	12 V DC	24 V DC	12 V DC	24 V DC	12 V DC	24 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	13.8 V DC
Output voltage adjustment	...	11 ... 13.8 V	10.8 ... 13.2 V	21.6 ... 26.4 V	—	—	10.8 ... 13.2 V	21.6 ... 26.4 V	—	10.2 ... 13.8 V	10.2 ... 13.8 V	10.2 ... 13.8 V	10.2 ... 13.8 V	10.2 ... 13.8 V	10.2 ... 13.8 V	10.2 ... 13.8 V	10.2 ... 15 V	9.8 ... 13 V	10.4 ... 14.2 V	11 ... 12.7 V	10.3 ... 13.7 V	11 ... 15 V	—	10.8 ... 13.2 V	11.4 ... 13.5 V	10.8 ... 13.2 V	—	
Maximal load	1 A	3.2 A	10 A	5 A	3.3 A	1.7 A	6.7 A	3.33 A	5 A	8.5 A	12.5 A	3 A	4.2 A	9 A	1.3 A	2.1 A	10 A	15 A	20 A	25 A	41 A	5 A	• 5 A (total) • 2 A / Single output - Polymer fuse	1.5 A	8.5 A	12.5 A	4.2 A	10.8 A
Output power	12 W	38 W	120 W	120 W	39 W	40 W	80 W	102 W	60 W	102 W	150 W	36 W	50.4 W	72 W	15.6 W	25.2 W	120 W	180 W	240 W	300 W	500 W	60 W	60 W	18 W	102 W	150 W	50.4 W	150 W
Number of outputs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	2 pcs	2 pcs	3 pcs	3 pcs	3 pcs	...	4 pcs	1 pcs	2 pcs	1 pcs	2 pcs	2 pcs
Operation temp	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
MTBF (Mean Time Between Faults)	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Protections	Short-circuit	• Short-circuit • Overload	• Short-circuit • Overload • Overvoltage • Overheat	• Short-circuit • Overload • Overvoltage • Overheat	• Short-circuit • Overload • Overvoltage • Overheat	• Short-circuit • Overload • Overvoltage • Overheat	• Short-circuit • Overload • Overvoltage • Overheat	• Short-circuit • Overload • Overvoltage • Overheat	• Short-circuit • Overload • Overvoltage	• Short-circuit • Overload • Overvoltage	• Short-circuit • Overload • Overvoltage	• Short-circuit • Overload • Overvoltage	• Short-circuit • Overload • Overvoltage	• Short-circuit • Overload • Overvoltage	• Short-circuit • Overload • Overvoltage	• Short-circuit • Overload • Overvoltage	• Short-circuit • Overload	• Short-circuit • Overload	• Overload • Short-circuit	Overvoltage, Overload	• Short-circuit • Overload	• Short-circuit • Overload	• Overload • Short-circuit • Overvoltage • Overheat	• Short-circuit • Overload • Overvoltage • Overheat	• Short-circuit • Overload • Overvoltage • Overheat	• Short-circuit • Overload • Overvoltage • Overheat	• Short-circuit • Overload • Overvoltage • Overheat	• Short-circuit • Overload • Overvoltage • Overheat
Housing type	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Operation temp. / Relative humidity	...	-10 °C ... 50 °C / 20 % ... 90 %	-10 °C ... 50 °C / 20 % ... 90 %	-10 °C ... 50 °C / 20 % ... 90 %	-10 °C ... 50 °C / 20 % ... 90 %	-10 °C ... 50 °C / 20 % ... 90 %	-10 °C ... 50 °C / 20 % ... 90 %	-10 °C ... 50 °C / 20 % ... 90 %	-30 °C ... 70 °C / 20 % ... 90 %	-30 °C ... 70 °C / 20 % ... 90 %	-30 °C ... 70 °C / 20 % ... 90 %	-30 °C ... 70 °C / 20 % ... 90 %	-30 °C ... 70 °C / 20 % ... 90 %	-30 °C ... 70 °C / 20 % ... 90 %	-20 °C ... 70 °C / 20 % ... 90 %	-20 °C ... 70 °C / 20 % ... 90 %	-10 °C ... 50 °C / 20 % ... 90 %	-10 °C ... 50 °C / 20 % ... 90 %	-10 °C ... 50 °C / 20 % ... 90 %	-10 °C ... 50 °C / 20 % ... 90 %	-10 °C ... 60 °C / 20 % ... 90 %	-10 °C ... 60 °C / 20 % ... 90 %	Plastic	-30 °C ... 70 °C / 5 % ... 95 %	-30 °C ... 70 °C / 5 % ... 95 %	-10 °C ... 70 °C / 5 % ... 95 %	-10 °C ... 70 °C / 20 % ... 90 %	-10 °C ... 40 °C / 20 % ... 90 %
Main features	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Weight	0.05 kg	0.18 kg	0.230 kg	0.237 kg	0.140 kg	0.145 kg	0.175 kg	0.166 kg	0.21 kg	0.31 kg	0.41 kg	0.2 kg	0.22 kg	0.11 kg	0.17 kg	0.452 kg	0.56 kg	0.66 kg	0.710 kg	1.38 kg	0.27 kg	0.23 kg	0.090 kg	0.29 kg	0.36 kg	0.18 kg	0.42 kg	
Manufacturer / Brand	...	...	ADLER Power	ADLER Power	ADLER Power	ADLER Power	ADLER Power	ADLER Power	MEAN WELL	MEAN WELL	MEAN WELL	MEAN WELL	MEAN WELL	MEAN WELL	MEAN WELL	MEAN WELL	MEAN WELL	MEAN WELL	MEAN WELL	MEAN WELL	MEAN WELL	MEAN WELL	DAHUA	Delta Electronics	Delta Electronics	Delta Electronics	Delta Electronics	ROGER
Dimensions	76 x 38 x 23 mm	101 x 78 x 37 mm	188 x 46 x 34 mm	188 x 46 x 36 mm	126 x 46 x 33 mm	125 x 46 x 33 mm	160 x 41 x 33 mm	109 x 53 x 34 mm	129 x 97 x 30 mm	159 x 97 x 30 mm	99 x 82 x 30 mm	99 x 82 x 30 mm	99 x 82 x 30 mm	100 x 97 x 30 mm	76 x 52 x 28 mm	92 x 52 x 28 mm	200 x 98 x 42 mm	200 x 100 x 43 mm	200 x 110 x 51 mm	200 x 110 x 50 mm	241 x 124 x 66 mm	160 x 98 x 42 mm	148 x 55 x 37 mm	77 x 52 x 30 mm	127 x 97 x 30 mm	159 x 97 x 30 mm	159 x 97 x 30 mm	
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	2 years	2 years	2 years	2 years	2 years	2 years	3 years	5 years	5 years	5 years	5 years	3 years