

| | POWER SUPPLY ADAPTER RACK 15-PSA2018U 24 V AC 20 A | AC POWER SUPPLY ADAPTER PSAC-08246 METAL ENCLOSURE TRANSFORMING | AC POWER SUPPLY ADAPTER 24V/3A/AC |
|---|---|--|---|
| |  |  |  |
| | 146.01 EUR 179.59 EUR | 90.83 EUR 111.72 EUR | 42.28 EUR 52.00 EUR |
| Adapter type | Transforming | Transforming | Transforming |
| Power voltage | 230 V AC | ... | 230 V AC |
| Output voltage | 24 V AC | 24 / 27 V AC | 24 V AC |
| Maximal load | 20 A | ... | 3 A |
| Output voltage adjustment | — | ✓ (step adjustment) | ... |
| Max. output current (total) | ... | 6 A | ... |
| Application | ... | ... | motor rotators, Speed Dome cameras |
| Output power | 480 W | ... | ... |
| Max. output current for single output | ... | 0.75 A | ... |
| Outputs protection | ... | 1 A Polymer / Glass Fuse | ... |
| Protection type | PTC Polymer Fuse : 18x 2 A (max) | ... | ... |
| LED indication | ... | ✓ | ... |
| Output | 18 pcs Cable terminals | ... | 1 pcs |
| AW output (fault) - OC type 50mA, LED indication of at least one output fault | ... | ✓ | ... |
| Housing type | 1.5 U Rack 19" | ... | ... |
| Operation temp | -10 ... 45 °C | ... | ... |
| Protection | ... | <ul style="list-style-type: none"> • Short-circuit • Overload • Overheat • Overvoltage • Tamper | ... |
| Input voltage | ... | 230 V @ 50Hz | ... |
| Power | ... | 150 VA | ... |
| Number of outputs | ... | 8 | ... |
| Connector type | ... | Cable terminals | ... |
| Housing type | ... | Metal, wall-mounted | ... |
| Key closed | ... | — | ... |
| Weight | 6.32 kg | 3.0 kg | 1.13 kg |
| Dimensions | 482 x 200 x 65 mm Rack 19" 1.5 U | 246 x 215 x 64 mm | Ø 87 x 43 mm |
| Manufacturer / Brand | ... | PULSAR | ... |
| Guarantee | 2 years | 2 years | 2 years |