

	OVERVOLTAGE LIMITER ACAR-MINI-AGD	POWER DISTRIBUTION UNIT ACAR-P7 (5 + 2 OUTLETS)	POWER DISTRIBUTION UNIT ACAR-504WE/RACK	POWER DISTRIBUTION UNIT ACAR-S8/FA/RACK	POWER DISTRIBUTION UNIT ACAR-XPROTECTOR	POWER DISTRIBUTION UNIT LE-50095 (4 OUTLETS) 1.5 m LEGRAND	POWER DISTRIBUTION UNIT LE-50097 (6 OUTLETS) 1.5 m LEGRAND	POWER DISTRIBUTION UNIT AK-SP-05A AKYGA	POWER DISTRIBUTION UNIT AK-SP-05B AKYGA	POWER DISTRIBUTION UNIT AK-SP-05U (5 OUTLETS + 2 USB) AKYGA	POWER DISTRIBUTION UNIT WITH REMOTE CONTROL OR-AE-13137 (5 OUTLETS) ORNO	POWER DISTRIBUTION UNIT OR-AE-13144 (4 SOCKETS + 2 USB) ORNO	POWER DISTRIBUTION UNIT ACAR-DIGITAL (6 OUTLETS)	POWER DISTRIBUTION UNIT ACAR-ECO-PLUS (6 OUTLETS)	
Rated current	9.80 EUR 12.85 EUR	11.48 EUR 14.12 EUR	26.88 EUR 23.06 EUR 10 A (total)	21.81 EUR 26.93 EUR	14.25 EUR 17.53 EUR	16.57 EUR 20.36 EUR	18.45 EUR 22.69 EUR	5.07 EUR 6.24 EUR	6.20 EUR 7.63 EUR	8.80 EUR 10.82 EUR	30.71 EUR 37.77 EUR	10.57 EUR 13.00 EUR	41.02 EUR 50.45 EUR	38.04 EUR 46.79 EUR	
Rated voltage	230 V AC / 50 Hz	230 V 230 V AC / 50 Hz	230 V AC	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	
Nominal voltage	...	...	...	10 A (total)	...	...	...	...	...	...	...	...	10 A (total)	...	
Nominal load current	10 A	10 A	...	10 A	10 A	16 A	16 A	10 A	10 A	10 A	10 A	10 A	10 A	10 A	
Total maximal current	10 A	10 A	...	10 A	10 A	16 A	16 A	10 A	10 A	10 A	10 A	10 A	10 A	10 A	
Maximal total load	2300 W	2300 W	...	2300 W	2300 W	3500 W	3500 W	2500 W	2500 W	2500 W	2300 W	2300 W	2300 W	2300 W	
Fuse	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
Maximal load power	...	...	...	...	...	...	...	...	...	...	...	...	...	10 A / 250 V	
Socket type	...	...	...	...	...	...	...	...	...	...	...	...	2300 W	2300 W	
Maximal voltage	250 V / 50 Hz	...	...	...	...	...	...	...	...	...	...	...	...	...	
Plug type	...	...	...	...	...	...	...	...	...	...	...	...	CEE 7/5 E type	...	
Protection level	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
Automatic delayed fuse	...	10 A / 250 V	...	✓	10 A / 250 V	...	...	10 A / 250 V	10 A / 250 V	10 A / 250 V	...	...	...	≤ 1.3 kV	
Leak current	...	< 0.5 mA	< 0.5 mA	< 0.5 mA	< 0.5 mA	...	...	...	...	...	...	...	...	< 0.5 mA	
DC filter to eliminate interferences	...	...	...	...	...	...	...	RFI ≤ 10 dB	RFI ≤ 10 dB	RFI ≤ 10 dB	...	...	...	< 0.5 mA	
Wireless	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
Number of outlets	2 grounded outlets 10A/250V	5 grounded outlets 10A/250V 2 non-grounded outlets 2.5A/250V	5 grounded outlets 10A/250V	8 grounded outlets 10A/250V	5 grounded outlets 10A/250V	4 grounded outlets 10A/250V	6 grounded outlets 10A/250V	5 grounded outlets 10A/250V	5 grounded outlets 10A/250V	5 grounded outlets 10A/250V	• 5 grounded outlets 10A/250V • 2 USB ports 2A/5V	5 grounded outlets 10A/250V	• 4 grounded outlets 10A/250V, • 2 USB ports 2.1A/5V	5 grounded outlets 16A/250V - (Schuko)	...
Response time	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	< 25 ns	
Wire gauge	...	...	...	...	...	3 x 1.5 mm <sup>2</sup>	3 x 1.5 mm <sup>2</sup>	...	...	...	...	...	...	...	
Nominal voltage of surge suppressor	...	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	...	...	...	250 V	
Electric shock protection system	Ground connectors (pins) connected with ground wire of AC mains	...	...	...	...	...	...	...	...	...	...	...	...	Ground connectors (pins) connected with ground wire of AC mains	
Maximum energy absorption	...	...	...	...	...	...	...	150 J	150 J	150 J	...	...	...	...	
Protection level of surge suppressor	≤ 1.3 kV (L/N)	≤ 1.3 kV (L/N)	≤ 1.3 kV (L/N)	≤ 1.3 kV (L/N)	≤ 1.3 kV (L/N)	≤ 1 kV (L/N)	≤ 1 kV (L/N)	...	...	...	...	...	...	...	
Nominal stroke current	2 kA (L/N) - (8/20µs)	2 kA (L/N) - (8/20µs)	2.5 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	1 kA (L/N) - (8/20µs)	2 kA (L/N) - (8/20µs)	2 kA (L/N) - (8/20µs)	...	...	...	...	...	2 kA (L/N) - 8/20 µs	2 kA (L/N) - (8/20µs)	
Number of output outlets	...	...	...	...	...	...	...	...	...	...	...	...	...	• 1 MASTER outlet, two-contact with ground contact • 3 SLAVE outlets with auto switch off the power supply after switch off the receiver powered from MASTER outlet • 2 outlets separate from MASTER outlet	
Switch	...	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	with light indication	with light indication	with light indication	---	---	Two-way switch - with light indication	two-way	
Operation temp	...	...	...	...	...	...	...	5 °C ... 50 °C	5 °C ... 50 °C	5 °C ... 50 °C	...	...	...	...	
Maximum stroke current	10 kA (L/N) - (8/20µs)	6.5 kA (L/N) - (8/20µs)	6.5 kA (L/N) - 8/20 µs	6.5 kA (L/N) - 8/20 µs	4.5 kA (L/N) - (8/20µs)	4 kA (L/N) - (8/20µs)	4 kA (L/N) - (8/20µs)	4.5 kA	4.5 kA	4.5 kA	...	...	6.5 kA (L/N) - 8/20 µs	6.5 kA (L/N) - (8/20µs)	
Main features	...	...	...	...	...	...	...	...	...	...	...	...	...	• radio remote controller in the set • Remote controlled: • Supports max. 5 devices • LED indicators displaying the device's operating status • Overload protection • Current paths shutters • Insulation - PVC • Wire gauge: 3 x 1.5 mm <sup>2</sup> • "Index of Protection": IP20	
Color	...	...	...	...	...	...	...	Black	Black	Black	Black	White + Gray	...	...	
Power supply	...	...	...	...	...	...	...	...	...	...	...	• 230 V AC, 50 Hz • Remote controller: 12V, type A23 battery (included)	...	...	
Main features	...	...	...	...	...	...	...	...	...	...	...	...	...	• Easily readable LCD with backlight displaying detailed information on system state, • Supply voltage measurement: 80 V ... 250 V @ 50Hz, • Supply current measurement: 0.01 A ... 10 A @ 50/60 Hz, • Power measurement: 1 W ... 2500 W, • Energy measurement: 1 Wh ... 9999 Wh • Energy meter reset • Setting the alarm after exceeding the power consumption	
Length of the cable	...	1.45 m	2.7 m	2.9 m	1.45 m	1.5 m	1.5 m	1.8 m	3.0 m	1.5 m	3 m	1.4 m	3 m	1.45 m	
Housing	Plastic - non-flammable	Plastic - non-flammable	RACK 19", 1U, Plastic - non-flammable	RACK 19", 1U, Plastic - non-flammable	Plastic - non-flammable	Plastic	Plastic	Plastic (ABS)	Plastic (ABS)	Plastic (ABS)	Plastic	Plastic	Plastic - non-flammable	Plastic - non-flammable	
Weight	0.12 kg	0.44 kg	0.59 kg	0.61 kg	0.51 kg	0.47 kg	0.54 kg	0.306 kg	0.372 kg	0.318 kg	0.92 kg	0.35 kg	0.65 kg	0.56 kg	
Manufacturer / Brand	...	...	...	...	...	LEGRAND	LEGRAND	AKYGA	AKYGA	AKYGA	ORNO	ORNO	...	...	
Dimensions	131 x 55 x 75 mm	370 x 65 x 44 mm	383 x 58 x 55 mm	445 x 54 x 55 mm	365 x 65 x 52 mm	315 x 90 x 63 mm	410 x 90 x 63 mm	305 x 50 x 40 mm	305 x 50 x 40 mm	305 x 50 x 40 mm	390 x 68 x 45 mm	94 x 78 x 78 mm	447 x 57 x 43 mm	447 x 55 x 53 mm	
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00