

	POWER DISTRIBUTION UNIT L19&VP	POWER DISTRIBUTION UNIT PD-6-P/RACK	POWER DISTRIBUTION UNIT L19&ZF	POWER DISTRIBUTION UNIT PD-6/R	POWER DISTRIBUTION UNIT PD-6/R-1P 1.8 m	POWER DISTRIBUTION UNIT PD-6/R-2P 1.8 m	POWER DISTRIBUTION UNIT PD-6/R-3P	POWER DISTRIBUTION UNIT PD-6/R-SPD-1L	POWER DISTRIBUTION UNIT PD-6/R-SPD-3L	POWER DISTRIBUTION UNIT PD-6/R-USB	POWER DISTRIBUTION UNIT PD-6/R-VA	POWER DISTRIBUTION UNIT PD-7/RACK	POWER DISTRIBUTION UNIT PD-8/R	POWER DISTRIBUTION UNIT PD-8/R/IEC 1.8 m	POWER DISTRIBUTION UNIT PD-8/R/IEC-N 1.8 m	POWER DISTRIBUTION UNIT PD-9/R	POWER DISTRIBUTION UNIT PD-9/R/IEC 1.8 m	POWER DISTRIBUTION UNIT L19&B	POWER DISTRIBUTION UNIT PD-7/R&N 1.8 m	POWER DISTRIBUTION UNIT PD-8/RACK-N	POWER DISTRIBUTION UNIT PD-4/R10	POWER DISTRIBUTION UNIT PD-4/R10/R 1.8 m	POWER DISTRIBUTION UNIT PD-7/RACK/IEC	POWER DISTRIBUTION UNIT PD-8/RACK	POWER DISTRIBUTION UNIT PD-8/RACK/IEC	POWER DISTRIBUTION UNIT PD-7/RACK	POWER DISTRIBUTION UNIT PD-8/RACK	POWER DISTRIBUTION UNIT ACAR-F5&FA/RACK	POWER DISTRIBUTION UNIT ACAR-S8&FA/RACK	POWER DISTRIBUTION UNIT PD-9/RACK	
																															
	19.55 EUR 19.80 EUR	16.60 EUR 16.60 EUR	22.24 EUR 24.00 EUR	16.10 EUR 16.10 EUR	18.78 EUR 18.78 EUR	22.62 EUR 22.62 EUR	17.63 EUR 17.63 EUR	18.78 EUR 18.78 EUR	21.47 EUR 21.47 EUR	24.92 EUR 24.92 EUR	49.45 EUR 49.45 EUR	17.60 EUR 17.60 EUR	17.63 EUR 17.63 EUR	17.63 EUR 17.63 EUR	20.70 EUR 20.70 EUR	17.25 EUR 17.25 EUR	18.02 EUR 18.02 EUR	20.70 EUR 20.70 EUR	19.15 EUR 19.15 EUR	16.87 EUR 16.87 EUR	14.36 EUR 14.36 EUR	15.33 EUR 15.33 EUR	18.89 EUR 18.89 EUR	22.85 EUR 22.85 EUR	20.51 EUR 20.51 EUR	19.94 EUR 19.94 EUR	22.33 EUR 22.33 EUR	27.01 EUR 27.01 EUR	28.35 EUR 28.35 EUR	28.59 EUR 28.59 EUR	
Rated voltage	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	230 V AC / 50 Hz	
Nominal load current	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	10 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	16 A	max. 10 A (total)	10 A (total)	16 A	
Total maximal current	3500 W	3680 W	3500 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	3680 W	2500 W	3680 W	3680 W	3500 W	4000 W	4000 W	3500 W	4000 W	3680 W	3680 W	3680 W	3680 W	3680 W	2300 W	...	3680 W	
Assembly	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets	In RACK 19" cabinets
Number of outlets	6 for universal plug 230 V (Schuko)	6 for universal plug 230 V (DIN 49441)	7 for universal plug 230 V (Schuko)	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	6 x CEE 7/5	7 x CEE 7/5	8 x CEE 7/5	8 x CEE 7/5	8 x CEE 7/5	8 x CEE 7/5	9 x CEE 7/5	9 x CEE 7/5	8 for universal plug 230 V (Schuko)	7 x CEE 7/5	8 for universal plug 230 V (Schuko)	4 x CEE 7/5	4 x CEE 7/5	7 x CEE 7/5	8 for universal plug 230 V (DIN 49441)	8 for universal plug 230 V (DIN 49441)	7 x CEE 7/5	8 for universal plug 230 V (DIN 49441)	5 grounded outlets 10A/250V	8 grounded outlets 10A/250V	9 for universal plug 230 V (DIN 49441)
Length of the power cable	1.8 m	2.15 m	1.8 m	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	1.8 m cable with power connector CEE 7/7	2 m	1.8 m cable with power connector CEE 7/7	1.8 m - cable with power connector IEC320 C14	1.8 m - cable with power connector IEC320 C14	1.8 m cable with power connector CEE 7/7	1.8 m - cable with power connector IEC320 C14	1.8 m	1.8 m cable with power connector CEE 7/7	1.8 m	1.8 m	1.8 m - cable with power connector CEE 7/7	2 m - cable with power connector IEC320 C14	2 m	2 m - cable with power connector IEC320 C14	2 m	2 m	...	...	3 m	
Nominal voltage of surge suppressor	...	...	...	...	...	...	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	...	...	250 V / 50 Hz	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	250 V / 50 Hz	250 V / 50 Hz	250 V / 50 Hz	
Automatic delayed fuse	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	10 A / 250 V	✓	...
Protection level of surge suppressor	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	≤ 1.3 kV (L/N)	≤ 1.3 kV (L/N)	≤ 1.3 kV (L/N)
Housing type	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U Rack 10"	1 U Rack 10"	1 U Rack 10"	1 U Rack 10"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"	1 U RACK 19"
Nominal stroke current	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	2 kA (L/N) - 8/20 µs	2 kA (L/N) - 8/20 µs	1 U RACK 19"
Leak current	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	≤ 0.5 mA	≤ 0.5 mA	...
Maximum stroke current	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	10 kA (L/N) - 8/20 µs 2 type	6.5 kA (L/N) - 8/20 µs	...
Response time	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	≤ 25 ns	≤ 25 ns	...
Switch	Yes (with built-in LED indicator)	two-way, with light indication	Yes (with built-in LED indicator)	two-way, with light indication	...	...	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	two-way, with light indication	...	...	...	Yes (with built-in LED indicator)	Yes (with built-in LED indicator and protected by a cover)	Yes (with built-in LED indicator and protected by a cover)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	Yes (with built-in LED indicator)	...	...	...	Yes (with built-in LED indicator)	...	two-way, with light indication	two-way, with light indication	...
Main features	• Overvoltage protection • LED indicators displaying the device's operating status	...	Overload protection	...	Circuit Breaker : 16 A, C type, 1P	Circuit Breaker, 16 A, C type, 2P	Overvoltage protection - Switch disconnect with fuse	• Overvoltage protection	• Signaling a lack of grounding • Overvoltage protection • AC input voltage presence indication	2 x USB socket : 5 V / 3 A	• Supply voltage measurement • Supply current measurement	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	• Current paths shutters • DC filter to eliminate interferences : ≤ 35 dB	...	...	...
Housing	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	RACK 19", 1U, Plastic - non-flammable	RACK 19", 1U, Plastic - non-flammable	...
Weight	0.75 kg	0.830 kg	0.8 kg	0.74 kg	0.83 kg	0.91 kg	0.76 kg	0.76 kg	0.78 kg	0.68 kg	0.78 kg	0.72 kg	0.78 kg	0.75 kg	0.75 kg	0.77 kg	0.74 kg	0.74 kg	0.72 kg	0.510 kg	0.52 kg	0.69 kg	0.830 kg	0.700 kg	0.35 kg	0.830 kg	0.93 kg	0.61 kg	0.85 kg		
Dimensions	482 x 45 x 54 mm	530 x 75 x 55 mm	484 x 45 x 56 mm	483 x 45 x 50 mm	483 x 44 x 84 mm	483 x 45 x 85 mm	483 x 45 x 54 mm	483 x 44 x 54 mm	483 x 45 x 54 mm	483 x 45 x 55 mm	483 x 45 x 54 mm	483 x 44 x 44 mm	483 x 44 x 54 mm	483 x 45 x 54 mm	481 x 45 x 45 mm	483 x 44 x 45 mm	483 x 45 x 44 mm	484 x 45 x 57 mm	480 x 45 x 51 mm	484 x 46 x 51 mm	257 x 45 x 45 mm	257 x 45 x 50 mm	482 x 46 x 44 mm	530 x 75 x 55 mm	482 x 46 x 44 mm	450 x 45 x 44 mm	450 x 45 x 44 mm	484 x 54 x 55 mm	445 x 54 x 55 mm	448 x 45 x 45 mm	
Length of the cable	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	2.9 m	2.9 m	...
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years