

	STABILIZER 48V/12V POE-802.3AF	STABILIZER 48V/12V POE-802.3AF/C	STABILIZER 48V/12V POE-802.3AT/24	ADAPTER TO POWER SUPPLY VIA TWISTED-PAIR CABLE INS-3AF-O-G UBIQUITI
				
	16.51 EUR 16.51 EUR	9.18 EUR 9.18 EUR	14.35 EUR 14.35 EUR	26.67 EUR 26.67 EUR
Standards	PoE (802.3af), PoE (802.3at)	PoE (802.3af), PoE (802.3at)	PoE (802.3af), PoE (802.3at)	...
Input socket	RJ-45 (T568B, T568A)	RJ-45	RJ-45	...
Number of inputs	1 x RJ-45 socket - PoE	1 x RJ-45 socket - PoE	1 x RJ-45 socket - PoE	1 pcs RJ-45 - 10/100/1000 Base-T
LED indicators	...	...	...	—
Protections	...	...	...	Overvoltage protection
Housing	...	...	...	Plastic
Number of outputs	1 x RJ-45 plug 1 x 2.1/5.5 mm plug on the cable	1 x RJ-45 plug 1 x 2.1/5.5 mm plug on the cable	1 x RJ-45 plug - on the cable 1 x 2.1/5.5 mm plug on the cable	...
Main features	...	...	...	Color : White
Input voltage	44 - 57 V PoE	44 - 57 V PoE	44 - 57 V PoE	48 V DC - PoE (802.3af)
Output voltage	12 V DC +/- 5%	12 V DC +/- 10%	12 V DC +/- 10%	24 V DC / 500 mA - Ubiquiti Passive PoE
Output current	max. 1A / 12V DC @ 48 V PoE max. 0,8A / 12V DC @ 57 V PoE	• 0.8A / 12V DC (continuous operation) • max. 1A / 12V DC (instantaneous operation)	• 1.6 A (continuous operation) • 2 A (instantaneous operation)	...
Operation temp. / Relative humidity	...	...	...	-30 ... 70 °C / 10 ... 90 %
Manufacturer / Brand	...	...	...	UBIQUITI
Supported data rates	• Ethernet - 10 Mbps Half Duplex • Fast Ethernet - 100 Mbps Full Duplex	• Ethernet - 10 Mbps Half Duplex • Fast Ethernet - 100 Mbps Full Duplex	• Ethernet - 10 Mbps Half Duplex • Fast Ethernet - 100 Mbps Full Duplex	...
Maximal transmission range	100 m (DATA)	100 m (DATA)	100 m (DATA)	...
LEDs application	...	Power supply PoE - Yellow	Power supply PoE - Yellow	...
Certificates	CE, FCC Class B	CE	CE	...
Weight	0.04 kg	0.05 kg	0.068 kg	0.09 kg
Dimensions	78 x 20 x 20 mm	82 x 29 x 24 mm	94 x 35 x 27 mm	160 x 30 x 30 mm
Guarantee	2 years	2 years	2 years	2 years