

																																						
	12.08 EUR 12.08 EUR	6.31 EUR 6.31 EUR	4.21 EUR 4.21 EUR	0.18 EUR 0.18 EUR	0.20 EUR 0.20 EUR	0.25 EUR 0.25 EUR	0.37 EUR 0.37 EUR	0.29 EUR 0.29 EUR	0.69 EUR 0.69 EUR	0.47 EUR 0.47 EUR	0.98 EUR 0.98 EUR	2.10 EUR 2.10 EUR	2.52 EUR 2.52 EUR	19.77 EUR 19.77 EUR	14.30 EUR 14.30 EUR	5.91 EUR 5.91 EUR	3.37 EUR 3.37 EUR	0.55 EUR 0.55 EUR	0.51 EUR 0.51 EUR	0.81 EUR 0.81 EUR	1.58 EUR 1.58 EUR	2.82 EUR 2.82 EUR	3.87 EUR 3.87 EUR	1.39 EUR 1.39 EUR	2.05 EUR 2.05 EUR	2.67 EUR 2.67 EUR	0.12 EUR 0.12 EUR	0.16 EUR 0.16 EUR	0.20 EUR 0.20 EUR	0.31 EUR 0.31 EUR	0.46 EUR 0.46 EUR	0.17 EUR 0.17 EUR	0.19 EUR 0.19 EUR	0.29 EUR 0.29 EUR	0.24 EUR 0.24 EUR			
Hole diameter	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
Mast diameter	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
In section	...	...	...	...	...	...	200 m . Price for 1m when buying a whole roll	200 m . Price for 1m when buying a whole roll	200 m . Price for 1m when buying a whole roll	200 m . Price for 1m when buying a whole roll	100 m . Price for 1m when buying a whole roll	max. Ø 40 mm	max. Ø 55 mm	...	...	...	...	...	...	...	max. Ø 38 mm	max. Ø 45 mm	...	...	...	...	...	...	...	...	...	...	...	...	...	...		
Mounting holes	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
External diameter	...	...	...	...	...	...	Ø 3 mm	Ø 3 mm	Ø 4 mm	Ø 4 mm	Ø 5 mm	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
In the kit	...	...	...	...	...	...	...	...	...	...	...	...	...	• Anchors - 6 pcs • Guy wires mount - 9 pcs	• Anchors - 3 pcs • Guy wires mount - 6 pcs	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...		
Inner diameter	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	
Tensile strength	...	...	...	...	...	...	480 kg	Ø 2.1 mm 270 kg	...	830 kg	630 kg	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Main features	• Mast diameter max. Ø 50 mm • Allows to mount the lightning conductor to the mast, mounting element - Clamp • The whole galvanized	• Mast diameter max. Ø 50 mm • Allows to mount the lightning conductor to the mast, mounting element - Clamp • The whole galvanized	• Mast diameter max. Ø 50 mm • Allows to mount the lightning conductor to the mast, mounting element - Clamp, U-Bolt • The whole galvanized	Corrosion resistance	Corrosion resistance	Corrosion resistance	...	...	...	...	The whole galvanized	The whole galvanized	...	The product has a threaded hole	• Allows to mount three guy-wires to the mast • Mast diameter Ø 30 ... 50 mm • Whole element is hot-dip galvanized • Screw diameter Ø 8 mm	• Allows to mount three guy-wires to the mast • Mast diameter Ø 30 ... 50 mm • The whole galvanized	...	• U-shaped metal bar diameter 5 mm • Work load 100 kg • Corrosion resistance	• U-shaped metal bar diameter 6 mm • Work load 150 kg • Corrosion resistance	• U-shaped metal bar diameter 8 mm • Work load 350 kg • Corrosion resistance	...	...	• Screw diameter 10 mm • Work load 220 kg • Corrosion resistance	• Screw diameter 5 mm • Work load 50 kg • Corrosion resistance	• Screw diameter 6 mm • Work load 70 kg • Corrosion resistance	• Screw diameter 8 mm • Work load 140 kg • Corrosion resistance	Corrosion resistance	Corrosion resistance	Corrosion resistance	Corrosion resistance	Corrosion resistance	...	...	...	...	...	...	
Material	Metal	Metal	Metal	Metal	Metal	Metal	Steel	Steel + PVC	Steel	Steel + PVC	Steel + PVC	Metal	Metal	Steel galvanized	Steel galvanized	Swedish steel	Metal	Metal	Metal	Metal	PET	PET	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	PET	PET	PET	PET	PET	PET	
Application	Mast	Mast	Mast	Steel lines Ø 3 mm	Steel lines Ø 4 mm	Steel lines Ø 5 mm	...	...	...	...	...	...	...	To the mast : MT-10A/CT	To the mast : MT-6.5A/CT	Mast	Mast	Steel lines	Steel lines	Steel lines	...	...	Steel lines	Steel lines	Steel lines	Steel lines	Steel lines	Steel lines	Steel lines	Steel lines	Steel lines	Steel lines	Steel lines	Steel lines	Steel lines	Steel lines	Steel lines	
Weight	0.24 kg	0.39 kg	0.38 kg	0.005 kg	0.004 kg	0.009 kg	...	...	...	...	...	...	...	0.65 kg	1.1 kg	...	...	0.015 kg	0.015 kg	...	0.03 kg	0.230 kg	0.05 kg	0.05 kg	0.05 kg	0.05 kg	0.05 kg	0.015 kg	0.015 kg	0.023 kg	0.006 kg	0.007 kg	0.006 kg	0.01 kg	...			
Dimensions	180 x 40 x 25 mm	175 x 60 x 30 mm	160 x 90 x 30 mm	29 x 20 x 7 mm	31 x 23 x 7 mm	41 x 27 x 9 mm	...	...	...	...	...	...	...	• Ø 70 x 405 mm - Ground Anchor • 400 x 50 mm - Anchors	Ø 70 x 405 mm	...	...	30 x 30 x 10 mm	40 x 40 x 12 mm	49 x 44 x 16 mm	40 x 40 x 32 mm	55 x 55 x 45 mm	220 x 35 x 14 mm	140 x 20 x 7 mm	140 x 20 x 7 mm	170 x 21 x 12 mm	20 x 20 x 12 mm	25 x 25 x 15 mm	27 x 30 x 15 mm	40 x 15 x 10 mm	40 x 20 x 10 mm	Ø 35 x 20 mm	Ø 40 x 20 mm	Ø 40 x 20 mm	Ø 49 x 26 mm	...		
Manufacturer / Brand	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	DELTA	
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	3 years	3 years	3 years	3 years	2 years	3 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	