

	ALARM KIT ATLO-AZ-WG13A-TUYA	ALARM KIT WAS-90H1 EL HOME	OPENING DETECTOR WITH AUDIO SIGNAL MA-95A3	AUTONOMOUS, WIRELESS PIR DETECTOR WITH ALARM FUNCTION OR-AB-MH-3005 ORNO	PIR DETECTOR WITH AUDIO SIGNAL OR-MA-701	PIR DETECTOR WITH AUDIO SIGNAL ATLO-AH-SL523 ATLO	PIR DETECTOR WITH AUDIO SIGNAL OR-MA-705	PIR DETECTOR WITH AUDIO SIGNAL OR-MA-711 ORNO
								
	42.23 EUR 42.23 EUR	48.45 EUR 48.45 EUR	4.24 EUR 4.24 EUR	78.09 EUR 78.09 EUR	14.87 EUR 14.87 EUR	19.08 EUR 19.08 EUR	27.68 EUR 27.68 EUR	20.14 EUR 20.14 EUR
Support	...	...	...	Wireless devices of the OR-AB-MH-3005 series	...	alarm control panel ATLO-AZ-WG13A-TUYA	...	...
Aspect ratios	2.4 " TFT LCD	...	...	...	...	...	...	...
Autonomous operation	...	...	...	...	...	✓	...	...
Range	...	...	...	...	4 ... 5 m	...	7 m (detector)	6 m (detector)
Detection angle	...	...	...	...	...	...	...	110 °
Number of supported wireless devices	max. 30 pcs	max. 16 pcs	...	...	...	max. 20 pcs	...	...
Number of supported remote control keyfobs	max. 8 pcs, In the kit : 2 pcs	...	...	...	...	max. 5 pcs	...	...
Frequency bandwidth of the system	...	...	...	...	...	433 MHz	...	...
The RFID cards/keyfobs support	Unique EM 125kHz	...	...	...	...	...	...	...
Enclosure included	...	✓	...	...	...	...	...	...
Number of supported wireless sirens	1 pcs	...	...	...	...	...	...	...
PIR detectors included	1 pcs, Wireless	2 pcs, Wireless	...	...	...	...	...	...
Operating range in open area	...	max. 50 m	...	...	...	...	...	...
Magnetic contact included	1 pcs, Wireless	1 pcs, Wireless	...	...	...	...	...	...
Keyboard included	✓	✓	...	...	...	...	...	...
Expander included	...	...	...	...	...	...	...	...
Wireless	433 MHz	433.93 MHz	...	...	...	...	...	...
Zones	99 (wireless zones)	...	...	...	...	...	...	...
Timers	✓	...	...	...	...	...	...	...
Users + admins	6	...	...	...	...	...	...	...
Default administrator password	6666	...	...	...	...	...	...	...
Default user password	1234	...	...	...	...	...	...	...
Built-in modules	GSM, WiFi	...	...	...	...	...	...	...
Access from PC	...	...	...	...	...	...	...	...
Mobile phones support	Access by a cloud (P2P) • The Tuya Smart free application on Android • The Tuya Smart free application on iOS Remote control of the control panel via SMS, Tuya Smart application	• Android: Free application eWeLink . • iOS (iPhone): Free application eWeLink	...	...	...	...	...	...
Maximal current consumption	...	...	...	...	...	150 mA	...	...
Compliance with standards	...	...	...	ETSI EN 300 220-2, ETSI EN 301 489-1, ETSI EN 301 489-3, EN60950-1, EN 62311, EN 62479	...	...	...	...
Permissible relative humidity	...	...	...	...	...	40 % ... 80 (non-condensing)	...	...
Supported languages	Chinese, English, German, Russian, Spanish, Polish, Italian, French, Portuguese, Greek, Romanian	...	...	...	...	...	...	...
Power supply	• 5 V DC / 2 A (power adapter included) • Built-in battery that maintains the control panel operation during a power failure : 3.7 V / 1000 mAh	• 5 V micro USB connector • 5 V DC / 2 A (power adapter included)	...	...	...	• built-in battery - 3.7 V 1000 mAh, • micro USB - 5 V / 1 A DC • Solar Panel - 5 V	...	...
Detection	Opening the door or window	Opening the door or window	Opening the door or window	...	...	...	...	...
Application	...	Indoor	...	...	Indoor	...	Internal	Internal
Sensor type	...	Passive Infra Red (PIR)	...	...	Passive Infra Red (PIR)	...	Passive Infra Red (PIR)	Passive Infra Red (PIR)
Alarm inputs	...	...	...	...	...	...	...	...
Recommended installation height	...	2.0 ... 2.4 m	...	...	...	...	...	...
Detection range / Detection angle	...	12 m / 110 °	...	...	...	...	...	...
Sensitivity adjustment	...	...	...	...	...	...	...	...
Pet immunity	...	< 20 kg	...	...	...	...	...	...
Digital temperature compensation	...	...	...	...	...	...	...	...
Alarm signaling	Signal to control panel	Signal to the eWeLink mobile application - via RB-80H1 Signal to the eWeLink mobile application - via RB-80H1	• Alarm siren max. 105 dB, • Beep signal - Entry signaling device	...	selectable by switch : • Gong • Alarm siren ~ 85 dB/m	...	Gong, Volume selectable by switch, Wireless	Alarm siren ≥ 100 dB / 30 m
Housing	Plastic	Plastic Plastic Plastic	...	...	...	...	...	...
"Index of Protection"	...	IP20 IP20 IP20	IP20	...	...	...	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Current consumption	...	≤ 15 mA (Standby mode) ≤ 40 mA (operation) ≤ 5 µA (Standby mode) ≤ 15 mA (operation) ≤ 9 µA (Standby mode) ≤ 10 mA (operation)	...	...	...	...	...	...
Operation temp	-10 °C ... 55 °C	0 °C ... 40 °C 0 °C ... 40 °C 0 °C ... 40 °C	10 °C ... 40 °C	-10 °C ... 40 °C	0 °C ... 40 °C	-20 °C ... 55 °C	0 °C ... 40 °C	...
Battery power supply	2 x 1.5V, type AAA/LR03 battery (included)	...	Battery 3 x 1.5 V LR44 included	• detector : 3 x 1.5V, type AAA/LR03 battery (not included) • Remote control : 1 x CR2032 3V (included)	• 6 V DC / 300 mA (power adapter not included) • 4 x battery LR6 (AA) (not included)	...	• Signaling device 3 x battery LR14 / Power adapter 6 V DC (not included) • Wireless detector 3 x battery 1.5 V AAA (not included)	• PIR detector with audio signal : 3 x battery LR6 (AA) • Remote control : 1 x Lithium battery 3 V CR2032 included
Frequency range	433 MHz 433 MHz	433.93 MHz 433.93 MHz	...	868.1 MHz	...	...	...	...
Radio communication range (at open area)	max. 30 m	max. 50 m max. 50 m	...	~ 80 m	...	≥ 100 m (in open area)	...	...
Detection angle / Detection range	120 ° / 12 m (max)	...	...	140 ° / 10 m	...	...	...	...
Main features	Code 1527 data encryption	LED indicator	Turning by switch	• The detector can operate as a simple, wireless alarm control panel • Built-in GSM communication module with the option of sending voice messages or SMS to max. 3 phone numbers • Built-in alarm siren - 130 dB • Learning system - automatic configuration of the additional devices	...	...	Wireless max. 120 m (open area)	• Remote control - 1 pcs (included), Radio communication range (at open area) : 30 m • Environmental immunity • Low battery level alarm • Support for up to 4 keyfobs : 433.92 MHz
Frequency band	433 MHz	...	...	...	...	...	...	...
Main features	• Bidirectional communication, • SMS notification about alarm and power failure, • LED indication, • LCD display, • Built-in alarm siren - 100 dB, • Alarm mute function • LED indication • One-touch action buttons : arm, disarm, arming only perimeter protection zones, SOS	• Built-in module to support wireless devices operating in the 433 MHz frequency band, • Built-in Wi-Fi module 2.4 GHz IEEE 802.11 b/g/n, • Phone notification - Signal to the eWeLink mobile application, • Configuration is done using the mobile application • LED indication	...	...	...	• Optical - sound signaling • Built-in PIR detector • Code 1527 data encryption • Remote update of software • Low battery level alarm • Pairing indicator • Tamper detection - removing from mounting surface • Light and durable construction (polycarbonate) • "Index of Protection" : IP65	...	...
Battery	1 x CR2032 3V (included) 1 x CR2025 (included)	1 x A23 12 V (not included) 2 x LR3 (AAA) 1.5 V (not included)	...	...	...	...	...	...
Connector	Jack 3.5 mm	...	...	...	...	...	...	...
Sound pressure level	120 dB	...	...	...	...	110 dB	...	...
Color	Black White	Black White White	...	...	...	White	...	...
Weight	0.2 kg • 0.02 kg - Transmitter • 0.01 kg - Magnet 0.06 kg 0.02 kg 0.06 kg	0.04 kg • 0.020 kg - Transmitter • 0.007 kg - Magnet 0.062 kg	0.042 kg	0.1 kg	0.13 kg	0.268 kg	• 0.085 kg - Motion detector • 0.13 kg - Signaling device	• 0.09 kg - PIR detector with audio signal • 0.02 kg - Remote control
Dimensions	185 x 125 x 14 mm • 60 x 23 x 13 mm - Transmitter • 40 x 13 x 10 mm - Magnet 105 x 40 x 27 mm 58 x 32 x 11 mm 63.5 x 54 x 47.5 mm	62 x 62 x 20 mm • 70 x 31 x 19 mm - Transmitter • 42 x 14 x 16 mm - Magnet 105 x 58 x 43 mm	• Transmitter : 32 x 65 x 24 mm • magnet : 10 x 53 x 15 mm	113 x 70 x 38 mm	72 x 82 x 122 mm	165 x 124 x 64 mm	• 70 x 106 x 48 mm - Motion detector • 94 x 130 x 43 mm - Signaling device	• 56 x 132 x 70 mm - PIR detector with audio signal • 33 x 65 x 8 mm - Remote control
Manufacturer / Brand	ATLO	EL HOME	EURA	ORNO	ORNO	ATLO	ORNO	ORNO
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00