

	AUTONOMOUS CABINET LOCK ATLO-ML-EM219	PROXIMITY READER WITH MEMORY ATLO-RM-822	PROXIMITY READER WITH MEMORY ZS46 VIDOS
			
	19.76 EUR 19.76 EUR	45.80 EUR 45.80 EUR	20.37 EUR 20.37 EUR
Cards support	Unique EM 125kHz	Unique EM 125kHz	Unique EM 125kHz
Reading distance of prox-keys	max. 5 cm	3 ... 6 cm	~ 5 cm
Autonomous operation	✓	✓	✓
Keyboard built-in	—	—	—
Doorbell button	—	—	—
Tamper output	—	—	—
Power supply	4 x 1.5V, type AA/LR6/FR6 battery	12 ... 24 V DC	12 ... 24 V DC
Relay contacts load	—	...	...
Maximal current consumption	...	• 35 mA (Standby mode) • 100 mA (operation)	• 35 mA (Standby mode) • 100 mA (operation)
Main features	• Four types of users: administrator, user, service, guest • The device is independent and its programming is done using the administrator card • The lock clamp has been equipped with a spring bumper that facilitates opening the cabinet door after unlocking it • The set includes an emergency power supply module that allows you to open the lock in the event of a low battery	• 10 000 indexed users • Cooperation with the exit button • NO/NC output • Wiegand 26-bit standard • Adjusting the opening time : 0 ... 99 s	• 10 000 indexed users • Cooperation with the exit button • NO/NC output • The user is equipped with the Wiegand 26/34 interface allowing cooperation with an external access controller • Adjusting the opening time : 0 ... 99 s
Operation temp	...	-20 °C ... 60 °C	-20 °C ... 60 °C
Permissible relative humidity	...	0 ... 95 % (non-condensing)	0 ... 95 % (non-condensing)
"Index of Protection"	—	IP68	IP65
Housing	Metal + Plastic	Metal	Plastic
Color	...	Silver + Black	Black
Weight	0.21 kg	0.35 kg	0.094 kg
Dimensions	130 x 63 x 25 mm - Door lock (strike) 115 x 55 x 17 - RFID reader	120 x 58 x 22 mm	107 x 47 x 20 mm
Manufacturer / Brand	ATLO	ATLO	VIDOS
Guarantee	3 years	2 years	3 years