	BATTERY 6V/1.3AH-MW	BATTERY 6V/1.3AH-UL ULTRACELL	BATTERY 6V/12AH-UL ULTRACELL	BATTERY 6V/4.5AH-UL ULTRACELL	BATTERY 6V/7.2AH-MWS MW Power	BATTERY AKU AA-2000/GCPP1.2 V Ni-MH HR6, AA Green Cell	BATTERY AKU AA-2600/GCPP4 1.2 V Ni-MH HR6, AA Green Cell	BATTERY AKU AA-2600GCPP4 1.2 V Ni-MH HR6, AA Green Cell	BATTERY AKU AAA-800/GCPP4 1.2 V Ni-MH HR03, AAA Green Cell	BATTERY AKU AAA-950/GCPP4 1.2 V Ni-MH HR03, AAA Green Cell	BATTERY BAT AA/AKU-1300PP4 1.2 V HR6 AA ENERGIZER	BATTERY BAT AA/AKU-2000PP4 1.2 V Ni-MH HR6 / AA ENERGIZER	BATTERY BAT AA/AKU-2300PP4 1.2 V Ni-MH HR6 AA ENERGIZER	BATTERY BAT AAA/AKU-500PP4 1.2 V Ni-MH AAA ENERGIZER	BATTERY BAT AAA/AKU-700PP4 1.2 V Ni-MH AAA ENERGIZER	BATTERY BAT AAA/AKU-800PP4 1.2 V Ni-MH AAA ENERGIZER	BATTERY BAT HR14/AKU-2500PP2 1.2 V Ni-MH HR14 / C ENERGIZER	BATTERY BAT HR20/AKU-2500PP2 1.2 V Ni-MH HR20 / D ENERGIZER	BATTERY BAT HR22/AKU-175 8.4 V Ni-MH 6HR61 ENERGIZER	LI-ION BATTERY BAT ICR18650-26HA/KU 3.7 V SAMSUNG	LI-ION BATTERY BAT ICR18650EP 3.7 V EUROPOWER	LI-ION BATTERY BAT ICR18650GCEP 3.6 V EUROPOWER	LI-ION BATTERY BAT ICR18650CILEP 3.6 V EUROPOWER	LI-ION BATTERY BAT INR18650-25R/KU 3.6 V SAMSUNG	LI-ION BATTERY BAT INR18650-30Q/KU 3.6 V SAMSUNG	LI-ION BATTERY BAT INR18650/26EGC 3.6 V Green Cell	LI-ION BATTERY BAT INR18650/30EGC 3.6 V Green Cell	LI-ION BATTERY BAT US18650VTC5/KU 3.6 V SONY / MURATA	BATTERY DS-2FSCH50 FOR THE DS-2XS6A87G1-LC/2S8B CAMERA 10.8 V Hikvision
	5.32 EUR 5.32 EUR	5.21 EUR 5.21 EUR	13.86 EUR 13.86 EUR	12.08 EUR 12.08 EUR	6.61 EUR 6.61 EUR	3.86 EUR 3.86 EUR	6.90 EUR 6.90 EUR	9.79 EUR 9.79 EUR	4.13 EUR 4.13 EUR	5.42 EUR 5.42 EUR	7.26 EUR 7.26 EUR	8.84 EUR 8.84 EUR	11.67 EUR 11.67 EUR	7.26 EUR 7.26 EUR	7.46 EUR 7.46 EUR	11.71 EUR 11.71 EUR	10.94 EUR 10.94 EUR	11.35 EUR 11.35 EUR	7.54 EUR 7.54 EUR	6.04 EUR 6.04 EUR	2.84 EUR 2.84 EUR	3.57 EUR 3.57 EUR	3.98 EUR 3.98 EUR	7.66 EUR 7.66 EUR	10.22 EUR 10.22 EUR	2.35 EUR 2.35 EUR	2.93 EUR 2.93 EUR	9.53 EUR 9.53 EUR	1036.79 EUR 1036.79 EUR
In package						**2 pcs The price for package**	**4 pcs The price for package**	**4 pcs The price for package**	**4 pcs The price for package**	**4 pcs The price for package**	**4 pcs The price for package**	**4 pcs The price for package**	**4 pcs The price for package**	**4 pcs The price for package**	**4 pcs The price for package**	**4 pcs The price for package**	**2 pcs The price for package**	**2 pcs The price for package**											
Application																														DS-2XS6A87G1-LC/2S8D
Rated voltage	6 V	6 V	6 V	6 V	6 V	1.2 V	1.2 V	1.2 V	1.2 V	1.2 V	1.2 V	1.2 V	1.2 V	1.2 V	1.2 V	1.2 V	1.2 V	1.2 V	8.4 V	3.7 V	3.7 V	3.6 V	3.6 V	3.6 V	3.6 V	3.6 V	3.6 V	3.6 V	3.6 V	10.8 V
Battery lifetime	≤ 5 years	≤ 5 years	≤ 5 years	≤ 5 years	≤ 5 years																									
Battery charging voltage																				max. 4.2 V	max. 4.2 V	max. 4.2 V	max. 4.2 V	max. 4.2 V	max. 4.2 V	max. 4.2 V	max. 4.2 V	max. 4.2 V	max. 4.25 V	max. 12.6 V
Battery capacity	1.3 Ah	1.3 Ah	12 Ah	4.5 Ah	7.2 Ah	2000 mAh	2600 mAh	2600 mAh	800 mAh	950 mAh	1300 mAh	2000 mAh	2300 mAh	500 mAh	700 mAh	800 mAh	2500 mAh	2500 mAh	175 mAh	2.6 Ah	2.5 Ah	2.15 Ah	2.4 Ah	2.5 Ah	3.0 Ah	2.6 Ah	2.9 Ah	2.6 Ah	30 Ah
Connector	T1 type	T1 type	T1 type	T1 type	T1 type																									
Battery charging current		< 0.39 A	< 3.6 A	< 1.35 A	< 2 A															1.3 A - standard charging 2.6 A - fast charging	1.25 A - standard charging 2.5 A - fast charging	1.075 A - standard charging 2.15 A - fast charging	1.2 A - standard charging 2.4 A - fast charging	1.25 A - standard charging 4.0 A - fast charging	1.5 A - standard charging 4.0 A - fast charging	1.3 A	1.45 A	max. 4.0 A	
Main features																														• Built-in MPPT batteries solar charge controller • RS-485 control
Housing																														Aluminum
"Index of Protection"																														IP68
Dimensions	97 x 54 x 21 mm	97 x 24 x 57 mm	151 x 51 x 97 mm	70 x 47 x 106 mm	151 x 35 x 100 mm																								
Maximal output current																				5.2 A	5 A	10 A	7.2 A	20.0 A - continuous	15.0 A - continuous	7.8 A - continuous	8.4 A - continuous	30.0 A - continuous, requires external temperature protection : 80 °C 20.0 A - continuous, without thermal protection.	8 A
Color																														White
Minimum allowable battery voltage (End voltage / Cut off)																				2.75 V	3 V	2.75 V	2.75 V	2.5 V	2.5 V	2.75 V	2.75 V	2.0 V	
Battery type	Maintenance free, sealed lead-acid battery AGM	Maintenance-free AGM (Absorbent Glass Mat) battery	Maintenance-free AGM (Absorbent Glass Mat) battery	Maintenance-free AGM (Absorbent Glass Mat) battery	Maintenance-free AGM (Absorbent Glass Mat) battery	Ni-MH	Ni-MH	Ni-MH	Ni-MH	Ni-MH		Ni-MH	Ni-MH	Ni-MH	Ni-MH	Ni-MH	Ni-MH	Ni-MH		Li-Ion	Li-Ion	Li-Ion	Li-Ion	Li-Ion	Li-Ion	Li-Ion	Li-Ion	Li-Ion	
Size						HR6, AA	HR6, AA	HR6, AA	HR03, AAA	HR03, AAA		HR6 / AA	HR6 AA	AAA	AAA	AAA	HR14 / C	HR20 / D	6HR61 / HR22	18650	18650	18650	18650	18650	18650	18650	18650	18650	
Type (size)											HR6 AA																		255 x 172 x 80 mm
Protection																				—	—	—	—	—	—	—	—	—	
Weight	0.3 kg	0.28 kg	1.78 kg	0.76 kg	1.03 kg	0.03 kg	0.03 kg	0.128 kg	0.01 kg	0.012 kg	0.021 kg	0.026 kg	0.028 kg	0.008 kg	0.011 kg	0.012 kg	0.057 kg	0.065 kg	0.034 kg	0.046 kg	0.046 kg	0.044 kg	0.044 kg	0.046 kg	0.046 kg	0.04 kg	0.04 kg	0.045 kg	3.4 kg
Manufacturer / Brand		ULTRACELL	ULTRACELL	ULTRACELL	MW Power	Green Cell	Green Cell	Green Cell	Green Cell	Green Cell	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	ENERGIZER	SAMSUNG	EUROPOWER	EUROPOWER	EUROPOWER	SAMSUNG	SAMSUNG	Green Cell	Green Cell	SONY / MURATA	Hikvision
Guarantee	12 months	12 months	12 months	12 months	12 months	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00