# INDUSTRIAL SWITCH **S5500-48GT4XF** 48-PORT SFP DAHUA

Net: 2 680.88 EUR Gross: 2 680.88 EUR



The S5500-48GT4XF switch is designed for large streams of video data in the CCTV IP surveillance networks. Designed to continuous operation 24/7.

### **SPECIFICATION**

LAN ports:	48 x RJ45 - 10/100/1000 Base-T
Transmission speed:	• 10 / 100 / 1000 Mbps - 48 LAN ports, • 1000 Mbps - 4 SFP ports
Management:	✓
MAC addresses table:	16k
Main features:	Switch is managed via a web browser, command line interface and SNMP, RMON protocols  OoS/DSCP priority based on IEEE 802.1p standard  Queue scheduling: SP, WRR, SP+WRR  Port/flow-based rate limiting  IEEE 802.1Q VLAN, Port Based VLAN, MAC Based VLAN, Private VLAN support  IEEE 802.1Q standard support, up to 512 VLAN groups and 4K VIDs  IGMP Snooping V1/V2/V3  IRF2 - technology allowing virtual connection of several physical devices into one logical device and managing it as a single device; The system based on the IRF technology also allows to build a system of many parallel connected devices, which translates into increased system performance, greater resistance to failures, the ability to connect redundant devices in the 1:N system with the possibility of replacing any device at any time without affecting the operation of the entire system (Hot Swap),  Support ARP Spoofing defence  BPDU Filtering/Guard  Data Flow Control (802.3x)  protection against lightning discharges and voltage differences and strokes between devices
Certificates:	CE, RoHS
Power supply:	230 V AC
Power consumption:	≤ 45 W
Operation temp:	0 °C 45 °C
Weight:	3.69 kg
Dimensions:	440 x 260 x 44 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

### PRESENTATION



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

2024-05-10 1/2

### Front panel:



## Mounting side view:



### In the kit:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm

Gross Weight: 0 kg