Code: PH-10-KIT

NETWORK ADAPTER **PH-10-KIT** Tenda

Net: 105.94 EUR Gross: 105.94 EUR

The PH-10-KIT network transmitters kit is designed for Ethernet signal transmission through power line. Devices are an ideal solution when it is impossible to install UTP cables or the environment does not allow to use wireless connectivity.

Devices must be plugged into the outlets using the same branch (phase).



SPECIFICATION

LAN ports:	1 pcs - LAN + Wi-Fi module 1 pcs - LAN module
Standards:	HomePlug AV2, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.11 b/g/n
Modulation:	OFDM, CSMA/CA
Protections:	128-bit AES encryption, WPA-PSK/WPA2-PSK
LED diodes:	Power supply, Link/Act, Power network, WiFi / WiFi CLONE
Transmission speed:	433 Mbps @ 5 GHz WiFi 200 Mbps @ 2.4 GHz WiFi 1000 Mbps @ Ethernet
Transmission range via electrical installation:	300 m - Within a building
Power supply:	230 V AC
Power consumption:	≤ 8.9 W - LAN + Wi-Fi module ≤ 3.2 W - LAN module
Main features:	• Plug & Play • HomePlug AV 2 compliance • Pair button - Encryption activation • WiFi CLONE
Certificates:	CE, FCC, RoHS
Operation temp:	0 °C ... 40
Weight:	0.27 kg - LAN + Wi-Fi module 0.1 kg - LAN module
Dimensions:	110 x 77 x 85 mm - LAN + Wi-Fi module 82 x 60 x 70 mm - LAN module
Manufacturer / Brand:	Tenda
Guarantee:	2 years

PRESENTATION

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Front view:



Rear view:



Side view:



Bottom view:


DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



ON-OFF switch:



Typical operation diagram:



1. Electrical installation of the building
2. Ethernet

In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60