

Code: RG-NBS5100-24GT4SFP

Switch **RG-NBS5100-24GT4SFP** 24-PORT REYEE

Net: **398.94 EUR** Gross: **398.94 EUR**

The RG-NBS5100-24GT4SFP switch is designed for large streams of video data in the CCTV IP surveillance networks.



SPECIFICATION

LAN ports:	• 24 x (RJ45) 10/100/1000 Mbps • 4 x SFP ports
Management:	✓
Transmission speed:	10/100/1000 Mbps - 24 x Gigabit Ethernet 1000 Mbps - 4 x port SFP
Switching performance:	56 Gb/s
Packet redirection speed:	42 Mpps
MAC addresses table:	16k
Certificates:	CE, RoHS
Number of fan coolers:	1
Mobile phones support:	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Jumbo Frame:	9 kB
Default IP address:	10.44.77.200
Main features:	• Can be mounted in a Rack cabinet • Switch is managed through the web and the cloud (Ruijie Reyee application) • IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs • DHCP client • BPDU Filtering/Guard • Loop back detection • Spanning Tree STP/RSTP • Errdisable Recovery • Up to 16 aggregation groups and up to 8 ports per group • IGMP Snooping V1/V2/V3 • DHCP snooping support • Port mirroring function • Loop Protection • IEEE802.3x Flow Control • MTBF (Mean Time Between Faults) > 200.000 h
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	10 % ... 90 % (non-condensing)
Protections:	Protection against lightning discharges : 6 kV
Power supply:	100 V ... 240 AC
Power consumption:	≤ 28 W

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Weight:	2.84 kg
Dimensions:	440 x 207 x 44 mm
Manufacturer / Brand:	RUIJIE / REYEE
Guarantee:	5 years

PRESENTATION

Front panel:



Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------