

Code: RG-S2915-24GT4MS-L

Switch **RG-S2915-24GT4MS-L** 24-PORT RUIJIE

Net: **467.08 EUR** Gross: **467.08 EUR**

The RG-S2915-24GT4MS-L switch is designed for large streams of video data in the CCTV IP surveillance networks.



SPECIFICATION

LAN ports:	• 24 x (RJ45) 10/100/1000 Mbps, • 4 x SFP ports - Uplink • 1 x RJ45 - Configuration possibility from PC, • 1 x USB - Configuration possibility from PC
Management:	✓
Transmission speed:	• 10/100/1000 Mbps - 24 x Gigabit Ethernet • 100/1000/2500 Mbps - 4 x port SFP
Switching performance:	68 Gb/s
Packet redirection speed:	51 Mpps
MAC addresses table:	16k
Certificates:	CE, RoHS
Number of fan coolers:	—
Mobile phones support:	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Jumbo Frame:	9 kB
Main features:	• Can be mounted in a Rack cabinet • Switch is managed through the web and the cloud (Ruijie Reyee application) • IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs • DHCP client • BPDU Filtering/Guard • Loop back detection • Spanning Tree STP/RSTP • Errdisable Recovery • IGMP Snooping V1/V2/V3 • DHCP snooping support • Port mirroring function • Loop Protection • IEEE802.3x Flow Control • MTBF (Mean Time Between Faults) > 200.000 h
Operation temp:	0 °C ... 45 °C
Permissible relative humidity:	10 % ... 90 % (non-condensing)
Protections:	Protection against lightning discharges : 10 kV
Power supply:	100 V ... 240 AC
Power consumption:	≤ 15.6 W

Weight:	2.53 kg
Dimensions:	442 x 222 x 44 mm
Manufacturer / Brand:	RUIJIE
Guarantee:	3 years

PRESENTATION


Front panel:



Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------