

Code: SG-64H

SWITCH POE **SG-64H** 4-PORT PULSAR

Net: **131.47 EUR** Gross: **161.71 EUR**



The SG-64H switch is designed to supply IP cameras operating in the IEEE 802.3af/at standard. The device with the power supply adapter is enclosed in a housing with IP56 protection class. Four ports support Power over Ethernet (PoE) function.

SPECIFICATION

LAN ports:	<ul style="list-style-type: none">• 4 x RJ45 10/100/1000 Base-TX - PoE (802.3af/at),• 2 x RJ45 10/100/1000 Base-TX - Uplink ports
Management via WWW / console:	—
Transmission speed:	<ul style="list-style-type: none">• 10 / 100 / 1000 Mbps - 4 LAN & PoE ports,• 10 / 100 / 1000 Mbps - 2 Uplink ports
Maximal output power:	30 W / port PoE
Maximal total power:	30 W
MAC addresses table:	1k
Main features:	There are cable glands in the housing : <ul style="list-style-type: none">• 6 pcs Ø 4 ... 8 mm• 1 pcs Ø 10 ... 14 mm
Certificates:	CE
Power supply:	230 V AC
Housing:	Plastic, IP56
Weight:	1.33 kg
Dimensions:	146 x 196 x 78 mm
Manufacturer / Brand:	PULSAR
Guarantee:	2 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Bottom view:



Internal view:





- 1 - LAN + PoE
- 2 - LAN + PoE
- 3 - LAN + PoE
- 4 - LAN + PoE
- 5 - Port Uplink
- 6 - Port Uplink

Top view:



Examples of connection diagrams:

