

Code: NSW2020-10T-POE-IN

SWITCH POE **NSW2020-10T-POE-IN** 8-PORT UNIVIEW

Net: **98.13 EUR** Gross: **120.70 EUR**

Due to the reliability and ensuring high quality of transmission, the NSW2020-10T-POE-IN 8-port PoE switch is an ideal solution for applications in CCTV IP installations. 8 ports support Power over Ethernet (PoE) function.



SPECIFICATION

| | |
|-------------------------------|---|
| LAN ports: | <ul style="list-style-type: none">• 8 x RJ45 10/100 Base-T (8 x PoE (802.3af/at)),• 2 x RJ45 100 Base-T - Uplink |
| Management via WWW / console: | — |
| LED diodes: | Link/Act, Power, PoE Max |
| Transmission speed: | <ul style="list-style-type: none">• 100 Mbps : 2 LAN ports - Uplink,• 10 / 100 Mbps : 8 LAN & PoE ports |
| Maximal output power: | 30 W / port PoE 802.3af/at |
| Maximal total power: | 88 W |
| MAC addresses table: | 1k |
| Operation modes: | <ul style="list-style-type: none">• Extend : 250 m, 10 Mbps• Default : 100 m, 100 Mbps |
| Main features: | <ul style="list-style-type: none">• EXTEND mode - ports 1, 2, 3, 4, 5, 6, 7, 8 support transmission up to 250 m• High priority ports : 1, 2• Data Flow Control• Buffer optimization• Metal housing• Possibility to mount to the wall |
| Certificates: | CE, FCC |
| Housing: | Desktop, Metal |
| Power supply: | <ul style="list-style-type: none">• 52 V DC / 1.8 A (power adapter included) |
| Operation temp: | 0 °C ... 40 °C |
| Weight: | 0.28 kg |
| Dimensions: | 171 x 101 x 26 mm |
| Manufacturer / Brand: | UNIVIEW |
| Guarantee: | 2 years |

PRESENTATION

Front view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Rear view:



Bottom view:



In the kit:



PACKAGE

| | |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|