

Code: NSW2010-10T-POE-IN

## SWITCH POE **NSW2010-10T-POE-IN** 8-PORT UNIVIEW

Net: **131.57 EUR** Gross: **131.57 EUR**

Due to the reliability and ensuring high quality of transmission, the NSW2010-10T-POE-IN 8-port PoE switch is an ideal solution for applications in CCTV IP installations. 8 ports support Power over Ethernet (PoE) function.



### SPECIFICATION

|                       |                                                                                                                                                                                                                                                                                                                |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LAN ports:            | <ul style="list-style-type: none"><li>• 8 x RJ45 10/100 Base-T ( 8 x PoE (802.3af/at) ),</li><li>• 2 x RJ45 100 Base-T - Uplink</li></ul>                                                                                                                                                                      |
| Management:           | —                                                                                                                                                                                                                                                                                                              |
| LED diodes:           | Link/Act, PoE, Power                                                                                                                                                                                                                                                                                           |
| Transmission speed:   | <ul style="list-style-type: none"><li>• 100 Mbps : 2 LAN ports - Uplink,</li><li>• 10 / 100 Mbps : 8 LAN &amp; PoE ports</li></ul>                                                                                                                                                                             |
| Maximal output power: | 30 W / port PoE 802.3af/at                                                                                                                                                                                                                                                                                     |
| Maximal total power:  | 120 W                                                                                                                                                                                                                                                                                                          |
| MAC addresses table:  | 4k                                                                                                                                                                                                                                                                                                             |
| Operation modes:      | <ul style="list-style-type: none"><li>• Default : 100 m, 100 Mbps</li><li>• VLAN - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports</li><li>• Extend : 250 m, 10 Mbps</li></ul>                                                                                             |
| Main features:        | <ul style="list-style-type: none"><li>• EXTEND mode - ports 1, 2, 3, 4, 5, 6, 7, 8 support transmission up to 250 m</li><li>• Data Flow Control</li><li>• Buffer optimization</li><li>• Metal housing</li><li>• Possibility to mount to the wall</li><li>• MTBF (Mean Time Between Faults) : 50000 h</li></ul> |
| Certificates:         | CE, FCC                                                                                                                                                                                                                                                                                                        |
| Housing:              | Desktop, Metal                                                                                                                                                                                                                                                                                                 |
| Power supply:         | 100 ... 240 V AC, 50 / 60 Hz                                                                                                                                                                                                                                                                                   |
| Operation temp:       | 0 °C ... 45 °C                                                                                                                                                                                                                                                                                                 |
| Weight:               | 1.2 kg                                                                                                                                                                                                                                                                                                         |
| Dimensions:           | 220 x 150 x 44 mm                                                                                                                                                                                                                                                                                              |
| Manufacturer / Brand: | UNIVIEW                                                                                                                                                                                                                                                                                                        |
| Guarantee:            | 2 years                                                                                                                                                                                                                                                                                                        |

### PRESENTATION

Front panel:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



Rear panel:



In the kit:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|