

Code: PFS3110-8ET1GT1GF-96

SWITCH POE **PFS3110-8ET1GT1GF-96** 8-PORT SFP DAHUA

Net: **203.62 EUR** Gross: **203.62 EUR**

The device is perfect to build a network of IP cameras with power supply in the PoE 802.3af / 802.3at standard.



SPECIFICATION

LAN ports:	<ul style="list-style-type: none">• 8 x RJ45 10/100 Base-T (1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at)),• 1 x RJ45 10/100/1000 Base-T - Uplink,• 1 x Port SFP 1000 Base-X - Uplink
Management:	—
LED diodes:	Power, PoE, Link/Act, Uplink 1, Uplink 2
Transmission speed:	10 / 100 Mbps : 8 LAN & PoE ports , 10 / 100 / 1000 Mbps : 1 Port RJ45 (Uplink) , 1000 Mbps : 1 Port SFP (Uplink)
Maximal output power:	<ul style="list-style-type: none">• 90 W / port Hi-PoE / PoE 802.3bt - Port 1• 30 W / port PoE 802.3af/at - 2 ... 8 ports
Maximal total power:	96 W
MAC addresses table:	8k
Operation modes:	<ul style="list-style-type: none">• Extend On : 250 m, 10 Mbps• Extend Off : 100 m, 100 Mbps• PD Alive
Main features:	<ul style="list-style-type: none">• PoE power mode - The device supports 8-pin power supply• Ports marked in red support IEEE802.3af, IEEE802.3at, IEEE802.3bt and Hi-PoE standards with a maximum output power of 90 W per port - designed to power high power devices• Intelligent PoE power management - the device controls power consumption on individual ports• PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected• protection against lightning discharges and voltage differences and strokes between devices• Industrial wide temperature design.
Certificates:	CE, FCC
Housing:	Desktop, Metal
Power supply:	53 V DC / 1.81 A (power adapter included)
Operation temp:	-10 °C ... 55 °C
Weight:	0.58 kg
Dimensions:	240 x 105 x 28 mm

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Manufacturer / Brand:	DAHUA
Guarantee:	5 years

PRESENTATION

Front view:



1 - LAN + Hi-PoE (802.3bt)

2 - LAN + PoE

3 - Port RJ45 (Uplink)

4 - Port SFP (Uplink)

Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60