

Code: DS-3T0506HP-E/HS

# SWITCH POE **DS-3T0506HP-E/HS** 4-PORT SFP Hikvision

Net: **112.30 EUR** Gross: **112.30 EUR**

Due to reliability and ensuring high quality of transmission, the DS-3T0506HP-E/HS 10/100/1000 Mb/s 4-port PoE desktop type switch is perfect solution for expanding home or office network. 4 ports support the Power over Ethernet (PoE) function.

DS-3T0506HP-E/HS is designed to mount on the DIN 35 mm rail.



## SPECIFICATION

|                       |  |
|-----------------------|--|
| LAN ports:            | <ul style="list-style-type: none"><li>• 4 x RJ45 10/100/1000 Base-TX ( 1 x Hi-PoE (802.3af/at/bt) + 3 x PoE (802.3af/at) ),</li><li>• 2 x port SFP 1000 Base-X - Uplink</li></ul>  |
| Transmission speed:   | <ul style="list-style-type: none"><li>• 10 / 100 / 1000 Mbps - 4 LAN &amp; PoE ports,</li><li>• 1000 Mbps - 2 SFP (Uplink) ports</li></ul>   |
| Maximal output power: | <ul style="list-style-type: none"><li>• 60 W / port Hi-PoE - Port 1</li><li>• 30 W / port PoE - 2 ... 4 ports</li></ul>  |
| Maximal total power:  | 60 W   |
| MAC addresses table:  | 2k   |
| Management:           | —  |
| Operation modes:      | <ul style="list-style-type: none"><li>• Extend Off : 100 m, 1000 Mbps - 1 ... 4 ports</li><li>• Extend On : 300 m, 10 Mbps - 3, 4 ports</li><li>• Port Isolation : 1 ... 4 ports</li><li>• Watchdog PoE : 1 ... 4 ports</li></ul>  |
| LED diodes:           | Power, Link/Act, PoE, PoE Max, SFP - 5, 6 ports  |
| Main features:        | <ul style="list-style-type: none"><li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li><li>• Overvoltage protection : 6 kV - PoE ports</li><li>• EXTEND mode - 3, 4 ports</li><li>• The device supports 8-pin power supply : wires 1-2, 3-6, 4-5, 7-8</li><li>• Port isolation</li><li>• PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected</li></ul> |
| Certificates:         | CE, FCC, RoHS  |
| Housing:              | Metal  |
| Power supply:         | 48 V DC / 1.35 A (power adapter included)  |
| Power consumption:    | max. 65 W  |
| Operation temp:       | -30 °C ... 65 °C   |
| Weight:               | 0.36 kg  |
| Dimensions:           | 158 x 104 x 32 mm  |
| Manufacturer / Brand: | Hikvision  |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|            |                |
|------------|----------------|
| SAP Code:  | 301801602      |
| Guarantee: | <b>3 years</b> |

## PRESENTATION

Front view:



- 1 - LAN + Hi-PoE
- 2 - LAN + PoE
- 3 - LAN + PoE
- 4 - LAN + PoE
- 5 - SFP
- 6 - SFP

Mounting side view:



Side view:



The device can be mounted vertically on a DIN TS-35 rail:



In the kit:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|