

Code: CS4010-8GT-110

SWITCH POE **CS4010-8GT-110** 8-PORT DAHUA

Net: **268.82 EUR** Gross: **268.82 EUR**

Due to reliability and ensuring high quality of transmission, the CS4010-8GT-110 10/100/1000 Mb/s 8-port PoE desktop type switch is perfect solution for expanding home or office network. 8 ports support Power over Ethernet (PoE) function.

Switch is managed through the web and the cloud (DoLink Care application).



SPECIFICATION

LAN ports:	• 8 x RJ45 10/100/1000 Base-T (1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink
Transmission speed:	• 10 / 100 / 1000 Mbps : 8 LAN & PoE ports, • 10 / 100 / 1000 : 2 Uplink ports
Maximal output power:	• 90 W / port Hi-PoE / PoE 802.3bt - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 8 ports
Maximal total power:	110 W
MAC addresses table:	8k
Management:	✓
Operation modes:	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6
LED diodes:	Power, System, PoE, Link/Act
Main features:	• Switch is managed through the web and the cloud (DoLink Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Spanning Tree STP/RSTP • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Possibility to mount to the wall
Certificates:	CE
Protections:	• Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV
Housing:	Desktop, Metal
Power supply:	54 V DC / 2.22 A (power adapter included)
Power consumption:	max. 110 W
Operation temp:	-10 °C ... 55 °C

Weight:	0.52 kg
Dimensions:	190 x 106 x 30 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

Front view:



Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------