

Code: RG-ES110D-P

## SWITCH POE **RG-ES110D-P** 8-PORT REYEE

Net: **91.29 EUR** Gross: **91.29 EUR**

Due to the reliability and ensuring high quality of transmission, the RG-ES110D-P 8-port PoE switch is an ideal solution for applications in CCTV IP installations. 8 ports support Power over Ethernet (PoE) function.



### SPECIFICATION

|                           |                                                                                                                                                                                                                                                                                                                                                                          |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LAN ports:                | <ul style="list-style-type: none"><li>• 8 x RJ45 10/100 Base-T ( 8 x PoE (802.3af/at) ),</li><li>• 2 x RJ45 10/100/1000 Base-T - Uplink</li></ul>                                                                                                                                                                                                                        |
| Management:               | —                                                                                                                                                                                                                                                                                                                                                                        |
| Number of fan coolers:    | —                                                                                                                                                                                                                                                                                                                                                                        |
| LED diodes:               | Power, PoE, Link/Act                                                                                                                                                                                                                                                                                                                                                     |
| Transmission speed:       | <ul style="list-style-type: none"><li>• 10 / 100 Mbps : 8 LAN &amp; PoE ports</li><li>• 10 / 100 / 1000 Mbps : 2 Uplink ports</li></ul>                                                                                                                                                                                                                                  |
| Maximal output power:     | 30 W / port PoE                                                                                                                                                                                                                                                                                                                                                          |
| Maximal total power:      | 110 W                                                                                                                                                                                                                                                                                                                                                                    |
| Switching performance:    | 5.6 Gb/s                                                                                                                                                                                                                                                                                                                                                                 |
| Packet redirection speed: | 4.17 Mpps                                                                                                                                                                                                                                                                                                                                                                |
| MAC addresses table:      | 2k                                                                                                                                                                                                                                                                                                                                                                       |
| Mobile phones support:    | Android: Free application <a href="#">Ruijie Reyee</a><br>iOS (iPhone): Free application <a href="#">Ruijie Reyee</a>                                                                                                                                                                                                                                                    |
| Operation modes:          | <ul style="list-style-type: none"><li>• Flow Control ON - Data flow control is enabled and all ports can communicate with each other,</li><li>• Flow Control OFF - Data flow control is disabled and all ports can communicate with each other,</li><li>• Port Isolation - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports</li></ul> |
| Main features:            | <ul style="list-style-type: none"><li>• View device status</li><li>• protection against lightning discharges and voltage differences and strokes between devices</li><li>• Grounding</li><li>• MTBF (Mean Time Between Faults) &gt; 200 000 h</li><li>• IEEE 802.3az - 1 ... 8 ports</li><li>• IEEE802.3x Flow Control</li></ul>                                         |
| Certificates:             | CE, RoHS                                                                                                                                                                                                                                                                                                                                                                 |
| Protections:              | Protection against lightning discharges : 6 kV                                                                                                                                                                                                                                                                                                                           |
| Housing:                  | Desktop, Metal                                                                                                                                                                                                                                                                                                                                                           |

|                       |                                             |
|-----------------------|---------------------------------------------|
| Power supply:         | 53.5 V DC / 2.24 A (power adapter included) |
| Power consumption:    | ≤ 129 W                                     |
| Operation temp:       | 0 °C ... 45 °C                              |
| Weight:               | 0.52 kg                                     |
| Dimensions:           | 191 x 105 x 28 mm                           |
| Manufacturer / Brand: | RUIJIE / REYEE                              |
| Guarantee:            | 3 years                                     |

PRESENTATION

Front panel:



Rear view:



In the kit:



PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|