

Code: RG-ES210GS-P

SWITCH POE **RG-ES210GS-P** 8-PORT REYEE

Net: **175.54 EUR** Gross: **175.54 EUR**

Due to the reliability and ensuring high quality of transmission, the RG-ES210GS-P 8-port PoE switch is an ideal solution for applications in CCTV IP installations. 8 ports support Power over Ethernet (PoE) function.



SPECIFICATION

LAN ports:	• 8 x RJ45 10/100/1000 Base-T (8 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink • 1 x port SFP 1000 Base-X - Uplink
Management:	✓
Number of fan coolers:	—
LED diodes:	STATUS indicator, PoE, Link/Act
Transmission speed:	10 / 100 / 1000 Mbps : 8 LAN & PoE ports + 2 Uplink ports 1000 Mbps - port SFP
Maximal total power:	120 W
Switching performance:	20 Gb/s
Packet redirection speed:	14.8 Mpps
MAC addresses table:	4k
Mobile phones support:	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Default IP address:	10.44.77.200
Main features:	• Switch is managed through the web and the cloud (Ruijie Reyee application) • Supports up to 16 VLANs at the same time (for 4K ID VLAN addresses) • DHCP client • DHCP snooping support • Port mirroring function • Loop Protection • IEEE802.3x Flow Control • MTBF (Mean Time Between Faults) > 200.000 h
Certificates:	CE, RoHS
Protections:	Protection against lightning discharges : 4 kV
Housing:	Desktop, Metal
Power supply:	54 V DC / 2.4 A (power adapter included)
Power consumption:	≤ 130 W
Operation temp:	0 °C ... 45 °C
Weight:	0.55 kg

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Dimensions:	202 x 104 x 28 mm
Manufacturer / Brand:	RUIJIE / REYEE
Guarantee:	3 years

PRESENTATION

Front panel:



Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------