

Code: CS4006-4GT-60

SWITCH POE **CS4006-4GT-60** 4-PORT DAHUA

Net: **143.45 EUR** Gross: **143.45 EUR**

Due to reliability and ensuring high quality of transmission, the CS4006-4GT-60 10/100/1000 Mb/s 4-port PoE desktop type switch is perfect solution for expanding home or office network. Four ports support Power over Ethernet (PoE) function.

Switch is managed through the web and the cloud (DoLynk Care application).



SPECIFICATION

LAN ports:	<ul style="list-style-type: none">• 4 x RJ45 10/100/1000 Base-T (1 x Hi-PoE + 3 x PoE (802.3af/at)),• 2 x RJ45 10/100/1000 Base-T - Uplink
Transmission speed:	<ul style="list-style-type: none">• 10 / 100 / 1000 Mbps : 4 LAN & PoE ports,• 10 / 100 / 1000 Mbps : 2 Uplink ports
Maximal output power:	<ul style="list-style-type: none">• 60 W / port Hi-PoE - Port 1• 30 W / port PoE 802.3af/at - 2 ... 4 ports
Maximal total power:	60 W
MAC addresses table:	8k
Management:	✓
Operation modes:	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6
LED diodes:	Power, System, PoE, Link/Act
Main features:	<ul style="list-style-type: none">• Switch is managed through the web and the cloud (DoLynk Care application)• PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-)• Intelligent management of Power Supply Unit power's output stage• protection against lightning discharges and voltage differences and strokes between devices• Watchdog PoE• Loop Protection• Compliance with the LLDP protocol• Port Based VLAN : 32• Data Flow Control (802.3x)• DHCP client• RESET button• Kensington Lock• Possibility to mount to the wall
Certificates:	CE
Protections:	<ul style="list-style-type: none">• Protection against lightning discharges (common/differential) : 4 / 2 kV• Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV
Housing:	Desktop, Metal
Power supply:	53 V DC / 1.22 A (power adapter included)

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Power consumption:	max. 65 W
Operation temp:	-10 °C ... 55 °C
Weight:	0.3 kg
Dimensions:	130 x 90 x 26 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

Front view:



- 1 - LAN + Hi-PoE
 - 2 - LAN + PoE
 - 3 - LAN + PoE
 - 4 - LAN + PoE
 - 5 - Uplink
 - 6 - Uplink
- Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

