

Code: RS-108

## SWITCH PoE TO RACK CABINET **RS-108** 10-PORT PULSAR

Net: **161.21 USD** Gross: **198.29 USD**

The RS-108 PoE Switch is an industrial type device enabling fluent network transmission at rates 10 / 100 Mbps. PoE/PoE+ powering possibility, compatible with the 802.3af/at standard makes the device more universal and easier to install.  
The device is mounted to RACK 19" cabinet.



### SPECIFICATION

Standards:	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at
Protocols:	CSMA/CD, TCP/IP
Management via WWW / console:	—
LAN ports:	<ul style="list-style-type: none"><li>• 8 x RJ45 ( 8 x PoE (802.3af/at) ),</li><li>• 2 x RJ45 - Uplink</li></ul>
Transmission method:	Store and Forward
LED diodes:	Power, PoE, Link/Act
Transmission speed:	10 / 100 Mb/s - 8 x LAN & PoE ports 10 / 100 Mb/s - 2 x Uplink ports
Maximal output power:	30 W / port PoE+
Maximal total power:	96 W
MAC addresses table:	1k - Auto update of MAC addresses table
Main features:	<ul style="list-style-type: none"><li>• Auto-learning and Auto-aging functions support for MAC addresses</li><li>• (RJ45) 10/100 Mb Auto-Negotiation, Auto MDI/MDIX</li><li>• Industrial wide temperature design.</li></ul>
Certificates:	CE
Power supply:	230 V AC
Housing:	Steel - powder painted
Color:	Black (RAL 9005)
Housing type:	RACK 19", 1U
Operation temp:	-20 °C ... 60 °C
Weight:	2.7 kg
Dimensions:	482 x 227 x 44 mm
Manufacturer / Brand:	PULSAR
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

## PRESENTATION

Front view:



Connectors:



1 2 3 4 5 6 7 8 9 10

1. LAN + PoE
2. LAN + PoE
3. LAN + PoE
4. LAN + PoE
5. LAN + PoE
6. LAN + PoE
7. LAN + PoE
8. LAN + PoE
9. LAN
10. LAN

Top view:



In the kit:

