

Code: PFS4228-24P-370

Switch PoE **PFS4228-24P-370** 24-PORT +SFP DAHUA

Net: **859.68 EUR** Gross: **1 057.41 EUR**

The DH-PFS4220-16T switch is designed for large streams of video data in the CCTV IP surveillance networks. Attention! The SFP port requires the SFP module, which is available in our offer.



SPECIFICATION

Standards:	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3x, IEEE 802.1x, IEEE 802.1Q VLAN, IEEE 802.3af, IEEE 802.3at
Management via WWW / console:	✓
LAN ports:	<ul style="list-style-type: none">• 2 x port SFP 1000 Base-X• 2 x RJ45 10/100/1000 Base-T• 24 x RJ45 10/100 Base-T (24 x PoE (802.3af/at))
Transmission speed:	<ul style="list-style-type: none">• 10 / 100 Mbps - 24 LAN & PoE ports• 10 / 100 / 1000 Mbps - 2 Uplink ports• 1000 Mbps - 2 SFP ports
Maximal output power:	30 W / port PoE
Maximal total power:	370 W
MAC addresses table:	16k
Transmission method:	Store and Forward
Main features:	<ul style="list-style-type: none">• Switch is web managed• IEEE 802.1Q VLAN• Spanning Tree STP/RSTP• Full Duplex: PAUSE frame, Half Duplex: Back Pressure• IGMP Snooping• Hardware supports IP + MAC binding based on port• IEEE 802.1x port authentication• Upload and download configuration file• System logs• protection against lightning discharges and voltage differences and strokes between devices
LED diodes:	Power, Link/Act, Console
Certificates:	CE
Power supply:	100 ... 240 V AC
Operation temp:	-10 °C ... 55 °C
Weight:	3.836 kg
Dimensions:	442 x 265 x 45 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Front panel:



Rear panel:



In the kit:

