

Code: DS-3E0326P-E/M(B)

SWITCH POE **DS-3E0326P-E/M(B)** 24-PORT SFP Hikvision

Net: **324.81 EUR** Gross: **399.52 EUR**

The DS-3E0326P-E/M(B) switch is designed for large streams of video data in the CCTV IP surveillance networks.

Attention! The SFP port requires the SFP module, which is available in our offer.



SPECIFICATION

LAN ports:	<ul style="list-style-type: none">• 24 x RJ45 10/100 Base-TX (24 x PoE (802.3af/at)),• 1 x port SFP - Uplink,• 1 x RJ45 - Uplink
Transmission speed:	<ul style="list-style-type: none">• 10 / 100 Mbps - 24 LAN & PoE ports,• 10 / 100 / 1000 Mbps - 2 Uplink ports
Maximal output power:	30 W / port PoE
Maximal total power:	230 W
MAC addresses table:	4k
Management:	—
Main features:	<ul style="list-style-type: none">• Extend - 17 ... 24 ports : 300 m, 10 Mbps @ UTP cat. 5e, 6• Support of the 3 network modes: Priority, Standard, Extend• protection against lightning discharges and voltage differences and strokes between devices• High priority ports : 1 ... 8 ports - Dedicated to video transmission• PoE power mode : The device supports 8-pin power supply
LED diodes:	Power, Link/Act, PoE, G2, PoE Max
Certificates:	CE
Power supply:	100 ... 240 V AC
Operation temp:	-10 °C ... 55 °C
Weight:	2.54 kg
Dimensions:	335 x 226 x 45 mm
Manufacturer / Brand:	Hikvision
SAP Code:	301801300
Guarantee:	3 years

PRESENTATION

Front panel:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



1-24: LAN & PoE ports
G1: Port Uplink
G2: Port Uplink
Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60