

Code: TL-SG2428P

SWITCH POE TL-SG2428P 24-PORT SFP TP-LINKNet: **232.19 EUR** Gross: **285.59 EUR**

Due to the reliability and ensuring high quality of transmission, the TL-SG2428P 24-port PoE switch is an ideal solution for applications in CCTV IP installations. 24 ports support the Power over Ethernet (PoE) function. PoE powering possibility, compatible with the 802.3af/at standard makes the device more universal and easier to install.

**SPECIFICATION**

Standards:	IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3ad, IEEE 802.3x, IEEE 802.3az IEEE 802.1d, IEEE 802.1s, IEEE 802.1w, IEEE 802.1q, IEEE 802.1p, IEEE 802.1x
Management via WWW / console:	✓
LAN ports:	<ul style="list-style-type: none"> • 4x port SFP - Uplink 10/100/1000 Mb/s, • 24x RJ45 - 10/100/1000 Base-TX + PoE (802.3af/at)
LED diodes:	Power, Link/Act, 1000 Mbps, PoE, PoE Max, System, Fan
Transmission speed:	<ul style="list-style-type: none"> • Ethernet - 10 Mbps • Fast Ethernet - 100 Mbps • Gigabit Ethernet - 1000 Mbps
Maximal output power:	30 W / port PoE
Maximal total power:	250 W
MAC addresses table:	8k
Main features:	<ul style="list-style-type: none"> • Omada Central Management System • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • SFP ports • Can be mounted in a Rack 19" cabinet • QoS - mechanisms, which provide the high quality of transmission • CoS/DSCP priority based on IEEE 802.1p standard • Queue scheduling: SP, WRR, SP+WRR • Rate limit • Limitation of the transmission speed • Storm Control function • Static routing • Static link aggregation • Loop back detection • Data Flow Control (802.3x) • Port mirroring function • DHCP snooping support • Multicast • IEEE802.1Q VLAN support • Access control • IEEE 802.1x and Radius Authentication • IPv6 compliance • Hardware supports IP + MAC binding based on port • Support DoS defence
Housing:	Metal

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Operation temp:	0 °C ... 50 °C
Certificates:	FCC Class A, CE, RoHS
Power supply:	100 ... 240 V AC
Power consumption:	max. 32.1 W max. 308.6 W (PoE 250 W)
Weight:	3.23 kg
Dimensions:	440 x 225 x 45 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	3 years

PRESENTATION

Front view:



Rear view:



In the kit:

