

Code: DS-3E1326P-EI

SWITCH POE **DS-3E1326P-EI** 24-PORT SFP Hikvision

Net: **1 800.00 PLN** Gross: **2 214.00 PLN**

The DS-3E1326P-EI switch is designed for large streams of video data in the CCTV IP surveillance networks.

Attention! The SFP port requires the SFP module, which is available in our offer.



SPECIFICATION

LAN ports:	<ul style="list-style-type: none">• 2 x port Combo: SFP (Base-X) / RJ45 (Base-T)• 24 x RJ45 10/100 Base-T (24 x PoE (802.3af/at))
Transmission speed:	<ul style="list-style-type: none">• 10 / 100 Mbps - 24 LAN & PoE ports• 10 / 100 / 1000 Mbps - 2 Uplink ports• 1000 Mbps - 2 SFP ports
Maximal output power:	30 W / port PoE
Maximal total power:	370 W
MAC addresses table:	16k
Management via WWW / console:	—
Default IP address:	192.168.1.64
Default admin user / password:	admin / -
Operation modes:	<ul style="list-style-type: none">• Extend On : 300 m, 10 Mbps @ UTP cat. 5e, 6• Extend Off : 100 m, 100 Mbps @ UTP cat. 5e, 6
Main features:	<ul style="list-style-type: none">• protection against lightning discharges and voltage differences and strokes between devices• High priority ports : 1 ... 8• Configuration and management from the iVMS-4200 application• View topology and network status• Possibility of aggregation of G1, G2 ports
LED diodes:	Power, Link/Act, PoE, PoE Max, G1, G2
Certificates:	CE
Power supply:	100 ... 240 V AC
Operation temp:	-10 °C ... 55 °C
Weight:	2.84 kg
Dimensions:	440 x 221 x 44 mm
Manufacturer / Brand:	Hikvision
SAP Code:	301801790
Guarantee:	3 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Front panel:



Rear panel:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------