

Code: PFS4218-16ET-240-V2

SWITCH POE **PFS4218-16ET-240-V2** 16-PORT SFP DAHUA

Net: **476.95 EUR** Gross: **586.65 EUR**

Due to reliability and ensuring high quality of transmission, the PFS4218-16ET-240-V2 10/100 Mb/s 16-port PoE desktop type switch is perfect solution for expanding home or office network.

Attention! The SFP port requires the SFP module, which is available in our offer.



SPECIFICATION

LAN ports:	<ul style="list-style-type: none">• 16 x RJ45 - 10/100 Base-T (14 PoE (802.3af/at) + 2 Hi-PoE / port Hi-PoE / PoE 802.3bt / PoE (802.3af/at))• 2 x Uplink (port SFP - 1000 Base-X / RJ45 - 10/100/1000 Base-T)
Management via WWW / console:	✓
Transmission speed:	<ul style="list-style-type: none">• Ethernet - 10 Mbps Full Duplex• Fast Ethernet - 100 Mbps Full Duplex• Gigabit Ethernet - 1000 Mbps Full Duplex (Uplink)
Maximal output power:	<ul style="list-style-type: none">• 30 W / port PoE• 90 W / port Hi-PoE / port Hi-PoE / PoE 802.3bt
Maximal total power:	240 W
MAC addresses table:	4k
Main features:	<ul style="list-style-type: none">• Switch is web managed• Intelligent management of Power Supply Unit power's output stage protection against lightning discharges and voltage differences and strokes between devices• IEEE 802.1Q VLAN• PoE Watchdog / Tryb PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected• Ports marked in red support IEEE802.3af, IEEE802.3at, IEEE802.3bt and Hi-PoE standards with a maximum output power of 90 W per port - designed to power high power devices• Range PoE : 250 m• The device supports 8-pin power supply
LED diodes:	Power : 50 % / 80 % / 100 %, Link, PoE, System
Certificates:	CE
Power supply:	100 ... 240 V AC
Housing type:	RACK 19", 1U
Operation temp:	-10 °C ... 55 °C
Weight:	3.2 kg
Dimensions:	440 x 300 x 44 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Front view:



Rear view:



In the kit:

