

Code: DS-3E1518P-SI

SWITCH POE **DS-3E1518P-SI** 16-PORT SFP Hikvision

Net: **380.50 EUR** Gross: **380.50 EUR**

The DS-3E1518P-SI switch is designed for large streams of video data in the CCTV IP surveillance networks.

Attention! The SFP port requires the SFP module, which is available in our offer.



SPECIFICATION

LAN ports:	• 16 x RJ45 10/100/1000 Base-T (16 x PoE (802.3af/at)), • 2 x port SFP 1000 Base-X
Transmission speed:	• 10 / 100 / 1000 Mbps - 16 LAN & PoE ports, • 1000 Mbps - 2 SFP ports - Uplink
Maximal output power:	30 W / port PoE
Maximal total power:	225 W
MAC addresses table:	8k
Management:	✓
Default IP address:	192.168.1.64
Default admin user / password:	admin / -
Operation modes:	• Extend On : 300 m, 10 Mbps @ UTP cat. 5e, 6 • Extend Off : 100 m, 1000 Mbps @ UTP cat. 5e, 6
Main features:	• Switch is web managed • Configuration and management from the iVMS-4200 application • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • View topology and network status • Data Flow Control • Storm Control function • Port mirroring function • Static link aggregation • QoS : Queue scheduling: SP, WRR, SP+WRR • VLAN • Spanning Tree STP/RSTP • SNMPv1/v2c • Watchdog PoE • The device supports 8-pin power supply • Remote configuration • Remote update of software • Can be mounted in a Rack 19" cabinet
LED diodes:	Power, Link/Act, PoE, PoE Max, 17 SFP, 18 SFP
Certificates:	CE
Housing:	Metal
Protections:	Overvoltage 6 kV - PoE ports
Power supply:	100 ... 240 V AC
Operation temp:	-10 °C ... 55 °C

Weight:	2.74 kg
Dimensions:	440 x 221 x 44 mm, RACK 19", 1U
Manufacturer / Brand:	Hikvision
SAP Code:	301802030
Guarantee:	3 years

PRESENTATION

Front panel:



1-16: LAN & PoE ports
17,18 SFP ports
Rear panel:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------